# Linux From Scratch

# Table of Contents

**Linux From Scratch....1**
Gerard Beekmans....1

**Dedication....2**

**Preface....8**

**Who would want to read this book....9**

**Who would not want to read this book....10**

**Organization....11**
Part I – Introduction....11
Part II – Installation of a basic system on Intel systems....11
Part III – Installation of a basic system on Apple PowerPC systems....11
Part IV – Appendixes....11

**I. Part I – Introduction....12**

**Chapter 1. Introduction....13**

**Introduction....14**

**How things are going to be done....15**

**Book versions....16**

**Acknowledgements....17**

**Changelog....18**

**Mailinglists and archives....25**
lfs-discuss....25
lfs-config....25
lfs-apps....25
lfs-announce....26
linux....26
alfs-discuss....26
How to subscribe?....26
How to unsubscribe?....27
Mail archives....27

**Contact information....28**

**Chapter 2. Important information....29**

**About $LFS....30**

# Table of Contents

**How to download the software....31**

**How to install the software....32**

**II. Part II – Installing LFS on Intel systems....34**

**Chapter 3. Packages you need to download....35**

**Chapter 4. Preparing a new partition....39**

**Introduction....40**

**Creating a new partition....41**

**Creating a ext2 file system on the new partition....42**

**Mounting the new partition....43**

**Creating directories....44**

**Chapter 5. Installing basic system software....46**

**How and why things are done....47**

**Debugging symbols and compiler optimizations....48**

**Preparing the LFS system....50**

**Installing Bash....51**
- Installing Bash....51
- Contents....51
- Description....51

**Installing Binutils....52**
- Installing Binutils....52
- Description....52
- Description....52
  - ld....52
  - as....52
  - ar....52
  - nm....52
  - objcopy....53
  - objdump....53
  - ranlib....53
  - size....53
  - strings....53
  - strip....53
  - c++filt....53

# Table of Contents

addr2line....54
nlmconv....54

**Installing Bzip2....55**
Installing Bzip2....55
Contents....55
Description....55
Bzip2....55
Bunzip2....55
bzcat....55
bzip2recover....56

**Installing Diffutils....57**
Installing Diffutils....57
Contents....57
Description....57
cmp and diff....57
diff3....57
sdiff....57

**Installing Fileutils....58**
Installing Fileutils....58
Contents....58
Description....58
chgrp....58
chmod....58
chown....58
cp....59
dd....59
df....59
ls, dir and vdir....59
dircolors....59
du....59
install....59
ln....59
mkdir....60
mkfifo....60
mknod....60
mv....60
rm....60
rmdir....60
sync....60
touch....60

**Installing GCC on the normal system if necessary....61**
Installing GCC on the normal system if necessary....61
Contents....61
Description....61

# Table of Contents

Compiler....62
Pre−processor....62
C++ Library....62

**Installing GCC on the LFS system....63**
Installing GCC on the LFS system....63
Creating necessary symlinks....63
Contents....63
Description....64
Compiler....64
Pre−processor....64
C++ Library....64

**Installing Linux Kernel....65**
Installing Linux Kernel....65
Contents....65
Description....65

**Installing Glibc....67**
A note on the glibc−crypt package....67
Installing Glibc....67
Copying old NSS library files....68
Contents....69
Description....69

**Installing Grep....70**
Installing Grep....70
Contents....70
Description....70
egrep....70
fgrep....70
grep....70

**Installing Gzip....71**
Installing Gzip....71
Contents....71
Description....71
gunzip....71
gzexe....72
gzip....72
zcat....72
zcmp....72
zdiff....72
zforce....72
zgrep....72
zmore....72
znew....73

# Table of Contents

**Installing Make....74**
Installing Make....74
Contents....74
Description....74

**Installing Sed....75**
Installing Sed....75
Contents....75
Description....75

**Installing Shellutils....76**
Installing Shellutils....76
Contents....76
Description....76
basename....76
chroot....76
date....76
dirname....76
echo....77
env....77
expr....77
factor....77
false....77
groups....77
hostid....77
hostname....77
id....77
logname....78
nice....78
nohup....78
pathchk....78
pinky....78
printenv....78
printf....78
pwd....78
seq....78
sleep....79
stty....79
su....79
tee....79
test....79
true....79
tty....79
uname....79
uptime....79
users....80
who....80
whoami....80

# Table of Contents

yes....80

**Installing Tar....81**
Installing Tar....81
Contents....81
Description....81
tar....81
rmt....81

**Installing Textutils....82**
Installing Textutils....82
Contents....82
Description....82
cat....82
cksum....82
comm....82
csplit....82
cut....83
expand....83
fmt....83
fold....83
head....83
join....83
md5sum....83
nl....83
od....83
paste....84
pr....84
ptx....84
sort....84
split....84
sum....84
tac....84
tail....84
tr....84
tsort....85
unexpand....85
uniq....85
wc....85

**Creating passwd and group files....86**

**Copying /proc/devices....87**

**Installing basic system software....88**

**Entering the chroot'ed environment....89**

# Table of Contents

**Creating device files....90**
Installing MAKEDEV....90
Creating the /dev entries....90

**Installing Ed....91**
Installing Ed....91
Contents....91
Description....91

**Installing Patch....92**
Installing Patch....92
Contents....92
Description....92

**Installing GCC....93**
Installing GCC....93
Contents....93
Description....93
Compiler....93
Pre−processor....93
C++ Library....93

**Installing Bison....95**
Installing Bison....95
Contents....95
Description....95

**Installing Mawk....97**
Installing Mawk....97
Contents....97
Description....97
gawk....97

**Installing Findutils....98**
Installing Findutils....98
Contents....98
Description....98
Find....98
Locate....98
Updatedb....99
Xargs....99

**Installing Ncurses....100**
Installing Ncurses....100
Contents....100
Description....100
The libraries....100
Tic....100

# Table of Contents

Infocmp....100
clear....101
tput....101
toe....101
tset....101

**Installing Less....102**
Installing Less....102
Contents....102
Description....102

**Installing Groff....103**
Installing Groff....103
Contents....103
Description....103
addftinfo....103
afmtodit....103
eqn....103
grodvi....103
groff....104
grog....104
grohtml....104
grolj4....104
grops....104
grotty....104
hpftodit....104
indxbib....104
lkbib....104
lookbib....105
neqn....105
nroff....105
pfbtops....105
pic....105
psbb....105
refer....105
soelim....105
tbl....106
tfmtodit....106
troff....106

**Installing Man....107**
Installing Man....107
Contents....107
Description....107
man....107
apropos....107
whatis....107
makewhatis....107

# Table of Contents

**Installing Perl....108**
Installing Perl....108
Contents....108
Description....108

**Installing M4....109**
Installing M4....109
Contents....109
Description....109

**Installing Texinfo....110**
Installing Texinfo....110
Contents....110
Description....110
info....110
install-info....110
makeinfo....110
texi2dvi....110
texindex....111

**Installing Autoconf....112**
Installing Autoconf....112
Contents....112
Description....112
autoconf....112
autoheader....112
autoreconf....112
autoscan....112
autoupdate....113
ifnames....113

**Installing Automake....114**
Installing Automake....114
Contents....114
Description....114
aclocal....114
automake....114

**Installing Bash....115**
Installing Bash....115
Contents....115
Description....115

**Installing Flex....116**
Installing Flex....116
Contents....116
Description....116

# Table of Contents

**Installing File....117**
Installing File....117
Contents....117
Description....117

**Installing Gettext....118**
Installing Gettext....118
Contents....118
Description....118
gettext....118

**Installing Libtool....119**
Installing Libtool....119
Contents....119
Description....119
libtool....119
libtoolize....119
ltdl library....119

**Installing Consoletools....120**
Installing Console−tools....120
Contents....120
Description....120
charset....120
chvt....120
codepage....120
consolechars....121
deallocvt....121
dumpkeys....121
fgconsole....121
fix_bs_and_del....121
font2psf....121
getkeycodes....121
kbd_mode....121
loadkeys....121
loadunimap....122
mapscrn....122
mk_modmap....122
openvt....122
psfaddtable....122
psfgettable....122
psfstriptable....122
resizecons....122
saveunimap....122
screendump....123
setfont....123
setkeycodes....123
setleds....123

# Table of Contents

setmetamode....123
setvesablank....123
showcfont....123
showkey....123
splitfont....123
unicode_start....124
unicode_end....124
vcstime....124
vt−is−UTF8....124
writevt....124

**Installing Consoledata....125**
Installing Console−data....125
Contents....125

**Installing Binutils....126**
Installing Binutils....126
Description....126
Description....126
ld....126
as....126
ar....126
nm....126
objcopy....127
objdump....127
ranlib....127
size....127
strings....127
strip....127
c++filt....127
addr2line....128
nlmconv....128

**Installing Bzip2....129**
Installing Bzip2....129
Contents....129
Description....129
Bzip2....129
Bunzip2....130
bzcat....130
bzip2recover....130

**Installing Diffutils....131**
Installing Diffutils....131
Contents....131
Description....131
cmp and diff....131
diff3....131

# Table of Contents

sdiff....131

**Installing E2fsprogs....132**
Installing E2fsprogs....132
Contents....132
Description....132
chattr....132
lsattr....132
uuidgen....132
badblocks....132
debugfs....133
dumpe2fs....133
e2fsck and fsck.ext2....133
e2label....133
fsck....133
mke2fs and mkfs.ext2....133
mklost+found....133
tune2fs....133

**Installing Fileutils....134**
Installing Fileutils....134
Contents....134
Description....134
chgrp....134
chmod....134
chown....134
cp....135
dd....135
df....135
ls, dir and vdir....135
dircolors....135
du....135
install....135
ln....135
mkdir....136
mkfifo....136
mknod....136
mv....136
rm....136
rmdir....136
sync....136
touch....136

**Installing Grep....137**
Installing Grep....137
Contents....137
Description....137
egrep....137

# Table of Contents

fgrep....137
grep....137

**Installing Gzip....138**
Installing Gzip....138
Contents....138
Description....138
gunzip....138
gzexe....138
gzip....138
zcat....138
zcmp....139
zdiff....139
zforce....139
zgrep....139
zmore....139
znew....139

**Installing Ldso....140**
Installing Ld.so....140
Contents....140
Description....140
ldconfig....140
ldd....141

**Installing Bin86....142**
Installing Bin86....142
Contents....142
Description....142
as86....142
as86_encap....142
ld86....142
objdump86....142
nm86....143
size86....143

**Installing Lilo....144**
Installing Lilo....144
Contents....144
Description....144

**Installing Make....145**
Installing Make....145
Contents....145
Description....145

**Installing Shellutils....146**
Installing Shell Utils....146

# Table of Contents

Contents....146
Description....146
basename....146
chroot....146
date....146
dirname....146
echo....147
env....147
expr....147
factor....147
false....147
groups....147
hostid....147
hostname....147
id....147
logname....148
nice....148
nohup....148
pathchk....148
pinky....148
printenv....148
printf....148
pwd....148
seq....148
sleep....149
stty....149
su....149
tee....149
test....149
true....149
tty....149
uname....149
uptime....149
users....150
who....150
whoami....150
yes....150

**Installing Shadowpwd....151**
Installing Shadow Password Suite....151
Contents....151
Description....151
chage....151
chfn....151
chsh....151
expiry....152
faillog....152
gpasswd....152

# Table of Contents

lastlog....152
login....152
newgrp....152
passwd....152
sg....152
su....152
chpasswd....153
dpasswd....153
groupadd....153
groupdel....153
groupmod....153
grpck....153
grpconv....153
grpunconv....153
logoutd....153
mkpasswd....154
newusers....154
pwck....154
pwconv....154
pwunconv....154
useradd....154
userdel....154
usermod....154
vipw and vigr....154

**Installing Modutils....155**
Installing Modutils....155
Contents....155
Description....155
depmod....155
genksyms....155
insmod....155
insmod_ksymoops_clean....155
kerneld....156
kernelversion....156
ksyms....156
lsmod....156
modinfo....156
modprobe....156
rmmod....156

**Installing Procinfo....157**
Installing Procinfo....157
Contents....157
Description....157

**Installing Procps....158**
Installing Procps....158

# Table of Contents

Contents....158
Description....158
free....158
kill....158
oldps and ps....158
skill....159
snice....159
sysctl....159
tload....159
top....159
uptime....159
vmstat....159
w....159
watch....159

**Installing Psmisc....160**
Installing Psmisc....160
Contents....160
Description....160
fuser....160
killall....160
pstree....160

**Installing Sed....161**
Installing Sed....161
Contents....161
Description....161

**Installing Vim....162**
Installing Vim....162
Contents....162
Description....162
ctags....162
etags....162
ex....162
gview....163
gvim....163
rgview....163
rgvim....163
rview....163
rvim....163
view....163
vim....163
vimtutor....163
xxd....164

**Installing Sysklogd....165**
Installing Sysklogd....165

# Table of Contents

Contents....165
Description....165
klogd....165
syslogd....165

**Installing Sysvinit....166**
Installing Sysvinit....166
Contents....166
Description....166
pidof....166
last....166
lastb....166
mesg....166
utmpdump....167
wall....167
halt....167
init....167
killall5....167
poweroff....167
reboot....167
runlevel....167
shutdown....168
sulogin....168
telinit....168

**Installing Tar....169**
Installing Tar....169
Contents....169
Description....169
tar....169
rmt....169

**Installing Textutils....170**
Installing Textutils....170
Contents....170
Description....170
cat....170
cksum....170
comm....170
csplit....170
cut....171
expand....171
fmt....171
fold....171
head....171
join....171
md5sum....171
nl....171

# Table of Contents

od....171
paste....172
pr....172
ptx....172
sort....172
split....172
sum....172
tac....172
tail....172
tr....172
tsort....173
unexpand....173
uniq....173
wc....173

**Installing Utillinux....174**
Installing Util–Linux....174
Contents....174
Description....175
arch....175
dmesg....175
kill....175
more....175
mount....175
umount....175
agetty....175
blockdev....175
cfdisk....176
ctrlaltdel....176
elvtune....176
fdisk....176
fsck.minix....176
hwclock....176
kbdrate....176
losetup....176
mkfs....176
mkfs.bfs....177
mkfs.minix....177
mkswap....177
sfdisk....177
swapoff....177
swapon....177
cal....177
chkdupexe....177
col....177
colcrt....178
colrm....178
column....178

# Table of Contents

cytune....178
ddate....178
fdformat....178
getopt....178
hexdump....178
ipcrm....178
ipcs....179
logger....179
look....179
mcookie....179
namei....179
rename....179
renice....179
rev....179
script....179
setfdprm....180
setsid....180
setterm....180
ul....180
whereis....180
write....180
ramsize....180
rdev....180
readprofile....180
rootflags....181
swapdev....181
tunelp....181
vidmode....181

**Installing Man−pages....182**
Installing Man−pages....182
Contents....182
Description....182

**Removing old NSS library files....183**

**Configuring essential software....184**
Configuring Glibc....184
Configuring Dynamic Loader....185
Configuring Lilo....185
Configuring Sysklogd....186
Configuring Shadow Password Suite....186
Configuring Sysvinit....187
Creating the /var/run/utmp file....187
Configuring Vim....188
Creating root password....188

**Chapter 6. Creating system boot scripts....189**

# Table of Contents

**What is being done here....190**

**Creating directories....191**

**Creating the rc script....192**

**Creating the rcS script....195**

**Creating the functions script....196**

**Creating the checkfs script....201**

**Creating the halt script....203**

**Creating the loadkeys script....204**

**Creating the mountfs script....205**

**Creating the reboot script....206**

**Creating the sendsignals script....207**

**Creating the setclock script....208**
Creating the /etc/sysconfig/clock file....208

**Creating the sysklogd script....210**

**Creating the umountfs script....212**

**Setting up symlinks and permissions....213**

**Creating the /etc/fstab file....214**

**Chapter 7. Setting up basic networking....215**

**Introduction....216**

**Installing network software....217**
Installing Netkit−base....217
Installing Net−tools....217

**Creating network boot scripts....218**
Creating the /etc/init.d/localnet bootscript....218
Setting up permissions and symlink....218
Creating the /etc/sysconfig/network file....219
Creating the /etc/hosts file....219
Creating the /etc/init.d/ethnet script....220
Editing the /etc/sysconfig/network file....221

# Table of Contents

Setting up permissions and symlink....221

**Chapter 8. Making the LFS system bootable....223**

**Introduction....224**

**Installing a kernel....225**

**Adding an entry to LILO....226**

**Testing the system....227**

**III. Part III – Installing LFS on Apple PowerPC systems....228**

**Chapter 9. Packages you need to download....229**

**Chapter 10. Preparing a new partition....233**

**Introduction....234**

**Creating a new partition....235**

**Mounting the new partition....236**

**Creating directories....237**

**Chapter 11. Installing basic system software....239**

**How and why things are done....240**

**Debugging symbols and compiler optimizations....241**

**Preparing the LFS system....243**

**Installing Bash....244**
Installing Bash....244
Contents....244
Description....244

**Installing Binutils....245**
Installing Binutils....245
Description....245
Description....245
ld....245
as....245
ar....245
nm....245
objcopy....246

# Table of Contents

objdump....246
ranlib....246
size....246
strings....246
strip....246
c++filt....246
addr2line....247
nlmconv....247

**Installing Bzip2....248**
Installing Bzip2....248
Contents....248
Description....248
Bzip2....248
Bunzip2....248
bzcat....248
bzip2recover....249

**Installing Diffutils....250**
Installing Diffutils....250
Contents....250
Description....250
cmp and diff....250
diff3....250
sdiff....250

**Installing Fileutils....251**
Installing Fileutils....251
Contents....251
Description....251
chgrp....251
chmod....251
chown....251
cp....252
dd....252
df....252
ls, dir and vdir....252
dircolors....252
du....252
install....252
ln....252
mkdir....253
mkfifo....253
mknod....253
mv....253
rm....253
rmdir....253
sync....253

# Table of Contents

touch....253

**Installing GCC on the normal system if necessary....254**
Installing GCC on the normal system if necessary....254
Contents....254
Description....254
Compiler....255
Pre−processor....255
C++ Library....255

**Installing GCC on the LFS system....256**
Installing GCC on the LFS system....256
Creating necessary symlinks....256
Contents....256
Description....257
Compiler....257
Pre−processor....257
C++ Library....257

**Installing Linux Kernel....258**
Installing Linux Kernel....258
Contents....258
Description....258

**Installing Glibc....260**
Contents....260
Description....260
A note on the glibc−crypt package....260
Installing Glibc....260
Copying old NSS library files....262

**Installing Grep....264**
Installing Grep....264
Contents....264
Description....264
egrep....264
fgrep....264
grep....264

**Installing Gzip....265**
Installing Gzip....265
Contents....265
Description....265
gunzip....265
gzexe....266
gzip....266
zcat....266
zcmp....266

# Table of Contents

zdiff....266
zforce....266
zgrep....266
zmore....266
znew....267

**Installing Make....268**
Installing Make....268
Contents....268
Description....268

**Installing Sed....269**
Installing Sed....269
Contents....269
Description....269

**Installing Shellutils....270**
Installing Shellutils....270
Contents....270
Description....270
basename....270
chroot....270
date....270
dirname....270
echo....271
env....271
expr....271
factor....271
false....271
groups....271
hostid....271
hostname....271
id....271
logname....272
nice....272
nohup....272
pathchk....272
pinky....272
printenv....272
printf....272
pwd....272
seq....272
sleep....273
stty....273
su....273
tee....273
test....273
true....273

# Table of Contents

tty....273
uname....273
uptime....273
users....274
who....274
whoami....274
yes....274

**Installing Tar....275**
Installing Tar....275
Contents....275
Description....275
tar....275
rmt....275

**Installing Textutils....276**
Installing Textutils....276
Contents....276
Description....276
cat....276
cksum....276
comm....276
csplit....276
cut....277
expand....277
fmt....277
fold....277
head....277
join....277
md5sum....277
nl....277
od....277
paste....278
pr....278
ptx....278
sort....278
split....278
sum....278
tac....278
tail....278
tr....278
tsort....279
unexpand....279
uniq....279
wc....279

**Creating passwd and group files....280**

# Table of Contents

**Copying /proc/devices....281**

**Installing basic system software....282**

**Entering the chroot'ed environment....283**

**Creating device files....284**
Installing MAKEDEV....284
Creating the /dev entries....284

**Installing Ed....285**
Installing Ed....285
Contents....285
Description....285

**Installing Patch....286**
Installing Patch....286
Contents....286
Description....286

**Installing GCC....287**
Installing GCC....287
Contents....287
Description....287
Compiler....287
Pre−processor....287
C++ Library....287

**Installing Bison....289**
Installing Bison....289
Contents....289
Description....289

**Installing Mawk....291**
Installing Mawk....291
Contents....291
Description....291
gawk....291

**Installing Findutils....292**
Installing Findutils....292
Contents....292
Description....292
Find....292
Locate....292
Updatedb....293
Xargs....293

# Table of Contents

**Installing Ncurses....294**
Installing Ncurses....294
Contents....294
Description....294
The libraries....294
Tic....294
Infocmp....294
clear....295
tput....295
toe....295
tset....295

**Installing Less....296**
Installing Less....296
Contents....296
Description....296

**Installing Groff....297**
Installing Groff....297
Contents....297
Description....297
addftinfo....297
afmtodit....297
eqn....297
grodvi....297
groff....298
grog....298
grohtml....298
grolj4....298
grops....298
grotty....298
hpftodit....298
indxbib....298
lkbib....298
lookbib....299
neqn....299
nroff....299
pfbtops....299
pic....299
psbb....299
refer....299
soelim....299
tbl....300
tfmtodit....300
troff....300

**Installing Man....301**
Installing Man....301

# Table of Contents

Contents....301
Description....301
man....301
apropos....301
whatis....301
makewhatis....301

**Installing Perl....302**
Installing Perl....302
Contents....302
Description....302

**Installing M4....303**
Installing M4....303
Contents....303
Description....303

**Installing Texinfo....304**
Installing Texinfo....304
Contents....304
Description....304
info....304
install−info....304
makeinfo....304
texi2dvi....304
texindex....305

**Installing Autoconf....306**
Installing Autoconf....306
Contents....306
Description....306
autoconf....306
autoheader....306
autoreconf....306
autoscan....306
autoupdate....307
ifnames....307

**Installing Automake....308**
Installing Automake....308
Contents....308
Description....308
aclocal....308
automake....308

**Installing Bash....309**
Installing Bash....309
Contents....309

# Table of Contents

Description....309

**Installing Flex....310**
Installing Flex....310
Contents....310
Description....310

**Installing File....311**
Installing File....311
Contents....311
Description....311

**Installing Gettext....312**
Installing Gettext....312
Contents....312
Description....312
gettext....312

**Installing Libtool....313**
Installing Libtool....313
Contents....313
Description....313
libtool....313
libtoolize....313
ltdl library....313

**Installing Consoletools....314**
Installing Console−tools....314
Contents....314
Description....314
charset....314
chvt....314
codepage....314
consolechars....315
deallocvt....315
dumpkeys....315
fgconsole....315
fix_bs_and_del....315
font2psf....315
getkeycodes....315
kbd_mode....315
loadkeys....315
loadunimap....316
mapscrn....316
mk_modmap....316
openvt....316
psfaddtable....316
psfgettable....316

# Table of Contents

psfstriptable....316
resizecons....316
saveunimap....316
screendump....317
setfont....317
setkeycodes....317
setleds....317
setmetamode....317
setvesablank....317
showcfont....317
showkey....317
splitfont....317
unicode_start....318
unicode_end....318
vcstime....318
vt−is−UTF8....318
writevt....318

**Installing Consoledata....319**
Installing Console−data....319
Contents....319

**Installing Binutils....320**
Installing Binutils....320
Description....320
Description....320
ld....320
as....320
ar....320
nm....320
objcopy....321
objdump....321
ranlib....321
size....321
strings....321
strip....321
c++filt....321
addr2line....322
nlmconv....322

**Installing Bzip2....323**
Installing Bzip2....323
Contents....323
Description....323
Bzip2....323
Bunzip2....324
bzcat....324
bzip2recover....324

# Table of Contents

**Installing Diffutils....325**
Installing Diffutils....325
Contents....325
Description....325
cmp and diff....325
diff3....325
sdiff....325

**Installing E2fsprogs....326**
Installing E2fsprogs....326
Contents....326
Description....326
chattr....326
lsattr....326
uuidgen....326
badblocks....326
debugfs....327
dumpe2fs....327
e2fsck and fsck.ext2....327
e2label....327
fsck....327
mke2fs and mkfs.ext2....327
mklost+found....327
tune2fs....327

**Installing Fileutils....328**
Installing Fileutils....328
Contents....328
Description....328
chgrp....328
chmod....328
chown....328
cp....329
dd....329
df....329
ls, dir and vdir....329
dircolors....329
du....329
install....329
ln....329
mkdir....330
mkfifo....330
mknod....330
mv....330
rm....330
rmdir....330
sync....330
touch....330

# Table of Contents

**Installing Grep....331**
Installing Grep....331
Contents....331
Description....331
egrep....331
fgrep....331
grep....331

**Installing Gzip....332**
Installing Gzip....332
Contents....332
Description....332
gunzip....332
gzexe....332
gzip....332
zcat....332
zcmp....333
zdiff....333
zforce....333
zgrep....333
zmore....333
znew....333

**Installing Ldso....334**
Installing Ld.so....334
Contents....334
Description....334
ldconfig....334
ldd....335

**Installing Bin86....336**
Installing Bin86....336
Contents....336
Description....336
as86....336
as86_encap....336
ld86....336
objdump86....336
nm86....337
size86....337

**Installing Make....338**
Installing Make....338
Contents....338
Description....338

**Installing Shellutils....339**
Installing Shell Utils....339

# Table of Contents

Contents....339
Description....339
basename....339
chroot....339
date....339
dirname....339
echo....340
env....340
expr....340
factor....340
false....340
groups....340
hostid....340
hostname....340
id....340
logname....341
nice....341
nohup....341
pathchk....341
pinky....341
printenv....341
printf....341
pwd....341
seq....341
sleep....342
stty....342
su....342
tee....342
test....342
true....342
tty....342
uname....342
uptime....342
users....343
who....343
whoami....343
yes....343

**Installing Shadowpwd....344**
Installing Shadow Password Suite....344
Contents....344
Description....344
chage....344
chfn....344
chsh....344
expiry....345
faillog....345
gpasswd....345

# Table of Contents

lastlog....345
login....345
newgrp....345
passwd....345
sg....345
su....345
chpasswd....346
dpasswd....346
groupadd....346
groupdel....346
groupmod....346
grpck....346
grpconv....346
grpunconv....346
logoutd....346
mkpasswd....347
newusers....347
pwck....347
pwconv....347
pwunconv....347
useradd....347
userdel....347
usermod....347
vipw and vigr....347

**Installing Modutils....348**
Installing Modutils....348
Contents....348
Description....348
depmod....348
genksyms....348
insmod....348
insmod_ksymoops_clean....348
kerneld....349
kernelversion....349
ksyms....349
lsmod....349
modinfo....349
modprobe....349
rmmod....349

**Installing Procinfo....350**
Installing Procinfo....350
Contents....350
Description....350

**Installing Procps....351**
Installing Procps....351

# Table of Contents

Contents....351
Description....351
free....351
kill....351
oldps and ps....351
skill....352
snice....352
sysctl....352
tload....352
top....352
uptime....352
vmstat....352
w....352
watch....352

**Installing Psmisc....353**
Installing Psmisc....353
Contents....353
Description....353
fuser....353
killall....353
pstree....353

**Installing Sed....354**
Installing Sed....354
Contents....354
Description....354

**Installing Vim....355**
Installing Vim....355
Contents....355
Description....355
ctags....355
etags....355
ex....355
gview....356
gvim....356
rgview....356
rgvim....356
rview....356
rvim....356
view....356
vim....356
vimtutor....356
xxd....357

**Installing Sysklogd....358**
Installing Sysklogd....358

# Table of Contents

Contents....358
Description....358
klogd....358
syslogd....358

**Installing Sysvinit....359**
Installing Sysvinit....359
Contents....359
Description....359
pidof....359
last....359
lastb....359
mesg....359
utmpdump....360
wall....360
halt....360
init....360
killall5....360
poweroff....360
reboot....360
runlevel....360
shutdown....361
sulogin....361
telinit....361

**Installing Tar....362**
Installing Tar....362
Contents....362
Description....362
tar....362
rmt....362

**Installing Textutils....363**
Installing Textutils....363
Contents....363
Description....363
cat....363
cksum....363
comm....363
csplit....363
cut....364
expand....364
fmt....364
fold....364
head....364
join....364
md5sum....364
nl....364

# Table of Contents

od....364
paste....365
pr....365
ptx....365
sort....365
split....365
sum....365
tac....365
tail....365
tr....365
tsort....366
unexpand....366
uniq....366
wc....366

**Installing Utillinux....367**
Installing Util–Linux....367
Contents....367
Description....368
arch....368
dmesg....368
kill....368
more....368
mount....368
umount....368
agetty....368
blockdev....368
cfdisk....369
ctrlaltdel....369
elvtune....369
fdisk....369
fsck.minix....369
hwclock....369
kbdrate....369
losetup....369
mkfs....369
mkfs.bfs....370
mkfs.minix....370
mkswap....370
sfdisk....370
swapoff....370
swapon....370
cal....370
chkdupexe....370
col....370
colcrt....371
colrm....371
column....371

# Table of Contents

cytune....371
ddate....371
fdformat....371
getopt....371
hexdump....371
ipcrm....371
ipcs....372
logger....372
look....372
mcookie....372
namei....372
rename....372
renice....372
rev....372
script....372
setfdprm....373
setsid....373
setterm....373
ul....373
whereis....373
write....373
ramsize....373
rdev....373
readprofile....373
rootflags....374
swapdev....374
tunelp....374
vidmode....374

**Installing Pmac−utils....375**

**Installing Man−pages....376**
Installing Man−pages....376
Contents....376
Description....376

**Removing old NSS library files....377**

**Configuring essential software....378**
Configuring Glibc....378
Configuring Dynamic Loader....379
Configuring Sysklogd....379
Configuring Shadow Password Suite....380
Configuring Sysvinit....380
Creating the /var/run/utmp file....381
Configuring Vim....381
Creating root password....382

# Table of Contents

**Chapter 12. Creating system boot scripts....383**

**What is being done here....384**

**Creating directories....385**

**Creating the rc script....386**

**Creating the rcS script....389**

**Creating the functions script....390**

**Creating the checkfs script....395**

**Creating the halt script....397**

**Creating the loadkeys script....398**

**Creating the mountfs script....399**

**Creating the reboot script....400**

**Creating the sendsignals script....401**

**Creating the setclock script....402**

**Creating the sysklogd script....403**

**Creating the umountfs script....405**

**Setting up symlinks and permissions....406**

**Creating the /etc/fstab file....407**

**Chapter 13. Setting up basic networking....408**

**Introduction....409**

**Installing network software....410**
Installing Netkit−base....410
Installing Net−tools....410

**Creating network boot scripts....411**
Creating the /etc/init.d/localnet bootscript....411
Setting up permissions and symlink....411
Creating the /etc/sysconfig/network file....412
Creating the /etc/hosts file....412
Creating the /etc/init.d/ethnet script....413

# Table of Contents

Editing the /etc/sysconfig/network file....414
Setting up permissions and symlink....414

**Chapter 14. Making the LFS system bootable....416**

**Introduction....417**

**Installing a kernel....418**

**Updating BootX....419**

**Testing the system....420**

**IV. Part IV − Appendixes....421**

**Appendix A. Package descriptions....422**

**Introduction....423**

**Glibc....424**
Contents....424
Description....424

**Linux kernel....425**
Contents....425
Description....425

**Ed....426**
Contents....426
Description....426

**Patch....427**
Contents....427
Description....427

**GCC....428**
Contents....428
Description....428
Compiler....428
Pre−processor....428
C++ Library....428

**Bison....429**
Contents....429
Description....429

**Mawk....430**
Contents....430

# Table of Contents

Description....430
gawk....430

**Findutils....431**
Contents....431
Description....431
Find....431
Locate....431
Updatedb....431
Xargs....431

**Ncurses....432**
Contents....432
Description....432
The libraries....432
Tic....432
Infocmp....432
clear....432
tput....432
toe....433
tset....433

**Less....434**
Contents....434
Description....434

**Groff....435**
Contents....435
Description....435
addftinfo....435
afmtodit....435
eqn....435
grodvi....435
groff....435
grog....435
grohtml....436
grolj4....436
grops....436
grotty....436
hpftodit....436
indxbib....436
lkbib....436
lookbib....436
neqn....437
nroff....437
pfbtops....437
pic....437
psbb....437

# Table of Contents

refer....437
soelim....437
tbl....437
tfmtodit....438
troff....438

**Man....439**
Contents....439
Description....439
man....439
apropos....439
whatis....439
makewhatis....439

**Perl....440**
Contents....440
Description....440

**M4....441**
Contents....441
Description....441

**Texinfo....442**
Contents....442
Description....442
info....442
install−info....442
makeinfo....442
texi2dvi....442
texindex....442

**Autoconf....443**
Contents....443
Description....443
autoconf....443
autoheader....443
autoreconf....443
autoscan....443
autoupdate....443
ifnames....443

**Automake....445**
Contents....445
Description....445
aclocal....445
automake....445

**Bash....446**

# Table of Contents

Contents....446
Description....446

**Flex....447**
Contents....447
Description....447

**Binutils....448**
Description....448
Description....448
ld....448
as....448
ar....448
nm....448
objcopy....448
objdump....448
ranlib....449
size....449
strings....449
strip....449
c++filt....449
addr2line....449
nlmconv....450

**Bzip2....451**
Contents....451
Description....451
Bzip2....451
Bunzip2....451
bzcat....451
bzip2recover....451

**Diffutils....452**
Contents....452
Description....452
cmp and diff....452
diff3....452
sdiff....452

**E2fsprogs....453**
Contents....453
Description....453
chattr....453
lsattr....453
uuidgen....453
badblocks....453
debugfs....453
dumpe2fs....453

# Table of Contents

e2fsck and fsck.ext2 ..... 454
e2label ..... 454
fsck ..... 454
mke2fs and mkfs.ext2 ..... 454
mklost+found ..... 454
tune2fs ..... 454

**File ..... 455**
Contents ..... 455
Description ..... 455

**Fileutils ..... 456**
Contents ..... 456
Description ..... 456
chgrp ..... 456
chmod ..... 456
chown ..... 456
cp ..... 456
dd ..... 456
df ..... 456
ls, dir and vdir ..... 457
dircolors ..... 457
du ..... 457
install ..... 457
ln ..... 457
mkdir ..... 457
mkfifo ..... 457
mknod ..... 457
mv ..... 458
rm ..... 458
rmdir ..... 458
sync ..... 458
touch ..... 458

**Gettext ..... 459**
Contents ..... 459
Description ..... 459
gettext ..... 459

**Grep ..... 460**
Contents ..... 460
Description ..... 460
egrep ..... 460
fgrep ..... 460
grep ..... 460

**Gzip ..... 461**
Contents ..... 461

# Table of Contents

Description....461
gunzip....461
gzexe....461
gzip....461
zcat....461
zcmp....461
zdiff....461
zforce....461
zgrep....462
zmore....462
znew....462

**Ld.so....463**
Contents....463
Description....463
ldconfig....463
ldd....463

**Libtool....464**
Contents....464
Description....464
libtool....464
libtoolize....464
ltdl library....464

**Bin86....465**
Contents....465
Description....465
as86....465
as86_encap....465
ld86....465
objdump86....465
nm86....465
size86....465

**Lilo....466**
Contents....466
Description....466

**Make....467**
Contents....467
Description....467

**Shellutils....468**
Contents....468
Description....468
basename....468
chroot....468

# Table of Contents

date....468
dirname....468
echo....468
env....468
expr....468
factor....469
false....469
groups....469
hostid....469
hostname....469
id....469
logname....469
nice....469
nohup....469
pathchk....470
pinky....470
printenv....470
printf....470
pwd....470
seq....470
sleep....470
stty....470
su....470
tee....471
test....471
true....471
tty....471
uname....471
uptime....471
users....471
who....471
whoami....471
yes....472

**Shadow Password Suite....473**
Contents....473
Description....473
chage....473
chfn....473
chsh....473
expiry....473
faillog....473
gpasswd....473
lastlog....473
login....474
newgrp....474
passwd....474
sg....474

# Table of Contents

su....474
chpasswd....474
dpasswd....474
groupadd....474
groupdel....475
groupmod....475
grpck....475
grpconv....475
grpunconv....475
logoutd....475
mkpasswd....475
newusers....475
pwck....475
pwconv....476
pwunconv....476
useradd....476
userdel....476
usermod....476
vipw and vigr....476

**Modutils....477**
Contents....477
Description....477
depmod....477
genksyms....477
insmod....477
insmod_ksymoops_clean....477
kerneld....477
kernelversion....477
ksyms....477
lsmod....478
modinfo....478
modprobe....478
rmmod....478

**Procinfo....479**
Contents....479
Description....479

**Procps....480**
Contents....480
Description....480
free....480
kill....480
oldps and ps....480
skill....480
snice....480
sysctl....480

# Table of Contents

tload....480
top....481
uptime....481
vmstat....481
w....481
watch....481

**Vim....482**
Contents....482
Description....482
ctags....482
etags....482
ex....482
gview....482
gvim....482
rgview....482
rgvim....482
rview....483
rvim....483
view....483
vim....483
vimtutor....483
xxd....483

**Psmisc....484**
Contents....484
Description....484
fuser....484
killall....484
pstree....484

**Sed....485**
Contents....485
Description....485

**Sysklogd....486**
Contents....486
Description....486
klogd....486
syslogd....486

**Sysvinit....487**
Contents....487
Description....487
pidof....487
last....487
lastb....487
mesg....487

# Table of Contents

utmpdump....487
wall....487
halt....488
init....488
killall5....488
poweroff....488
reboot....488
runlevel....488
shutdown....488
sulogin....488
telinit....489

**Tar....490**
Contents....490
Description....490
tar....490
rmt....490

**Textutils....491**
Contents....491
Description....491
cat....491
cksum....491
comm....491
csplit....491
cut....491
expand....491
fmt....491
fold....492
head....492
join....492
md5sum....492
nl....492
od....492
paste....492
pr....492
ptx....492
sort....493
split....493
sum....493
tac....493
tail....493
tr....493
tsort....493
unexpand....493
uniq....493
wc....494

# Table of Contents

**Util Linux....495**
Contents....495
Description....495
arch....495
dmesg....495
kill....495
more....495
mount....495
umount....495
agetty....496
blockdev....496
cfdisk....496
ctrlaltdel....496
elvtune....496
fdisk....496
fsck.minix....496
hwclock....496
kbdrate....496
losetup....497
mkfs....497
mkfs.bfs....497
mkfs.minix....497
mkswap....497
sfdisk....497
swapoff....497
swapon....497
cal....497
chkdupexe....498
col....498
colcrt....498
colrm....498
column....498
cytune....498
ddate....498
fdformat....498
getopt....498
hexdump....499
ipcrm....499
ipcs....499
logger....499
look....499
mcookie....499
namei....499
rename....499
renice....499
rev....500
script....500
setfdprm....500

# Table of Contents

setsid....500
setterm....500
ul....500
whereis....500
write....500
ramsize....500
rdev....501
readprofile....501
rootflags....501
swapdev....501
tunelp....501
vidmode....501

**Console−tools....502**
Contents....502
Description....502
charset....502
chvt....502
codepage....502
consolechars....502
deallocvt....502
dumpkeys....502
fgconsole....503
fix_bs_and_del....503
font2psf....503
getkeycodes....503
kbd_mode....503
loadkeys....503
loadunimap....503
mapscrn....503
mk_modmap....503
openvt....504
psfaddtable....504
psfgettable....504
psfstriptable....504
resizecons....504
saveunimap....504
screendump....504
setfont....504
setkeycodes....504
setleds....505
setmetamode....505
setvesablank....505
showcfont....505
showkey....505
splitfont....505
unicode_start....505
unicode_end....505

# Table of Contents

vcstime....505
vt−is−UTF8....506
writevt....506

**Console−data....507**
Contents....507

**Man−pages....508**
Contents....508
Description....508

**Appendix B. Resources....509**

**Introduction....510**

**Books....511**

**HOWTOs and Guides....512**

**Other....513**

# Linux From Scratch


## Gerard Beekmans



Copyright © 1999, 2000 by Gerard Beekmans


This book describes the process of creating your own Linux system from scratch from an already installed Linux distribution, using nothing but the sources of software that are needed.


This book may be distributed only subject to the terms and conditions set forth in the LDP License at http://www.linuxdoc.org/COPYRIGHT.html

It is not necessary to display the license notice, as described in the LDP License, when only a small part of this book is quoted for informational or similar purposes. However, I do require you to display with the quotation(s) a line similar to the following line: "Quoted from the LFS−BOOK at http://www.linuxfromscratch.org"


---

---

# Dedication

This book is dedicated to my loving and supportive wife *Beverly Beekmans*.

***Table of Contents***


*Preface*
- *Who would want to read this book*
- *Who would not want to read this book*
- *Organization*
  - *Part I – Introduction*
  - *Part II – Installation of a basic system on Intel systems*
  - *Part III – Installation of a basic system on Apple PowerPC systems*
  - *Part IV – Appendixes*

*I. Part I – Introduction*
- *1. Introduction*
  - *Introduction*
  - *How things are going to be done*
  - *Book versions*
  - *Acknowledgements*
  - *Changelog*
  - *Mailinglists and archives*
  - *Contact information*
- *2. Important information*
  - *About $LFS*
  - *How to download the software*
  - *How to install the software*

*II. Part II – Installing LFS on Intel systems*
- *3. Packages you need to download*
- *4. Preparing a new partition*
  - *Introduction*
  - *Creating a new partition*
  - *Creating a ext2 file system on the new partition*
  - *Mounting the new partition*
  - *Creating directories*
- *5. Installing basic system software*
  - *How and why things are done*
  - *Debugging symbols and compiler optimizations*
  - *Preparing the LFS system*
  - *Installing Bash*
  - *Installing Binutils*
  - *Installing Bzip2*
  - *Installing Diffutils*
  - *Installing Fileutils*
  - *Installing GCC on the normal system if necessary*
  - *Installing GCC on the LFS system*
  - *Installing Linux Kernel*
  - *Installing Glibc*
  - *Installing Grep*
  - *Installing Gzip*
  - *Installing Make*

*Installing Sed*
*Installing Shellutils*
*Installing Tar*
*Installing Textutils*
*Creating passwd and group files*
*Copying /proc/devices*
*Installing basic system software*
*Entering the chroot'ed environment*
*Creating device files*
*Installing Ed*
*Installing Patch*
*Installing GCC*
*Installing Bison*
*Installing Mawk*
*Installing Findutils*
*Installing Ncurses*
*Installing Less*
*Installing Groff*
*Installing Man*
*Installing Perl*
*Installing M4*
*Installing Texinfo*
*Installing Autoconf*
*Installing Automake*
*Installing Bash*
*Installing Flex*
*Installing File*
*Installing Gettext*
*Installing Libtool*
*Installing Consoletools*
*Installing Consoledata*
*Installing Binutils*
*Installing Bzip2*
*Installing Diffutils*
*Installing E2fsprogs*
*Installing Fileutils*
*Installing Grep*
*Installing Gzip*
*Installing Ldso*
*Installing Bin86*
*Installing Lilo*
*Installing Make*
*Installing Shellutils*
*Installing Shadowpwd*
*Installing Modutils*
*Installing Procinfo*
*Installing Procps*
*Installing Psmisc*
*Installing Sed*
*Installing Vim*
*Installing Sysklogd*

*Installing Sysvinit*
*Installing Tar*
*Installing Textutils*
*Installing Utillinux*
*Installing Man−pages*
*Removing old NSS library files*
*Configuring essential software*
*6. Creating system boot scripts*
*What is being done here*
*Creating directories*
*Creating the rc script*
*Creating the rcS script*
*Creating the functions script*
*Creating the checkfs script*
*Creating the halt script*
*Creating the loadkeys script*
*Creating the mountfs script*
*Creating the reboot script*
*Creating the sendsignals script*
*Creating the setclock script*
*Creating the sysklogd script*
*Creating the umountfs script*
*Setting up symlinks and permissions*
*Creating the /etc/fstab file*
*7. Setting up basic networking*
*Introduction*
*Installing network software*
*Creating network boot scripts*
*8. Making the LFS system bootable*
*Introduction*
*Installing a kernel*
*Adding an entry to LILO*
*Testing the system*
*III. Part III − Installing LFS on Apple PowerPC systems*
*9. Packages you need to download*
*10. Preparing a new partition*
*Introduction*
*Creating a new partition*
*Mounting the new partition*
*Creating directories*
*11. Installing basic system software*
*How and why things are done*
*Debugging symbols and compiler optimizations*
*Preparing the LFS system*
*Installing Bash*
*Installing Binutils*
*Installing Bzip2*
*Installing Diffutils*
*Installing Fileutils*
*Installing GCC on the normal system if necessary*
*Installing GCC on the LFS system*

*Installing Linux Kernel*
*Installing Glibc*
*Installing Grep*
*Installing Gzip*
*Installing Make*
*Installing Sed*
*Installing Shellutils*
*Installing Tar*
*Installing Textutils*
*Creating passwd and group files*
*Copying /proc/devices*
*Installing basic system software*
*Entering the chroot'ed environment*
*Creating device files*
*Installing Ed*
*Installing Patch*
*Installing GCC*
*Installing Bison*
*Installing Mawk*
*Installing Findutils*
*Installing Ncurses*
*Installing Less*
*Installing Groff*
*Installing Man*
*Installing Perl*
*Installing M4*
*Installing Texinfo*
*Installing Autoconf*
*Installing Automake*
*Installing Bash*
*Installing Flex*
*Installing File*
*Installing Gettext*
*Installing Libtool*
*Installing Consoletools*
*Installing Consoledata*
*Installing Binutils*
*Installing Bzip2*
*Installing Diffutils*
*Installing E2fsprogs*
*Installing Fileutils*
*Installing Grep*
*Installing Gzip*
*Installing Ldso*
*Installing Bin86*
*Installing Make*
*Installing Shellutils*
*Installing Shadowpwd*
*Installing Modutils*
*Installing Procinfo*
*Installing Procps*

*Installing Psmisc*
*Installing Sed*
*Installing Vim*
*Installing Sysklogd*
*Installing Sysvinit*
*Installing Tar*
*Installing Textutils*
*Installing Utillinux*
*Installing Pmac−utils*
*Installing Man−pages*
*Removing old NSS library files*
*Configuring essential software*
*12. Creating system boot scripts*
*What is being done here*
*Creating directories*
*Creating the rc script*
*Creating the rcS script*
*Creating the functions script*
*Creating the checkfs script*
*Creating the halt script*
*Creating the loadkeys script*
*Creating the mountfs script*
*Creating the reboot script*
*Creating the sendsignals script*
*Creating the setclock script*
*Creating the sysklogd script*
*Creating the umountfs script*
*Setting up symlinks and permissions*
*Creating the /etc/fstab file*
*13. Setting up basic networking*
*Introduction*
*Installing network software*
*Creating network boot scripts*
*14. Making the LFS system bootable*
*Introduction*
*Installing a kernel*
*Updating BootX*
*Testing the system*
*IV. Part IV − Appendixes*
*A. Package descriptions*
*Introduction*
*Glibc*
*Linux kernel*
*Ed*
*Patch*
*GCC*
*Bison*
*Mawk*
*Findutils*
*Ncurses*
*Less*

*Groff*
*Man*
*Perl*
*M4*
*Texinfo*
*Autoconf*
*Automake*
*Bash*
*Flex*
*Binutils*
*Bzip2*
*Diffutils*
*E2fsprogs*
*File*
*Fileutils*
*Gettext*
*Grep*
*Gzip*
*Ld.so*
*Libtool*
*Bin86*
*Lilo*
*Make*
*Shellutils*
*Shadow Password Suite*
*Modutils*
*Procinfo*
*Procps*
*Vim*
*Psmisc*
*Sed*
*Sysklogd*
*Sysvinit*
*Tar*
*Textutils*
*Util Linux*
*Console−tools*
*Console−data*
*Man−pages*
*B. Resources*
*Introduction*
*Books*
*HOWTOs and Guides*
*Other*

# Preface

# Who would want to read this book

This book is intended for Linux users who want to learn more about the inner workings of Linux and how the various pieces of the Operating System fit together. This book will guide you step−by−step in creating your own custom build Linux system from scratch, using nothing but the sources of software that are needed.

This book is also intended for Linux users who want to get away from the existing commercial and free distributions that are often too bloated. Using existing distributions also forces you to use the file system structure, boot script structure, etc. that they choose to use. With this book you can create your own structures and methods in exactly the way you like them (which can be based on the ones this book provides)

Also, if you have security concerns, you don't want to rely on pre−compiled packages. So instead, you want to compile all programs from scratch and install them yourself. That could be another reason why you would want to build a custom made Linux system.

Those are just a few out of many reasons why people want to build their own Linux system. If you're one of those people, this book is meant for you.

---

# Who would not want to read this book

Users who don't want to build an entire Linux system from scratch probably don't want to read this book. If you, however, do want to learn more about what happens behind the scenes, in particulair what happens between turning on your computer and seeing the command prompt, you want to read the "From Power Up To Bash Prompt" (P2B) HOWTO. This HOWTO builds a bare system, in a similar way as this book does, but it focusses more on just installing a bootable system instead of a complete system.

To decide whether you want to read this book or the P2B HOWTO, you could ask yourself this question: Is my main objective to get a working Linux system that I'm going to build myself and along the way learn and learn what every component of a system is for, or is just the learning part your main objective. If you want to build and learn, read this book. If you just want to learn, then the P2B HOWTO is probably better material to read.

The "From Power Up To Bash Prompt" HOWTO can be downloaded from
http://learning.taslug.org.au/power2bash

---

# Organization

This book is devided into the following parts. Although there is a lot of duplicate information in certain parts, it's the easiest way to read it and not to mention the easiest way for me to maintain the book.

---

## Part I – Introduction

Part One gives you general information about this book (versions, where to get it, changelog, mailinglists and how to get in touch with me). It also explains a few important aspects you really want and need to read before you start building an LFS system.

---

## Part II – Installation of a basic system on Intel systems

Part Two guides you through the installation of a basic system on Intel systems which will be the foundation for the rest of the system. Whatever you choose to do with your brand new LFS system, it will be built on the foundation that's installed in this part.

---

## Part III – Installation of a basic system on Apple PowerPC systems

Part Three is the Apple PowerPC version of part two.

---

## Part IV – Appendixes

Part Four contains various Appendixes.

# I. Part I – Introduction

***Table of Contents***

*1. Introduction*
*2. Important information*

# Chapter 1. Introduction

# Introduction

Having used a number of different Linux distributions, I was never fully satisfied with any of those. I didn't like the way the bootscripts were arranged, or I didn't like the way certain programs were configured by default and more of those things. I came to realize that when I want to be totally satisfied with a Linux system, I have to build my own Linux system from scratch, ideally only using the source code. Not using pre−compiled packages of any kind. No help from some sort of cdrom or bootdisk that would install some basic utilities. You would use your current Linux system and use that one to build your own.

This, at one time, wild idea seemed very difficult and at times almost impossible. The reason for most problems were due to my lack of knowledge about certain programs and procedures. After sorting out all kinds of dependency problems, compilation problems, etcetera, a custom built Linux system was created and fully operational. I called this system an LFS system, which stands for LinuxFromScratch.

---

# How things are going to be done

We are going to build the LFS system using an already installed Linux distribution such as Debian, SuSe, Slackware, Mandrake, RedHat, etc. You don't need to have any kind of bootdisk. We will use an existing Linux system as the base (since we need a compiler, linker, text editor and other tools).

If you don't have Linux installed yet, you won't be able to put this book to use right away. I suggest you first install a Linux distribution. It really doesn't matter which one you install. It also doesn't need to be the latest version, though it shouldn't be a too old one. If it is about a year old or newer it should do just fine. You will safe yourself a lot of trouble if your normal system uses glibc−2.0 or newer. Libc5 isn't supported by this book, though it isn't impossible to use a libc5 system if you have no choice.

---

# Book versions

This is the 2.3.6 development version dated July 19th, 2000. If this version is older than a month you definitely want to take a look at our website and download a newer version.

The latest versions of this book and related files can be downloaded from one of the following sites. Please avoid the main site at Dallas whenever possible.

- Dallas, Texas, United States – http://www.linuxfromscratch.org/index2.html
- Columbus, Ohio, United States – http://lfs.bcpub.com/index2.html
- United States – http://lfs.sourceforge.net/index2.html
- Braunschweig, Niedersachsen, Germany – http://134.169.139.209/index2.html
- Brisbane, Queensland, Australia – http://lfs.mirror.aarnet.edu.au/index2.html
- France – http://www.linuxien.com/lfs/index2.html

---

# Acknowledgements

I would like to thank the following people and organizations for their contributions towards the LinuxFromScratch project:

- Paul Jensen for providing http://www.pcrdallas.com as the main linuxfromscratch.org host
- Bryan Dumm for providing http://www.bcpub.com as the lfs.bcpub.com mirror
- Jan Niemann for providing http://helga.lk.etc.tu−bs.de as the 134.169.139.209 mirror
- Jason Andrade for providing http://mirror.aarnet.edu.au as the lfs.mirror.aarnet.edu.au mirror
- Johan Lenglet for providing http://www.linuxien.com/ as the www.linuxien.com/lfs/ mirror
- Michael Peters for contributing the Apple PowerPC modifications
- VA Linux Systems who, on behalf of Linux.com, donated a VA Linux 420 (formerly StartX SP2) workstation towards this project
- Jesse Tie Ten Quee who donated a Yamaha CDRW 8824E CD−RW.
- Countless other people from the various LFS mailinglists who are making this book happen by making suggestions, testing and submitting bug reports.

# Changelog

If, for example, a change is listed for chapter 5 it (usually) means the same change has been done in the chapters for the other architectures.

j.3.6 – July 19th, 2000

- Chapter 3: Re–ordered the software download list so it once again matches the order in which packages are used (the first package listed in the list is the first package that we will be using in the book, the second listed package will be the second package used in the book, etc).
- Chapter 3: Added the file sizes of the packages you have to download.
- Chapter 3: Removed the start–stop–daemon package.
- Chapter 3: Added the findutils and glibc patches to the package list.
- Chapter 3: Added the man–pages package to the package list.
- Chapter 4: Moved the creation of the $LFS/dev/ files to chapter 5 after we have entered the chroot environment. This is done because GID's on normal system and LFS system might differ and the MAKEDEV script depends on the GID's.
- Chapter 5: Added the installation of the man–pages package.
- Chapter 5: Added a few commonly used groups to the /etc/group file when it is created (these are the groups needed by the MAKEDEV script).
- Chapter 5: The /proc/devices file is copied to $LFS/proc for the benefit of the MAKEDEV script. The presence of this file ensures the proper creation of the device files.
- Chapter 5: Layout changes. Every package installation has it's own page now. Also the text from appendixa for every package is included with the installation instructions so you can read what a package is about during (or after or before) the installation of it.
- Chapter 5: Removed the patches for diffutils, grep, gzip and sed that used to fix static link problems. The problems can be fixed by passing compile arguments to the C pre–processor (cpp) instead.
-

Chapter 5: Added the −−disable−termcap option to configure to disable termcap backward compatibility (if you want to know why termcap isn't used anymore, please read the INSTALL file that comes with the Ncurses package).

- Chapter 5: Added a few missing files from the fileutils package to the "mv" commands.
- Chapter 5: Removed the installation of the start−stop−daemon package.
- Chapter 5: Removed the −e parameters from the make command lines.
- Chapter 5: Instead of editing the procinfo, procps and psmisc Makefile files with a text editor, the sed command it used.
- Chapter 6: Added the setclock script in case your hardware clock isn't set to GMT.
- Chapter 6: Removed the use of the start−stop−daemon program and replaced them with custom functions that use programs like pidof and kill to accomplish the same tasks but with more control over what happens.
- Chapter 6: Added the loadproc and killproc functions to the /etc/init.d/functions file that take over the functions the start−stop−daemon program used to perform.
- Chapter 6: When the checkfs script runs without errors it now prints a green OK.
- Chapter 6: When /fastboot or /forcefsck exist, they won't be deleted from within the checkfs script but from within the mountfs script as soon as the root partition has been remounted in read−write mode.
- Chapter 6 & 7: Instead of sourcing a file with ". /etc/init.d/functions", "source /etc/init.d/functions" is now used. This makes it easier to read and is clearer for persons who don't know much about scripting.
- Appendix A: removed start−stop−daemon.
- Appendix B: Removed a few unrelated items from the book and howto sections (the references to Sendmail and ISP−Hookup−HOWTO).

j.3.5 – June 19th, 2000

-

Chapter 3: Updated LILO download location

- Chapter 3: Updated Shadow Password Suite download location
- Chapter 3: Updated the Flex download location
- Chapter 3: Updated the File download location
- Chapter 3: Added netkit−base and net−tools to the mandatory packages section
- Chapter 5: A glibc−2.1.3 patch is available if you have problems compiling glibc on a bash−2.04 machine.
- Chapter 5: Added compiler optimization
- Chapter 5: Added the creation of the root password to "Configuring essential software"
- Chapter 5: The Linux86 package has been replaced by the Bin86 package.
- Chapter 5: Included information on how to optimize compilations.
- Chapter 5: Moved installation of Groff and Man before Perl. This way Perl known how to install man pages and where to install them.
- Chapter 5: Changed GCC's local−prefix option to /usr/local instead of /usr (this was still a residue from the time where /usr/local was a symbolic link to /usr)
- Chaper 5: Fixed the commands when a patch is used and the patch filename contained the .gz suffix.
- Chapter 5: Added −−disable−nls to every configure command in the "Perparing the LFS system..." section which didn't have it yet.
- Chapter 5: Added the installation of bash−2.03 so you have a shell that can be used to compile packages that violate POSIX standards regarding valid characters in variable names
-

Chapter 5: Added the installation of console−tools and console−data for people who have non−US keyboards

- Chapter 5: Moved the ed program to the /bin directory conforming the FHS standard
- Chapter 6 & 7: Implemented LSB recommended run level scheme.
- Chapter 6 & 7: Implemented "fancy bootscripts". When something fails in a bootscript it still says FAILED but the text red. When something succeeded it still will print OK but the text is green.
- Chater 6: Added the loadkeys scripts for people with non−US keyboards
- Chapter 6: Added the /etc/sysconfig directory to "Creating directories"
- Chapter 6: Renamed the checkroot boot script into checkfs. The script also checks other file systems now.
- Chapter 6: Updated the mountfs boot script to mount all file systems that are mentioned in the /etc/fstab file and don't have the noauto option set.
- Chapter 6: After checkfs evaluated the existence of /fastboot or /forcecheck it will remove those files.
- Chapter 6 & 7: Changed the mode of the boot scripts from 755 to 754
- Chapter 7: Moved system specific information for hostname and ethernet configuration to the /etc/sysconfig/network file
- Chapter 7: Removed the default gateway command
- Chapter 7: Fixed the typo in the ethnet script (NETMAKSK −> NETMASK)
- Chapter 7: A net−tools patch is available to fix a minor bug in the package (illegal variable names that bash−2.04 will complain about)

j.3.4 − June 5th, 2000

-

Chapter 5: Fixed the kernel header files configuration

- Chapter 5: Fixed the lilo configuration

j.3.3 – May 15th, 2000

- Changed the default mount point from /mnt/xxx to /mnt/lfs (where xxx used to be the partition's designation like hda5, sda5 and others). The reason for the change is to make cross–platform instructions easier.
- Chapter 4: Changed the default modes for the $LFS/root and $LFS/tmp directory to respectively 0750 and 1777.
- Chapter 5: Removed the encoded password from the passwd file. Instead a file with no set password is created. The root password can be set by the user when the system is rebooted into the LFS system (after chapter 8).
- Chapter 5: Fixed the procps compile command for watch.c. It should compile properly now.
- Chapter 5: Fixed gzip patch installation (used the wrong filename in the patch command
- Chapter 5: Changed 'entering the chroot'ed environment' to make bash a login shell.
- Chapter 5: Configuring the kernel has been moved to this chapter because it needs to be done before programs like e2fsprogs and lilo are compiled.
- Chapter 6: Fixed the rc script. It now checks to see if the previous run level starts a service before attempting to stop it in the new run level. Also, if a service is already started in the previous run level it won't attempt to start the service in the new run level again. Thanks to Jason Pearce for providing this fixed script.
- Chapter 7: Fixed the ethnet script – removed paratheses from the environment variables and removed the command to add a route. The ifconfig command used to bring the eth device up already sets this route.

j.3.2 – April 18th, 2000

- Chapter 4.7: Change only the owner of the $LFS/dev/* files
-

Fixed a large amount of typo's that occured during the transistion from the LinuxDoc DTD (2.2 and lower) to the DocBook DTD (2.3.1 and higher).

- Moved chapters around quite a bit and applied a new structure in the book. Installations for Intel, Apple PowerPC and future systems will be put in their own dedicated part of the book.
- After the system is prepared to install the basic system software, we no longer reboot the system but instead we setup a chroot'ed environment. This will have the same effect without having to reboot.
- Apple PowerPC has it's own dedicated chapters now. This should increase readability a lot
- All optional chapters have been removed for now. These chapters are going to be restructured into dedicated parts such as a chapter that deals with setting up LFS as an email server. A chapter that deals with setting up LFS as a http server, and so forth. These reorganizations couldn't make this development version in time. So you'll have to read the current stable 2.2 version of this book for those parts.
- Replaced the fixed packages by patch files. This way you can see what needs to be changed in a package in order to get it to compile properly.

j.3.1 – April 12th, 2000

- Chapter 4.4: Added the $LFS/usr/info symlink which points to $LFS/usr/share/info
- Chapter 7.3.1: Added a second variation to a 'swap–line' in a fstab file.
- Chapter 7.3.2: Removed $LFS from the commands.
- Chapter 7.4.43: Added the vi symlink
- Chapter 9.2.5: Improved ethnet script to include routing information
- Chapter 10.1.2: Fixed missing subdirectory 'mqueue' in mkdir /var/spool –> /mkdir /var/spool/mqueue
- Chapter 10.1.4: Updated the sendmail configuration file with a few necessary options
- Chapter 10.1.7: Fixed wrong directory path /etc/init.d/rc2.d –> /etc/rc2.d

# Mailinglists and archives

The linuxfromscratch.org server is hosting the following public accessible mailinglists:

- lfs−discuss
- lfs−config
- lfs−apps
- lfs−announce
- linux
- alfs−discuss

---

## lfs−discuss

The lfs−discuss mailinglist discusses matters strictly related to the LFS−BOOK. If you have problems with the book, want to report a bug or two or have suggestions to improve the book, use this mailinglist.

Compilation problems, questions how to configure a piece of software and such are to be posted to the lfs−config or lfs−apps mailinglist. To find out what kind of questions go to which of the two lists you can read in the descriptions for those two lists.

---

## lfs−config

The lfs−config list discusses problems with compiling, installing and configuring software that is used in the LFS−BOOK.

Problems with compiling, installing or configuring programs that didn't give problems on a non−LFS system are discussed on the lfs−apps list. If your problem doesn't fit on the lfs−config or lfs−apps mailinglist, please use the linux mailinglist.

---

## lfs−apps

The lfs−apps list discussed the compilation and configuration of software that's not used in this book. The list is mainly used when you have problems installing software on an LFS system when you don't have problems compiling it on your normal distribution. It's not that LFS is incompatible with

"normal" distributions but just the fact that you might be missing support−software that programs need or need to configure a few things on your new LFS system.

If you had problems with software on non−LFS systems as well, please use the linux mailinglist for help.

## lfs−announce

The lfs−announce list is a moderated list. You can subscribe to it, but you can't post any messages to this list. This list is used to announce new stable releases. If you want to be informed about development releases as well then you'll have to join the lfs−discuss list. If you're already on the lfs−discuss list there's little use subscribing to this list as well because everything that is posted to the lfs−announce list will be posted to the lfs−discuss list as well.

## linux

The linux list is a general Linux discussion list that handles everything that has got anything to do with Linux in any way, shape and form. Ocasionally we discuss the price of beer as well.

## alfs−discuss

The alfs−discuss discusses the development of ALFS which stands for Automated LinuxFromScratch. The goal of this project is to develop an installation tool that can install an LFS system automatically for you. It's main goal is to speed up compilation by taking away your need to manually enter the commands to configure, compile and install packages.

## How to subscribe?

You can subscribe to any of the above mentioned mailinglists by sending an email to majordomo@linuxfromscratch.org and write *subscribe listname* in the body of the message, where listname is replaced by either lfs−discuss, lfs−config, lfs−apps, lfs−announce, linux or alfs−discuss. No subject required.

You can, if you want, subscribe to multiple lists at the same time using one email. Just repeat the subscribe command for each of the lists you want to subscribe to.

After you have sent the email, the Majordomo program will send you an email back requesting a confirmation of your subscription request. After you have sent back this confirmation email, Majordomo will send you an email again with the message that you have been subscribed to the list(s) along with an introduction message for that particulair list.

## How to unsubscribe?

To unsubscribe from a list, send an email to majordomo@linuxfromscratch.org and write *unsubscribe listname* in the body of the message, where listname is replaced by either lfs−discuss, lfs−config, lfs−apps, lfs−announce, linux or alfs−discuss.

You can, if you want, unsubscribe from multiple lists at the same time using one email. Just repeat the unsubscribe command for each of the lists you want to unsubscribe from.

---

## Mail archives

The lfs−discuss, lfs−config, lfs−apps and linux mailing lists have an archive you can access to find information on subjects already posted to this list. You can find them at http://www.pcrdallas.com/mail−archives

---

# Contact information

Direct all your emails to the lfs−discuss mailinglist preferably.

If you need to reach Gerard Beekmans personally, send an email to gerard@linuxfromscratch.org

If you need to reach Michael Peters, Apple PPC maintainer of this book, personally, send an email to mpters@mac.com

# Chapter 2. Important information

# About $LFS

Please read the following carefully: throughout this document you will frequently see the variable name $LFS. $LFS must at all times be replaced by the directory where the partition that contains the LFS system is mounted. How to create and where to mount the partition will be explained later on in full detail in chapter 4. In my case the LFS partition is mounted on /mnt/lfs. If I read this document myself and I see $LFS somewhere, I will pretend that I read /mnt/lfs. If I read that I have to run this command: cp inittab $LFS/etc I actually will run this: cp inittab /mnt/lfs/etc

It's important that you do this no matter where you read it; be it in commands you enter on the prompt, or in some file you edit or create.

If you want, you can set the environment variable LFS. This way you can literally enter $LFS instead of replacing it by something like /mnt/lfs. This is accomplished by running: export LFS=/mnt/lfs

If I read cp inittab $LFS/etc, I literally can type cp inittab $LFS/etc and the shell will replace this command by cp inittab /mnt/lfs/etc automatically.

Do not forget to set the $LFS variable at all times. If you haven't set the variable and you use it in a command, $LFS will be ignored and whatever i left will be executed. The command cp inittab $LFS/etc without the LFS variable set, will result in copying the inittab file to the /etc directory which will overwrite your system's inittab. A file like inittab isn't that big a problem as it can easily be restored, but if you would make this mistake during the installation of the C Library, you can break your system badly and might have to reinstall it if you don't know how to repair it.

---

# How to download the software

Throughout this document I will assume that you have stored all the packages you have downloaded somewhere in $LFS/usr/src.

I use the convention of having a $LFS/usr/src/sources directory. Under sources you'll find the directory 0–9 and the directories a through z. A package as sysvinit–2.78.tar.gz is stored under $LFS/usr/src/sources/s/ A package as bash–2.04.tar.gz is stored under $LFS/usr/src/sources/b/ and so forth. You don't have to follow this convention of course, I was just giving an example. It's better to keep the packages out of $LFS/usr/src and move them to a subdirectory, so we'll have a clean $LFS/usr/src directory in which we will unpack the packages and work with them.

The next chapter contains the list of all the packages you need to download, but the partition that is going to contain our LFS system isn't created yet. Therefore store the files temporarily somewhere where you want and remember to copy them to $LFS/usr/src/ when you have finished the chapter in which you prepare a new partition (which chapter exactly depends on your architecture).

---

# How to install the software

Before you can actually start doing something with a package, you need to unpack it first. Often you will find the package files being tar'ed and gzip'ed (you can see this from a .tar.gz or .tgz extension). I'm not going to write down every time how to ungzip and how to untar an archive. I will tell you how to do that once, in this paragraph. There is also the possibility that you have the ability of downloading a .tar.bz2 file. Such a file is tar'ed and compressed with the bzip2 program. Bzip2 achieves a better compression than the commonly used gzip does. In order to use bz2 archives you need to have the bzip2 program installed. Most if not every distribution comes with this program so chances are high it is already installed on your system. If not, install it using your distribution's installation tool.

To start with, change to the $LFS/usr/src directory by running:

```
root:~# cd $LFS/usr/src
```

When you have a file that is tar'ed and gzip'ed, you unpack it by running either one of the following two commands, depending on the filename format:

```
root:/usr/src# tar xvfz filename.tar.gz
root:/usr/src# tar xvfz filename.tgz
```

When you have a file that is tar'ed and bzip'ed, you unpack it by running:

```
root:/usr/src#    bzcat filename.tar.bz2 | tar xv
```

When you have a file that is tar'ed, you unpack it by running:

```
root:/usr/src# tar xvf filename.tar
```

When the archive is unpacked a new directory will be created under the current directory (and this document assumes that you unpack the archives under the $LFS/usr/src directory). You have to enter that new directory before you continue with the installation instructions. So everytime the book is going to install a program, it's up to you to unpack the source archive.

After you have installed a package you can do two things with it. You can either delete the directory that contains the sources or you can keep it. If you decide to keep it, that's fine by me. But if you need the same package again in a later chapter you need to delete the directory first before using it again. If you don't do this, you might end up in trouble because old settings will be used (settings that apply to your normal Linux system but which don't always apply to your LFS system). Doing a simple make clean does not always guarantee a totally clean source tree. The configure script can also have files lying around in various subdirectories which aren't always removed by a make clean process.

# II. Part II – Installing LFS on Intel systems

***Table of Contents***

*3. Packages you need to download*
*4. Preparing a new partition*
*5. Installing basic system software*
*6. Creating system boot scripts*
*7. Setting up basic networking*
*8. Making the LFS system bootable*

---

# Chapter 3. Packages you need to download

Below is a list of all the packages you need to download for building the basic system. The version numbers printed correspond to versions of the software that is known to work and which this book is based on. If you experience problems which you can't solve yourself, download the version that is assumed in this book (in case you download a newer version).

The listed file sizes refer to the sizes of the .tar.gz archives. Sometimes you can find .tar.bz2 archives, but as .tar.gz is still the most widely used format, that size is listed.

- Bash (2.04) – 1,708,138 bytes: ftp://ftp.gnu.org/gnu/bash/
- Binutils (2.10) 7,210,401 bytes: ftp://ftp.gnu.org/gnu/binutils/
- Bzip2 (1.0.1) 464,991 bytes: http://sourceware.cygnus.com/bzip2/
- Diff Utils (2.7) 312,330 bytes: ftp://ftp.gnu.org/gnu/diffutils/
- File Utils (4.0) 1,181,464 bytes: ftp://ftp.gnu.org/gnu/fileutils/
- GCC (2.95.2) 12,973,458 bytes: ftp://ftp.gnu.org/gnu/gcc/
- Linux Kernel (2.2.16) 17,261,494 bytes: ftp://ftp.kernel.org/pub/linux/kernel/
- Glibc (2.1.3) 9,106,875 bytes: ftp://ftp.gnu.org/gnu/glibc/
- Glibc−crypt (2.1.3) 40,930 bytes: ftp://ftp.gwdg.de/pub/linux/glibc/
- Glibc−linuxthreads (2.1.3) 154,425 bytes: ftp://ftp.gnu.org/gnu/glibc/
- Glibc Patch (2.1.3) – 751 bytes: http://www.linuxfromscratch.org/download/glibc−2.1.3.patch.gz
- Grep (2.4.2) 463,477 bytes: ftp://ftp.gnu.org/gnu/grep/
- Gzip (1.2.4a) 221,779 bytes: ftp://ftp.gnu.org/gnu/gzip/
-

Make (3.79.1) 1,037,173 bytes: ftp://ftp.gnu.org/gnu/make/

- Sed (3.02) 265,549 bytes: ftp://ftp.gnu.org/gnu/sed/
- Shell Utils (2.0) 1,253,022 bytes: ftp://ftp.gnu.org/gnu/sh−utils/
- Tar (1.13) 1.058,280 bytes: ftp://ftp.gnu.org/gnu/tar/
- Text Utils (2.0) 1,547,106 bytes: ftp://ftp.gnu.org/gnu/textutils/
- MAKEDEV (2.5) − 11,562 bytes: ftp://ftp.ihg.uni−duisburg.de/Linux/system
- Ed (0.2) 185,913 bytes: ftp://ftp.gnu.org/gnu/ed/
- Patch (2.5.4) 187,675 bytes: ftp://ftp.gnu.org/gnu/patch/
- Bison (1.28) 422,864 bytes: ftp://ftp.gnu.org/gnu/bison/
- Mawk (1.3.3) 209,948 bytes: ftp://ftp.whidbey.net/pub/brennan/
- Find Utils (4.1) 294,512 bytes: ftp://ftp.gnu.org/gnu/findutils/
- Find Utils Patch (4.1) 985 bytes: http://www.linuxfromscratch.org/download/findutils−4.1.patch.gz
- Ncurses (5.1) 1,711,689 bytes: ftp://ftp.gnu.org/gnu/ncurses/
- Less (358) 231,140 bytes: ftp://ftp.gnu.org/gnu/less/
- Groff (1.16) 1,427,333 bytes: ftp://ftp.gnu.org/gnu/groff/
- Man (1.5h1) 179,170 bytes: ftp://ftp.win.tue.nl/pub/linux−local/utils/man/
- Perl (5.6.0) 5,491,334 bytes: http://www.perl.com
-

M4 (1.4) 319,084 bytes: ftp://ftp.gnu.org/gnu/m4/

- Texinfo (4.0) 1,140,565 bytes: ftp://ftp.gnu.org/gnu/texinfo/
- Autoconf (2.13) 445,493 bytes: ftp://ftp.gnu.org/gnu/autoconf/
- Automake (1.4) 355,529 bytes: ftp://ftp.gnu.org/gnu/automake/
- Flex (2.5.4a) 383,228 bytes: ftp://ftp.gnu.org/non−gnu/flex/
- File (3.31) 138,549 bytes: ftp://ftp.gw.com/mirrors/pub/unix/file/
- Gettext (0.10.35) 718.331 bytes: ftp://ftp.gnu.org/gnu/gettext/
- Libtool (1.3.5) 541,231 bytes: ftp://ftp.gnu.org/gnu/libtool/
- Console−tools (0.2.3) 673,736 bytes: ftp://metalab.unc.edu/pub/Linux/system/keyboards/
- Console−tools (0.2.3) Patch: 4,059 bytes: http://www.linuxfromscratch.org/download/console−tools−0.2.3.patch.gz
- Console−data (1999.08.29) 560,870 bytes: ftp://metalab.unc.edu/pub/Linux/system/keyboards/
- E2fsprogs (1.18) 835,075 bytes: ftp://tsx−11.mit.edu/pub/linux/packages/ext2fs/
- Ld.so (1.9.9) 356,800 bytes: ftp://tsx−11.mit.edu/pub/linux/packages/GCC/
- Bin86 (0.15.1) 142,195 bytes: http://www.cix.co.uk/~mayday/
- Lilo (21.5) 215,560 bytes: ftp://brun.dyndns.org/pub/linux/lilo/
- Shadow Password Suite (19990827) 727,755 bytes: ftp://ftp.ists.pwr.wroc.pl/pub/linux/shadow/
- Modutils (2.3.12) 202,061 bytes: ftp://ftp.ocs.com.au/pub/modutils/
-

Procinfo (17) 22,976 bytes: ftp://ftp.cistron.nl/pub/people/svm/

- Procps (2.0.7) 196,993 bytes: ftp://people.redhat.com/johnsonm/procps/
- Psmisc (19) 21,681 bytes: ftp://lrcftp.epfl.ch/pub/linux/local/psmisc/
- Vim−rt (5.7) 1,103,734 bytes: ftp://ftp.vim.org/pub/editors/vim/unix/
- Vim−src (5.7) 1,238.878 bytes: ftp://ftp.vim.org/pub/editors/vim/unix/
- Sysklogd (1.3.31) 96,281 bytes: ftp://sunsite.unc.edu/pub/Linux/system/daemons/
- Sysvinit (2.78) 109,524 bytes: ftp://ftp.cistron.nl/pub/people/miquels/sysvinit/
- Util Linux (2.10m) 1,207,247 bytes: ftp://ftp.win.tue.nl/pub/linux/utils/util−linux/
- Man−pages (1.30) 667,665 bytes: ftp://ftp.win.tue.nl/pub/linux/docs/manpages/
- Netkit−base (0.16) 52,943 bytes: ftp://ftp.uk.linux.org/pub/linux/Networking/netkit/
- Net−tools (1.57) 262,342 bytes: http://www.tazenda.demon.co.uk/phil/net−tools/

---

# Chapter 4. Preparing a new partition

# Introduction

In this chapter the partition that is going to host the LFS system is going to be prepared. A new partition will be created, an ext2 file system will be created on it and the directory structure will be created. When this is done, we can move on to the next chapter and start building a new Linux system from scratch.

---

# Creating a new partition

Before we can build our new Linux system, we need to have an empty Linux partition on which we can build our new system. I recommend a partition size of around 750 MB. This gives you enough space to store all the tarballs and to compile all packages without worrying running out of the necessary temporary disk sapce. If you already have a Linux Native partition available, you can skip this subsection.

Start the fdisk program (or some other fdisk program you prefer) with the appropriate hard disk as the option (like /dev/hda if you want to create a new partition on the primary master IDE disk). Create a Linux Native partition, write the partition table and exit the fdisk program. If you get the message that you need to reboot your system to ensure that that partition table is updated, then please reboot your system now before continuing. Remember what your new partition's designation is. It could be something like hda11 (as it is in my case). This newly created partition will be referred to as the LFS partition in this book.

---

# Creating a ext2 file system on the new partition

Once the partition is created, we have to create a new ext2 file system on that partition. To create a new ext2 file system we use the mke2fs command. Enter the new partition as the only option and the file system will be created. If your partition is hda11, you would run:

```
root:~# mke2fs /dev/hda11
```

# Mounting the new partition

Now that we have created the ext2 file system, it is ready for use. All we have to do to be able to access it (as in reading from and writing date to it) is mounting it. If you mount it under /mnt/lfs, you can access this partition by going to the /mnt/lfs directory and then do whatever you need to do. This document will assume that you have mounted the partition on a subdirectory under /mnt. It doesn't matter which directory you choose (or you can use just the /mnt directory as the mount point) but this book will assume /mnt/lfs in the commands it tells you to execute.

Create the /mnt/lfs directory by runnning:

```
root:~#    mkdir -p /mnt/lfs
```

Now mount the LFS partition by running:

```
root:~#    mount /dev/xxx /mnt/lfs
```

Replace "xxx" by your partition's designation.

This directory (/mnt/lfs) is the $LFS variable you have read about earlier. So if you read somewhere to "cp inittab $LFS/etc" you actually will type "cp inittab /mnt/lfs/etc".

---

# Creating directories

Let's create the directory tree on the LFS partition according to the FHS standard which can be found at http://www.pathname.com/fhs/. Issuing the following commands will create the necessary directories:

```
root:~#   cd $LFS
root:lfs#   mkdir bin boot dev etc home lib mnt proc root
sbin tmp usr  var
root:lfs#   cd $LFS/usr
root:usr#   mkdir bin etc include lib local sbin share src
tmp var
root:usr#   ln -s share/man man
root:usr#   ln -s share/doc doc
root:usr#   ln -s share/info info
root:usr#   cd $LFS/usr/share
root:share#   mkdir dict doc info locale man nls misc
terminfo zoneinfo
root:share#   cd $LFS/usr/share/man
root:man#   mkdir man1 man2 man3 man4 man5 man6 man7 man8
root:man#   cd $LFS/usr/local
root:local#    mkdir bin etc include lib local sbin share src
tmp var
root:local#    ln -s share/man man
root:local#    ln -s share/doc doc
root:local#    ln -s share/info info
root:local#    cd $LFS/usr/local/share
root:share#    mkdir dict doc info locale man nls misc
terminfo zoneinfo
root:share#    cd $LFS/usr/local/share/man
root:man#    mkdir man1 man2 man3 man4 man5 man6 man7 man8
root:man#   cd $LFS/var
root:var#   mkdir lock log run spool tmp
```

Normally directories are created with permission mode 755, which isn't desired for all directories. I haven't checked the FHS if they suggest default modes for certain directories, so I'll just change the modes for two directories. The first change is a mode 0750 for the $LFS/root directory. This is to make sure that not just everybody can enter the /root directory (the same you would do with /home/username directories). The second change is a mode 1777 for the $LFS/tmp directory. This way every user can write stuff to the /tmp directory if they need to. The sticky (1) bit makes sure users can't delete other user's file which they normally can do because the directory is set in such a way that every body (owner, group, world) can write to that directory.

```
root:~#   cd $LFS
```

```
root:lfs#   chmod 0750 root
root:lfs#   chmod 0555 proc
root:lfs#   chmod 1777 tmp usr/tmp
```

Now that the directories are created, copy the source files you have downloaded in chapter 3 to some subdirectory under $LFS/usr/src (you will need to create this subdirectory yourself).

---

# Chapter 5. Installing basic system software

# How and why things are done

In this chapter we will install all the software that belongs to a basic Linux system. After you're done with this chapter you have a fully working Linux system. The remaining chapters deal with setting up networking, creating the boot scripts and adding an entry to lilo.conf so that you can boot your LFS system.

This chapter is devided in two chunks. The first part installs a few necessary programs on the LFS system. These programs are needed to install the rest of the programs that belong to a basic system. When the first part is done, we will enter a chroot'ed environment. This means that we start a shell with $LFS as the root directory (instead of the usual / directory as the root directory). This has the same effect as rebooting the computer into the LFS system, but this way we don't have to reboot. If something goes wrong, you don't need to reboot back in the normal Linux system to fix whatever you need to fix. You just open a new shell on a virtual console, or start a new xterm and you can do what you need to do.

The software in the first part will be linked statically. These programs will be re−installed in the second part and linked dynamically. The reason for the static version first is that there is a chance that our normal Linux system and your LFS system aren't using the same C Library versions. If the programs in the first part are linked against an older C library version, those program might not work well on the LFS system.

The key to learn what makes Linux tick is to know exactly what packages are used for and why you or the system needs them. In depth descriptions of the package are provided in Appendix A.

---

# Debugging symbols and compiler optimizations

Most programs and libraries by default are compiled with debugging symbols and optimizing level 2 (gcc options −g and −O2) and are compiled for a specific CPU. On Intel platforms software is compiled for i386 processors by default. If you don't wish to run software on other machines other than your own, you might want to change the default compiler options so that they will be compiled with a higher optimization level, no debugging symbols and generate code for your specific architecture. Let me first explain what debugging symbols are.

A program compiled with debugging symbols means you can run a program or library through a debugger and the debugger's output will be user friendlier. These debugging symbols also enlarge the program or library significantly.

To remove debugging symbols from a binary (must be an a.out or ELF binary) run **`strip --strip-debug filename`** You can use wild cards if you need to strip debugging symbols from multiple files (use something like strip −−strip−debug $LFS/usr/bin/*). Another, easier, options is just not to compile programs with debugging symbols. Most people will probably never use a debugger on software, so by leaving those symbols out you can save a lot of diskspace.

Before you wonder if these debugging symbols would make a big difference, here are some statistics:

- A static Bash binary with debugging symbols: 2.3MB
- A static Bash binary without debugging symbols: 645KB
- A dynamic Bash binary with debugging symbols: 1.2MB
- A dynamic Bash binary without debugging symbols: 478KB
- $LFS/lib and $LFS/usr/lib (glibc and gcc files) with debugging symbols: 87MB
- $LFS/lib and $LFS/usr/lib (glibc and gcc files) without debugging symbols: 16MB

Sizes may vary depending on which compiler was used and which C library version was used to link dynamic programs against, but your results will be similar if you compare programs with and without debugging symbols. After I was done with this chapter and stripped all debugging symbols from all LFS binaries and libraries I regained a little over 102 MB of disk space. Quite the difference.

There are a few ways to change the default compiler options. One way is to edit every Makefile file you can find in a package, look for the CFLAGS and CXXFLAGS variables (a well designed package uses the CFLAGS variable to define gcc compiler options and CXXFLAGS to define g++ compiler options) and change their values. Packages like binutils, gcc, glibc and others have a lot of Makefile files in a lot of subdirectories so this would take a lot of time to do. Instead there's an easier way to do things: create the CFLAGS and CXXFLAGS environment variables. Most configure scripts read the CFLAGS and

CXXFLAGS variables and use them in the Makefile files. A few packages don't follow this convention and those package require manual editing.

The optimization options presented here are a minimal set of optimizations. This is to ensure that it will work on most platforms. Run the following command in the shell that you are going to use to compile the software in. If you exit the shell to, for example, pause compilation and continue later, make sure you execute the following commands again when you start compiling again (you only need to execute it once when you open a new virtual console, xterm, Eterm or some other terminal emulation program). Or you can insert these commands into your `/etc/profile`, `$HOME/.bashrc` or similar files. Run the following commands to setup the environment variables:

```
root:~#    export CFLAGS="-O3 -mcpu=xxx -march=yyy"
root:~#    export CXXFLAGS="-O3 -mcpu=xxx -march=yyy"
```

Replace xxx and yyy with the appropriate cpu idenfifiers such as i686. More information on what values these variables can have can be found in the GCC info page.

Please keep in mind that if you find that a package doesn't compile and gives errors like "segmentation fault, core dumped" it's most likely got to do with these compiler optimizations. Try lowering the optimizing level by changing −O3 to −O2. If that doesn't work try −O or leave it out all together. Also try changing the −mcpu and −march variables. Compilers are very sensitive to certain hardware too. Bad memory can cause compilation problems when a high level of optimization is used, like the −O3 setting. The fact that I don't have any problems compiling everything with −O3 doesn't mean you won't have any problems either. Another problem can be the Binutils version that's installed on your system which often causes compilation problems in Glibc (most noticable in RedHat because RedHat often uses beta software which aren't always very stable. "RedHat likes living on the bleeding edge, but leaves the bleeding up to you" (quoted from somebody on the lfs−discuss mailinglist).

---

# Preparing the LFS system

We're about to start with installing the first set of packages. These packages will be, as previously explained, linked statically.

Before we start, make sure you have the CFLAGS and CXXFLAGS environment variables setup if you plan on using compiler optimizations.

---

# Installing Bash

## Installing Bash

Install Bash by running the following commands:

```
root:bash-2.04#   ./configure --enable-static-link \
> --prefix=/usr --disable-nls
root:bash-2.04#   make
root:bash-2.04#   make prefix=$LFS/usr install
root:bash-2.04#   cd $LFS/usr/bin
root:bin#   mv bash bashbug $LFS/bin
root:bin#   cd $LFS/bin
root:bin#   ln -s bash sh
```

---

## Contents

The Bash package contains the bash program

---

## Description

Bash is the Bourne–Again SHell, which is a widely used command interpreter on Unix systems. Bash is a program that reads from standard input, the keyboard. You type something and the program will evaluate what you have typed and do something with it, like running a program.

---

# Installing Binutils

## Installing Binutils

Install Binutils by running the following commands:

```
root:binutils-2.10#    ./configure --prefix=/usr --disable-nls
root:binutils-2.10#    make -e LDFLAGS=-all-static tooldir=/usr
root:binutils-2.10#  make -e prefix=$LFS/usr tooldir=$LFS/usr
install
```

---

## Description

The Binutils package contains the ld, as, ar, nm, objcopy, objdump, ranlib, size, strings, strip, c++filt, addr2line and nlmconv programs

---

## Description

### ld

ld combines a number of object and archive files, relocates their data and ties up symbol references. Often the last step in building a new compiled program to run is a call to ld.

---

### as

as is primarily intended to assemble the output of the GNU C compiler gcc for use by the linker ld.

---

### ar

The ar program creates, modifies, and extracts from archives. An archive is a single file holding a collection of other files in a structure that makes it possible to retrieve the original individual files (called members of the archive).

---

### nm

nm lists the symbols from object files.

---

## objcopy

objcopy utility copies the contents of an object file to another. objcopy uses the GNU BFD Library to read and write the object files. It can write the destination object file in a format different from that of the source object file.

---

## objdump

objdump displays information about one or more object files. The options control what particular information to display. This information is mostly useful to programmers who are working on the compilation tools, as opposed to programmers who just want their program to compile and work.

---

## ranlib

ranlib generates an index to the contents of an archive, and stores it in the archive. The index lists each symbol defined by a member of an archive that is a relocatable object file.

---

## size

size lists the section sizes −−and the total size−− for each of the object files objfile in its argument list. By default, one line of output is generated for each object file or each module in an archive.

---

## strings

For each file given, strings prints the printable character sequences that are at least 4 characters long (or the number specified with an option to the program) and are followed by an unprintable character. By default, it only prints the strings from the initialized and loaded sections of object files; for other types of files, it prints the strings from the whole file.

strings is mainly useful for determining the contents of non−text files.

---

## strip

strip discards all or specific symbols from object files. The list of object files may include archives. At least one object file must be given. strip modifies the files named in its argument, rather than writing modified copies under different names.

---

## c++filt

The C++ language provides function overloading, which means that you can write many functions with the same name (providing each takes parameters of different types). All C++ function names are encoded into a low−level assembly label (this process is known as mangling). The c++filt program does the inverse

mapping: it decodes (demangles) low−level names into user−level names so that the linker can keep these overloaded functions from clashing.

## addr2line

addr2line translates program addresses into file names and line numbers. Given an address and an executable, it uses the debugging information in the executable to figure out which file name and line number are associated with a given address.

## nlmconv

nlmconv converts relocatable object files into the NetWare Loadable Module files, optionally reading header files for NLM header information.

# Installing Bzip2

## Installing Bzip2

Install Bzip2 by running the following commands:

```
root:bzip2-1.0.0#   sed \
> s/"\$(CC) \$(CFLAGS) -o"/"\$(CC) \$(CFLAGS) \$(LDFLAGS)
-o"/ \
> Makefile >Makefile2
root:bzip2-1.0.1#   mv Makefile2 Makefile
root:bzip2-1.0.1#   make LDFLAGS=-static
root:bzip2-1.0.1#   make PREFIX=$LFS/usr install
root:bzip2-1.0.1#   cd $LFS/usr/bin
root:bin#   mv bzcat bunzip2 bzip2 bzip2recover $LFS/bin
```

---

## Contents

The Bzip2 packages contains the bzip2, bunzip2, bzcat and bzip2recover programs.

---

## Description

### Bzip2

bzip2 compresses files using the Burrows–Wheeler block sorting text compression algorithm, and Huffman coding. Compression is generally considerably better than that achieved by more conventional LZ77/LZ78–based compressors, and approaches the performance of the PPM family of statistical compressors.

---

### Bunzip2

Bunzip2 decompresses files that are compressed with bzip2.

---

### bzcat

bzcat (or bzip2 –dc) decompresses all specified files to the standard output.

---

## bzip2recover

bzip2recover recovers data from damaged bzip2 files.

# Installing Diffutils

## Installing Diffutils

Install Diffutils by running the following commands:

```
root:diffutils-2.7#
CPPFLAGS=-Dre_max_failures=re_max_failures2 \
> ./configure --prefix=/usr --disable-nls
root:diffutils-2.7#   make LDFLAGS=-static
root:diffutils-2.7#   make prefix=$LFS/usr install
```

---

## Contents

The Diffutils packagec contains the cmp, diff, diff3 and sdiff programs.

---

## Description

### cmp and diff

cmp and diff both compare two files and report their differences. Both programs have extra options which compare files in different situations.

---

### diff3

The difference between diff and diff3 is that diff comprares 2 files, diff3 compares 3 files.

---

### sdiff

sdiff merges two two files and interactively outputs the results.

---

# Installing Fileutils

## Installing Fileutils

Install Fileutils by running the following commands:

```
root:fileutils-4.0#   ./configure --disable-nls --prefix=/usr
root:fileutils-4.0#   make -e LDFLAGS=-static
root:fileutils-4.0#   make -e prefix=$LFS/usr install
root:fileutils-4.0#   cd $LFS/usr/bin
root:bin#   mv chgrp chmod chown cp dd df dir $LFS/bin
root:bin#   mv dircolors du install ln ls mkdir mkfifo
$LFS/bin
root:bin#   mv mknod mv rm rmdir sync touch vdir $LFS/bin
```

---

## Contents

The Fileutils package contains the chgrp, chmod, chown, cp, dd, df, dir, dircolors, du, install, ln, ls, mkdir, mkfifo, mknod, mv, rm, rmdir, sync, touch and vdir programs.

---

## Description

### chgrp

chgrp changes the group ownership of each given file to the named group, which can be either a group name or a numeric group ID.

---

### chmod

chmod changes the permissions of each given file according to mode, which can be either a symbolic representation of changes to make, or an octal number representing the bit pattern for the new permissions.

---

### chown

chown changes the user and/or group ownership of each given file.

---

## cp

cp copies files from one place to another.

---

## dd

dd copies a file (from the standard input to the standard output, by default) with a user−selectable blocksize, while optionally performing conversions on it.

---

## df

df displays the amount of disk space available on the filesystem containing each file name argument. If no file name is given, the space available on all currently mounted filesystems is shown.

---

## ls, dir and vdir

dir and vdir are versions of ls with different default output formats. These programs list each given file or directory name. Directory contents are sorted alphabetically. For ls, files are by default listed in columns, sorted vertically, if the standard output is a terminal; otherwise they are listed one per line. For dir, files are by default listed in columns, sorted vertically. For vdir, files are by default listed in long format.

---

## dircolors

dircolors outputs commands to set the LS_COLOR environment variable. The LS_COLOR variable is use to change the default color scheme used by ls and related utilities.

---

## du

du displays the amount of disk space used by each argument and for each subdirectory of directory arguments.

---

## install

install copies files and sets their permission modes and, if possible, their owner and group.

---

## ln

ln makes hard or soft (symbolic) links between files.

---

## mkdir

mkdir creates directories with a given name.

---

## mkfifo

mkfifo creates a FIFO with each given name.

---

## mknod

mknod creates a FIFO, character special file, or block special file with the given file name.

---

## mv

mv moves files from one directory to another or renames files, depending on the arguments given to mv.

---

## rm

rm removes files or directories.

---

## rmdir

rmdir removes directories, if they are empty.

---

## sync

sync forces changed blocks to disk and updates the super block.

---

## touch

touch changes the access and modification times of each given file to the current time. Files that do not exist are created empty.

---

# Installing GCC on the normal system if necessary

## Installing GCC on the normal system if necessary

In order to compile Glibc−2.1.3 later on you need to have gcc−2.95.2 installed. Although any GCC version above 2.8 would do, 2.95.2 is the highly recommended version to use. egcs−2.91.x is also known to work. If you don't have gcc−2.95.x or egcs−2.91.x you need to install gcc−2.95.2 on your normal sytem before you can compile Glibc later in this chapter.

To find out which compiler version your systems has, run the following command:

```
root:~#   gcc --version
```

If you normal Linux system does not have gcc−2.95.x or egcs−2.91.x installed you need to install it now. We won't replace the current compiler on your system, but instead we will install gcc in a separate directory (/usr/local/gcc2952). This way no binaries or header files will be replaced.

After you unpacked the gcc−2.95.2 archive don't enter the newly created gcc−2.95.2 directory but stay in the $LFS/usr/src directory. Install GCC by running the following commands:

```
root:src#   mkdir $LFS/usr/src/gcc-build
root:src#   cd $LFS/usr/src/gcc-build
root:gcc-build#   ../gcc-2.95.2/configure \
> --prefix=/usr/local/gcc2952 \
> --with-local-prefix=/usr/local/gcc2952  \
> --with-gxx-include-dir=/usr/local/gcc2952/include/g++  \
> --enable-shared --enable-languages=c,c++
root:gcc-build#   make bootstrap
root:gcc-build#   make install
```

---

## Contents

The GCC package contains compilers, preprocessors and the GNU C++ Library.

---

## Description

## Compiler

A compiler translates source code in text format to a format that a computer understands. After a source code file is compiled into an object file, a linker will create an executable file from one or more of these compiler generated object files.

---

## Pre−processor

A pre−processor pre−processes a source file, such as including the contents of header files into the source file. You generally don't do this yourself to save yourself a lot of time. You just insert a line like #include <filename>. The pre−processor file insert the contents of that file into the source file. That's one of the things a pre−processor does.

---

## C++ Library

The C++ library is used by C++ programs. The C++ library contains functions that are frequently used in C++ programs. This way the programmer doens't have to write certain functions (such as writing a string of text to the screen) from scratch every time he creates a program.

---

# Installing GCC on the LFS system

## Installing GCC on the LFS system

After you unpacked the gcc−2.95.2 archive don't enter the newly created gcc−2.95.2 directory but stay in the $LFS/usr/src directory. Install GCC by running the following commands:

```
root:src#   mkdir $LFS/usr/src/gcc-build
root:src#   cd $LFS/usr/src/gcc-build
root:gcc-build#   ../gcc-2.95.2/configure --prefix=/usr \
> --with-gxx-include-dir=/usr/include/g++ \
> --enable-languages=c,c++ --disable-nls
root:gcc-build#   make -e LDFLAGS=-static bootstrap
root:gcc-build#   make prefix=$LFS/usr
local_prefix=$LFS/usr/local \
> gxx_include_dir=$LFS/usr/include/g++ install
```

---

### Creating necessary symlinks

The system needs a few symlinks to ensure every program is able to find the compiler and the pre−processor. Some programs run the cc program, others run the gcc program. Some programs expect the cpp program in /lib and others expect to find it in /usr/bin. Create those symlinks by running:

```
root:~#   cd $LFS/lib
root:lib#   ln -s ../usr/lib/gcc-lib/<host>/2.95.2/cpp cpp
root:lib#   cd $LFS/usr/lib
root:lib#   ln -s gcc-lib/<host>/2.95.2/cpp cpp
root:lib#   cd $LFS/usr/bin
root:bin#   ln -s gcc cc
```

Replace <host> with the directory where the gcc−2.95.2 files are installed (which is i686−unknown−linux in my case).

---

# Contents

The GCC package contains compilers, preprocessors and the GNU C++ Library.

---

# Description

## Compiler

A compiler translates source code in text format to a format that a computer understands. After a source code file is compiled into an object file, a linker will create an executable file from one or more of these compiler generated object files.

---

## Pre−processor

A pre−processor pre−processes a source file, such as including the contents of header files into the source file. You generally don't do this yourself to save yourself a lot of time. You just insert a line like #include <filename>. The pre−processor file insert the contents of that file into the source file. That's one of the things a pre−processor does.

---

## C++ Library

The C++ library is used by C++ programs. The C++ library contains functions that are frequently used in C++ programs. This way the programmer doens't have to write certain functions (such as writing a string of text to the screen) from scratch every time he creates a program.

---

# Installing Linux Kernel

## Installing Linux Kernel

We won't be compiling a new kernel image yet. We'll do that after we have finished the installation of the basic system software in this chapter. But because certain software need the kernel header files, we're going to unpack the kernel archive now and set it up so that we can compile package that need the kernel.

Create the kernel configuration file by running the following command:

```
root:linux#   yes "" | make config
```

Ignore the warning *Broken pipe* you might see at the end. Now run the following commands to set up all the dependencies correctly:

```
root:linux#   make dep
```

Now that that's done, we need to create the `$LFS/usr/include/linux` and the `$LFS/usr/include/asm` symlinks. Create them by running the following commands:

```
root:~#   cd $LFS/usr/include
root:include#   ln -s ../src/linux/include/linux linux
root:include#   ln -s ../src/linux/include/asm asm
```

---

## Contents

The Linux kernel package contains the Linux kernel.

---

## Description

The Linux kernel is at the core of every Linux system. It's what makes Linux tick. When you turn on your computer and boot a Linux system, the very first piece of Linux software that gets loaded is the kernel. The kernel initializes the system's hardware components such as serial ports, parallel ports, sound cards, network cards, IDE controllers, SCSI controllers and a lot more. In a nutshell the kernel makes the hardware available

so that the software can run.

# Installing Glibc

## A note on the glibc−crypt package

An excerpt from the README file that is distributed with the glibc−crypt package:

The add−on is not included in the main distribution of the GNU C library because some governments, most notably those of France, Russia, and the US, have very restrictive rules governing the distribution and use of encryption software. Please read the node "Legal Problems" in the manual for more details.

In particular, the US does not allow export of this software without a licence, including via the Internet. So please do not download it from the main FSF FTP site at ftp.gnu.org if you are outside the US. This software was completely developed outside the US.

"This software" refers to the glibc−crypt package at ftp://ftp.gwdg.de/pub/linux/glibc/. This law only affects people who don't live in the US. It's not prohibited to import DES software, so if you live in the US you can import the file safely from Germany without breaking cryptographic laws. This law is changing lately and I don't know what the status of it is at the moment. Better be safe than sory.

---

## Installing Glibc

Unpack the glibc−crypt and glibc−linuxthreads in the glibc−2.1.3 directory, not in /usr/src. Don't enter the created directories. Just unpack them and leave it with that.

A few default parameters of Glibc need to be changed, such as the directory where the shared libraries are supposed to be installed in and the directory that contains the system configuration files. For this purpose you need to create the `$LFS/usr/src/glibc−build` directory and in that directory you create a new file `configparms` containing the following:

```
# Begin configparms

slibdir=/lib
sysconfdir=/etc

# End configparms
```

If your system had already a suitable GCC version installed, change to the `$LFS/usr/src/glibc−build` directory and install Glibc by running the following commands:

```
root:glibc−build#    ../glibc−2.1.3/configure \
```

```
> --prefix=/usr --enable-add-ons \
> --with-headers=$LFS/usr/include
root:glibc-build#   make
root:glibc-build#   make install_root=$LFS install
```

If you're getting errors related to illegal character 45 in some variable name during the compilation, apply the Glibc patch to the glibc-2.1.3 directory by running the following command:

```
root:glibc-2.1.3#   patch -Np1 -i ../glibc-2.1.3.patch
```

If your system didn't have a suitable GCC version installed, change to the `$LFS/usr/src/glibc-build` directory and install Glibc using the gcc-2.95.2 you just installed by running the following commands:

```
root:glibc-build#   CC=/usr/local/gcc2952/bin/gcc \
> ../glibc-2.1.3/configure --prefix=/usr  --enable-add-ons \
> --with-headers=$LFS/usr/include
root:glibc-build#   make
root:glibc-build#   make install_root=$LFS install
```

If you're getting errors related to illegal character 45 in some variable name during the compilation, apply the Glibc patch to the glibc-2.1.3 directory by running the following command:

```
root:glibc-2.1.3#    patch -Np1 -i ../glibc-2.1.3.patch
```

---

# Copying old NSS library files

If your normal Linux system runs glibc-2.0, you need to copy the NSS library files to the LFS partition. Certain statically linked programs still depend on the NSS library, especially programs that need to lookup usernames,userid's and groupid's. You can check which C library version your normal Linux system uses by running:

```
root:~# ls /lib/libc*
```

Your system uses glib−2.0 if there is a file that looks like *libc−2.0.7.so*

Your system uses glibc−2.1 if there is a file that looks like *libc−2.1.3.so*

Of course, the micro version number can be different (you could have libc−2.1.2 or libc−2.1.1 for example).

If you have a libc−2.0.x file copy the NSS library files by running:

```
root:~# cp -av /lib/libnss*  $LFS/lib
```

There are a few distributions that don't have files from which you can see which version of the C Library it is. If that's the case, it will be hard to determine which C library version you exactly have. Try to obtain this information using your distribution's installation tool. It often says which version it has available. If you can't figure out at all which C Library version is used, then copy the NSS files anyway and hope for the best. That's the best advise I can give I'm afraid.

## Contents

The Glibc package contains the GNU C Library.

## Description

The C Library is a collection of commonly used functions in programs. This way a programmer doens't need to create his own functions for every single task. The most common things like writing a string to your screen are already present and at the disposal of the programmer.

The C library (actually almost every library) come in two flavours: dynamic ones and static ones. In short when a program uses a static C library, the code from the C library will be copied into the executable file. When a program uses a dynamic library, that executable will not contain the code from the C library, but instead a routine that loads the functions from the library at the time the program is run. This means a significant decrease in the file size of a program. If you don't understand this concept, you better read the documentation that comes with the C Library as it is too complicated to explain here in one or two lines.

# Installing Grep

## Installing Grep

Install Grep by running the following commands:

```
root:grep-2.4.2#
CPPFLAGS=-Dre_max_failures=re_max_failures2 \
> ./configure --prefix=/usr --disable-nls
root:grep-2.4.2#   make LDFLAGS=-static
root:grep-2.4.2#   make prefix=$LFS/usr install
```

---

## Contents

The grep package contains the egrep, fgrep and grep programs.

---

## Description

### egrep

egrep prints lines from files matching an extended regular expression pattern.

---

### fgrep

fgrep prints lines from files matching a list of fixed strings, separated by newlines, any of which is to be matched.

---

### grep

grep prints lines from files matching a basic regular expression pattern.

---

# Installing Gzip

## Installing Gzip

Install Gzip by running the following commands:

```
root:gzip-1.2.4a#   ./configure --prefix=/usr --disable-nls
root:gzip-1.2.4a#   make LDFLAGS=-static
root:gzip-1.2.4a#   make prefix=$LFS/usr install
root:gzip-1.2.4a#   cd $LFS/usr/bin
root:bin#   cp gunzip gzip $LFS/bin
root:bin#   rm gunzip gzip
```

This package is known to cause compilation problems on certain platforms. If you're having trouble compiling this package as well, you can download a patch from
http://www.linuxfromscratch.org/download/gzip−1.2.4a.patch.gz

Install this patch by running the following command:

```
root:gzip-1.2.4a#   patch −Np1 −i ../gzip−1.2.4a.patch
```

Now recompile the package using the same commands as above.

---

## Contents

The Gzip package contains the gunzip, gzexe, gzip, zcat, zcmp, zdiff, zforece, zgrep, zmore and znew programs.

---

## Description

### gunzip

gunzip decompresses files that are compressed with gzip.

---

## gzexe

gzexe allows you to compress executables in place and have them automatically uncompress and execute when you run them (at a penalty in performance).

---

## gzip

gzip reduces the size of the named files using Lempel−Ziv coding (LZ77).

---

## zcat

zcat uncompresses either a list of files on the command line or its standard input and writes the uncompressed data on standard output

---

## zcmp

zcmp invokes the cmp program on compressed files.

---

## zdiff

zdiff invokes the diff program on compressed files.

---

## zforce

zforce forces a .gz extension on all gzip files so that gzip will not compress them twice. This can be useful for files with names truncated after a file transfer.

---

## zgrep

zgrep invokes the grep program on compressed files.

---

## zmore

Zmore is a filter which allows examination of compressed or plain text files one screenful at a time on a soft−copy terminal (similar to the more program).

---

## znew

Znew recompresses files from .Z (compress) format to .gz (gzip) format.

# Installing Make

## Installing Make

Install Make by running the following commands:

```
root:make-3.79.1#   ./configure --prefix=/usr --disable-nls
root:make-3.79.1#   make LDFLAGS=-static
root:make-3.79.1#   make prefix=$LFS/usr install
```

---

## Contents

The Make package contains the make program.

---

## Description

make determine automatically which pieces of a large program need to be recompiled, and issue the commands to recompile them.

---

# Installing Sed

## Installing Sed

Install Sed by running the following commands:

```
root:sed-3.02#   CPPFLAGS=-Dre_max_failures=re_max_failures2 \
> ./configure --prefix=/usr --disable-nls
root:sed-3.02#   make LDFLAGS=-static
root:sed-3.02#   make prefix=$LFS/usr install
root:sed-3.02#   mv $LFS/usr/bin/sed $LFS/bin
```

---

## Contents

The Sed package contains the sed program.

---

## Description

sed is a stream editor. A stream editor is used to perform basic text transformations on an input stream (a file or input from a pipeline).

---

# Installing Shellutils

## Installing Shellutils

Install Shellutils by running the following commands:

```
root:sh-utils-2.0#   ./configure --prefix=/usr --disable-nls
root:sh-utils-2.0#   make LDFLAGS=-static
root:sh-utils-2.0#   make prefix=$LFS/usr install
root:sh-utils-2.0#   cd $LFS/usr/bin
root:/bin#   mv date echo false pwd stty $LFS/bin
root:bin#   mv su true uname hostname $LFS/bin
```

---

## Contents

The Shellutils package contains the basename, chroot, date, dirname, echo, env, expr, factor, false, groups, hostid, hostname, id, logname, nice, nohup, pathchk, pinky, printenv, printf, pwd, seq, sleep, stty, su, tee, test, true, tty, uname, uptime, users, who, whoami and yes programs.

---

## Description

### basename

basename strips directory and suffixes from filenames.

---

### chroot

chroot runs a command or interactive shell with special root directory.

---

### date

date displays the current time in a specified format, or sets the system date.

---

### dirname

dirname strips non−directory suffixes from file name.

---

## echo

echo displays a line of text.

## env

env runs a program in a modified environment.

## expr

expr evaluates expressions.

## factor

factor prints the prime factors of all specified integer numbers.

## false

false always exits with a status code indicating failure.

## groups

groups prints the groups a user is in.

## hostid

hostid prints the numeric identifier (in hexadecimal) for the current host.

## hostname

hostname sets or prints the name of the current host system

## id

id prints the real and effective UIDs and GIDs of a user or the current user.

## logname

logname prints the current user's login name.

## nice

nice runs a program with modified scheduling priority.

## nohup

nohup runs a command immune to hangups, with output to a non−tty

## pathchk

pathchk checks whether file names are valid or portable.

## pinky

pinky is a lightweight finger utility which retrieves information about a certain user

## printenv

printenv prints all or part of the environment.

## printf

printf formats and print data (the same as the printf C function).

## pwd

pwd prints the name of the current/working directory

## seq

seq prints numbers in a certain range with a certain increment.

## sleep

sleep delays for a specified amount of time.

## stty

stty changes and prints terminal line settings.

## su

su runs a shell with substitute user and group IDs

## tee

tee reads from standard input and write to standard output and files.

## test

test checks file types and compares values.

## true

True always exitx with a status code indicating success.

## tty

tty prints the file name of the terminal connected to standard input.

## uname

uname prints system information.

## uptime

uptime tells how long the system has been running.

## users

users prints the user names of users currently logged in to the  current host.

---

## who

who shows who is logged on.

---

## whoami

whoami prints your effective userid.

---

## yes

yes outputs a string repeatedly until killed.

---

# Installing Tar

## Installing Tar

Install Tar by running the following commands:

```
root:tar-1.13#   ./configure --prefix=/usr --disable-nls
root:tar-1.13#   make LDFLAGS=-static
root:tar-1.13#   make prefix=$LFS/usr install
root:tar-1.13#   mv $LFS/usr/bin/tar $LFS/bin
```

---

## Contents

The tar package contains the tar and rmt programs.

---

## Description

### tar

tar is an archiving program designed to store and extract files from an archive file known as a tarfile.

---

### rmt

rmt is a program used by the remote dump and restore programs in manipulating a magnetic tape drive through an interprocess communication connection.

---

# Installing Textutils

## Installing Textutils

Install Textutils by running the following commands:

```
root:textutils-2.0#   ./configure --prefix=/usr --disable-nls
root:textutils-2.0#   make LDFLAGS=-static
root:textutils-2.0#   make prefix=$LFS/usr install
root:textutils-2.0#   mv $LFS/usr/bin/cat $LFS/bin
```

---

## Contents

The Textutils package contains the cat, cksum, comm, split, cut, expand, fmt, fold, head, join, md5sum, nl, od, paste, pr, ptx, sort, split, sum, tac, tail, tr, tsort, unexpand, uniq and wc programs.

---

## Description

### cat

cat concatenates file(s) or standard input to standard output.

---

### cksum

cksum prints CRC checksum and byte counts of each specified file.

---

### comm

comm compares two sorted files line by line.

---

### csplit

cplit outputs pieces of a file separated by (a) pattern(s) to files xx01, xx02, ..., and outputs byte counts of each piece to standard output.

---

## cut

cut prints selected parts of lines from specified files to standard output.

## expand

expand converts tabs in files to spaces, writing to standard output.

## fmt

fmt reformats each paragraph in the specified file(s), writing to standard output.

## fold

fold wraps input lines in each specified file (standard input by default), writing to standard output.

## head

Print first xx (10 by default) lines of each specified file to standard output.

## join

join joins lines of two files on a common field.

## md5sum

md5sum prints or checks MD5 checksums.

## nl

nl writes each specified file to standard output, with line numbers added.

## od

od writes an unambiguous representation, octal bytes by default, of a specified file to standard output.

## paste

paste writes lines consisting of the sequentially corresponding lines from each specified file, separated by TABs, to standard output.

## pr

pr paginates or columnates files for printing.

## ptx

ptx produces a permuted index of file contents.

## sort

sort writes sorted concatenation of files to standard output.

## split

split outputs fixed−size pieces of an input file to PREFIXaa, PREFIXab, ...

## sum

sum prints checksum and block counts for each specified file.

## tac

tac writes each specified file to standard output, last line first.

## tail

tail print the last xx (10 by default) lines of each specified file to standard output.

## tr

tr translates, squeezes, and/or deletes characters from standard input, writing to standard output.

## tsort

tsort writes totally ordered lists consistent with the partial ordering in specified files.

## unexpand

unexpand converts spaces in each file to tabs, writing to standard output.

## uniq

uniq discards all but one of successive identical lines from files or standard input and writes to files or standard output.

## wc

wc prints line, word, and byte counts for each specified file, and a total line if more than one file is specified.

# Creating passwd and group files

In order for user and group root to be recognized and to be able to logon it needs an entry in the /etc/passwd and /etc/group file. Besides the groupt root a couple of other groups are recommended and needed by packages. The groups with their GID's below aren't part of any standard. The LSB only recommends besides a group root a group bin to be present with GID 1. Other group names and GID's can be chosen by yourself. Well written packages don't depend on GID numbers but just use the group name, it doesn't matter all that much what GID a group has. Since there aren't any standards for groups I won't follow any conventions used by Debian, RedHat and others. The groups added here are the groups the MAKEDEV script (the script that creates the device files in the /dev directory) mentions.

Create a new file `$LFS/etc/passwd` by running the following command:

```
root:~#   echo "root:x:0:0:root:/root:/bin/bash" >
$LFS/etc/passwd
```

Create a new file `$LFS/etc/group` by running the following command:

```
root:~#   echo "root:x:0:" > $LFS/etc/group
root:~#   echo "bin:x:1:" >> $LFS/etc/group
root:~#   echo "sys:x:2:" >> $LFS/etc/group
root:~#   echo "kmem:x:3:" >> $LFS/etc/group
root:~#   echo "tty:x:4:" >> $LFS/etc/group
root:~#   echo "uucp:x:5:" >> $LFS/etc/group
root:~#   echo "daemon:x:6:" >> $LFS/etc/group
root:~#   echo "floppy:x:7:" >> $LFS/etc/group
root:~#   echo "disk:x:8:" >> $LFS/etc/group
```

---

# Copying /proc/devices

In order for the MAKEDEV script properly create device entries in /dev it needs access to /proc/devices. We can't mount the proc file system on our LFS system yet so instead we just copy the /proc/devices file to $LFS/proc. This means the $LFS/proc/devices file won't be updated when the kernel updates /proc/devices but I don't see any harm in doing it, since it's only needed during the execution of the MAKEDEV script. Just make sure you don't add or remove any hardware during the next 3 minutes by loading or unloading a kernel module or rebooting your computer before continuing with this book.

Copy the /proc/devices file by running the following command:

```
root:~#   cp /proc/devices $LFS/proc
```

---

# Installing basic system software

The installation of all the software is pretty straightforward and you'll think it's so much easier and shorter to give the generic installation instructions for each package and only explain how to install something if a certain package requires an alternate installation method. Although I agree with you on that, I, however, choose to give the full instructions for each and every package. This is simply to avoid any possible confusion and errors.

---

# Entering the chroot'ed environment

It's time to enter our chroot'ed environment in order to install the rest of the software we need.

Enter the following command to enter the chroot'ed environment. From this point on there's no need to use the $LFS variable anymore, because everything you do will be restricted to the LFS partition (since / is actually /mnt/lfs but the shell doesn't know that).

```
root:~#   chroot $LFS bash --login
```

Now that we are inside a chroot'ed environment, we can continue to install all the basic system software. Make sure you execute all the following commands in this chapter from within the chroot'ed environment.

---

# Creating device files

## Installing MAKEDEV

Install MAKEDEV by running the following commands:

```
root:MAKEDEV-2.5#     cp MAKEDEV /dev
root:MAKEDEV-2.5#     chmod 754 /dev/MAKEDEV
root:MAKEDEV-2.5#    sed s/"# 9"/9/ /dev/MAKEDEV >/dev/MAKEDEV2
root:MAKEDEV-2.5#    mv /dev/MAKEDEV2 /dev/MAKEDEV
```

---

## Creating the /dev entries

Create the device files by running the following commands:

```
root:~#     cd /dev
root:dev#     ./MAKEDEV -v generic
```

Now that the device file entries are created the /proc/devices file can be removed by running the following command:

```
root:~#    rm /proc/devices
```

Please note that this script dates back from 1997 and therefore can be outdated and not support newer hardware. If you need device files which aren't known by this script please read the Documentation/devices.txt file in a Linux source tree. This file lists all the major and minor numbers for all the device files that the kernel knows about. With this list you can create such device files yourself. See the mknod man page for more information on how to make device files yourself.

---

# Installing Ed

## Installing Ed

Install Ed by running the following commands:

```
root:ed-0.2#    ./configure --prefix=/usr
root:ed-0.2#    make
root:ed-0.2#    make install
root:ed-0.2#    cd /usr/bin
root:bin#    mv ed red /bin
```

---

## Contents

The Ed package contains the ed program.

---

## Description

Ed is a line−oriented text editor.  It is used to create, display, modify and otherwise manipulate text files.

---

# Installing Patch

## Installing Patch

Install Patch by running the following commands:

```
root:patch-2.5.4#   ./configure --prefix=/usr
root:patch-2.5.4#   make
root:patch-2.5.4#   make install
```

## Contents

The Patch package contains the patch program.

## Description

The patch program modifies a file according to a patch file. A patch file usually is a list created by the diff program that contains instructions on how an original file needs to be modified. Patch is used a lot for source code patches since it saves time and space. Imagine you have a package that is 1MB in size. The next version of that package only has changes in two files of the first version. You can ship an entirely new package of 1MB or provide a patch file of 1KB which will update the first version to make it identical to the second version. So if you have downloaded the first version already, a patch file can save you a second large download.

# Installing GCC

## Installing GCC

After you unpacked the gcc−2.95.2 archive don't enter the newly created gcc−2.95.2 directory but stay in the /usr/src directory. Install GCC by running the following commands:

```
root:src#   mkdir /usr/src/gcc-build
root:src#   cd /usr/src/gcc-build
root:gcc-build#   ../gcc-2.95.2/configure --prefix=/usr \
> --with-gxx-include-dir=/usr/include/g++ \
> --enable-shared --enable-languages=c,c++
root:gcc-build#   make bootstrap
root:gcc-build#   make install
```

---

## Contents

The GCC package contains compilers, preprocessors and the GNU C++ Library.

---

## Description

### Compiler

A compiler translates source code in text format to a format that a computer understands. After a source code file is compiled into an object file, a linker will create an executable file from one or more of these compiler generated object files.

---

### Pre−processor

A pre−processor pre−processes a source file, such as including the contents of header files into the source file. You generally don't do this yourself to save yourself a lot of time. You just insert a line like #include <filename>. The pre−processor file insert the contents of that file into the source file. That's one of the things a pre−processor does.

---

### C++ Library

The C++ library is used by C++ programs. The C++ library contains functions that are frequently used in C++ programs. This way the programmer doens't have to write certain functions (such as writing a string of text to the screen) from scratch every time he creates a program.

# Installing Bison

## Installing Bison

Install Bison by running the following commands:

```
root:bison-1.28#    ./configure --prefix=/usr \
> --datadir=/usr/share/bison
root:bison-1.28#    make
root:bison-1.28#    make install
```

---

## Contents

The Bison package contains the bison program.

---

## Description

Bison is a parser generator, a replacement for YACC. YACC stands for Yet Another Compiler Compiler. What is Bison then? It is a program that generates a program that analyses the structure of a textfile. Instead of writing the actual program you specify how things should be connected and with those rules a program is constructed that analyses the textfile.

There are alot of examples where structure is needed and one of them is the calculator.

Given the string :

```
1 + 2 * 3
```

You can easily come to the result 7. Why ? Because of the structure. You know how to interpretet the string. The computer doesn't know that and Bison is a tool to help it understand by presenting the string in the following way to the compiler:

```
  +
 / \
1   *
   / \
  2   3
```

You start at the bottom of a tree and you come across the numbers 2 and 3 which are joined by the multiplication symbol, so the computers multiplies 2 and 3. The result of that multiplication is remembered and the next thing that the computer sees is the result of 2*3 and the number 1 which are joined by the add symbol. Adding 1 to the previous result makes 7. In calculating the most complex calculations can be broken down in this tree format and the computer just starts at the bottom and works it's way up to the top and comes with the correct answer. Of course, Bison isn't only used for calculators alone.

---

# Installing Mawk

## Installing Mawk

Install Mawk by running the following commands:

```
root:mawk-1.3.3#    ./configure
root:mawk-1.3.3#    make
root:mawk-1.3.3#    make BINDIR=/usr/bin
MANDIR=/usr/share/man/man1 install
root:mawk-1.3.3#    cd /usr/bin
root:bin#    ln -s mawk awk
```

---

## Contents

The Mawk package contains the mawk program.

---

## Description

### gawk

Mawk is an interpreter for the AWK Programming Language. The AWK language is useful for manipulation of data files, text retrieval and processing, and for prototyping and experimenting with algorithms.

---

# Installing Findutils

## Installing Findutils

Install Findutils by running the following commands:

```
root:findutils-4.1#    ./configure --prefix=/usr
root:findutils-4.1#    make
root:findutils-4.1#    make install
```

This package is known to cause compilation problem. If you're having trouble compiling this package as well, apply the Findutils patch.

Install this patch by running the following command:

```
root:findutils-4.1#    patch -Np1 -i ../findutils-4.1.patch
```

Now recompile the package using the same commands as above.

---

## Contents

The Findutils package contains the find, locate, updatedb and xargs programs.

---

## Description

### Find

The find program searches for files in a directory hierarchy which match a certain criteria. If no criteria is given, it lists all files in the current directory and it's subdirectories.

---

### Locate

Locate scans a database which contain all files and directories on a filesystem. This program lists the files and directories in this database matching a certain criteria. If you're looking for a file this program will scan the database and tell you exactly where the files you requested are located. This only makes sense if your locate database is fairly up−to−date else it will provide you with out−of−date information.

## Updatedb

The updatedb program updates the locate database. It scans the entire file system (including other file system that are currently mounted unless you specify it not to) and puts every directory and file it finds into the database that's used by the locate program which retrieves this information. It's a good practice to update this database once a day so that you are ensured of a database that is up−to−date.

## Xargs

The xargs command applies a command to a list of files. If you need to perform the same command on multiple files, you can create a file that contains all these files (one per line) and use xargs to perform that command on the list.

# Installing Ncurses

## Installing Ncurses

Install Ncurses by running the following commands:

```
root:ncurses-5.1#   ./configure --prefix=/usr --libdir=/lib \
> --with-shared --disable-termcap
root:ncurses-5.1#   make
root:ncurses-5.1#   make install
```

---

## Contents

The Ncurses package contains the ncurses, panel, menu and form libraries. It also contains the tic, infocmp, clear, tput, toe and tset programs.

---

## Description

### The libraries

The libraries that make up the Ncurses library are used to display text (often in a fancy way) on your screen. An example where ncurses is used is in the kernel's "make menuconfig" process. The libraries contain routines to create panels, menu's, form and general text display routines.

---

### Tic

Tic is the terminfo entry−description compiler. The program translates a terminfo file from source format into the binary format for use with the ncurses library routines. Terminfo files contain information about the capabilities of your terminal.

---

### Infocmp

The infocmp program can be used to compare a binary terminfo entry with other terminfo entries, rewrite a terminfo description to take advantage of the use= terminfo field, or print out a terminfo description from the binary file (term) in a variety of formats (the opposite of what tic does).

---

## clear

The clear program clears your screen if this is possible. It looks in the environment for the terminal type and then in the terminfo database to figure out how to clear the screen.

---

## tput

The tput program uses the terminfo database to make the values of terminal−dependent capabilities and information available to the shell, to initialize or reset the terminal, or return the long name of the requested terminal type.

---

## toe

The toe program lists all available terminal types by primary name with descriptions.

---

## tset

The Tset program initializes terminals so they can be used, but it's not widely used anymore. It's provided for 4.4BSD compatibility.

---

# Installing Less

## Installing Less

Install Less by running the following commands:

```
root:less-358#   ./configure --prefix=/usr
root:less-358#   make
root:less-358#   make install
root:less-358#   mv /usr/bin/less /bin
```

---

## Contents

The Less package contains the less program

---

## Description

The less program is a file pager (or text viewer). It displays the contents of a file with the ability to scroll. Less is an improvement on the common pager called "more". Less has the ability to scroll backwards through files as well and it doesn't need to read the entire file when it starts, which makes it faster when you are reading large files.

---

# Installing Groff

## Installing Groff

Install Groff by running the following commands:

```
root:groff-1.16#    ./configure --prefix=/usr
root:groff-1.16#    make
root:groff-1.16#    make install
```

---

## Contents

The Groff packages contains the addftinfo, afmtodit, eqn, grodvi, groff, grog, grohtml, grolj4, grops, grotty, hpftodit, indxbib, lkbib, lookbib, neqn, nroff, pfbtops, pic, psbb, refer, soelim, tbl, tfmtodit and troff programs.

---

## Description

### addftinfo

addftinfo reads a troff font file and adds some additional font−metric information that is used by the groff system.

---

### afmtodit

afmtodit creates a font file for use with groff and grops.

---

### eqn

eqn compiles descriptions of equations embedded within troff input files into commands that are understood by troff.

---

### grodvi

grodvi is a driver for groff that produces TeX dvi format.

---

## groff

groff is a front−end to the groff document formatting system. Normally it runs the troff program and a postprocessor appropriate for the selected device.

## grog

grog reads files and guesses which of the groff options −e, −man, −me, −mm, −ms, −p, −s, and −t are required for printing files, and prints the groff command including those options on the standard output.

## grohtml

grohtml translates the output of GNU troff to html

## grolj4

grolj4 is a driver for groff that produces output in PCL5 format suitable for an HP Laserjet 4 printer.

## grops

grops translates the output of GNU troff to PostScript.

## grotty

grotty translates the output of GNU troff into a form suitable for typewriter−like devices.

## hpftodit

hpftodit creates a font file for use with groff −Tlj4 from an HP tagged font metric file.

## indxbib

indxbib makes an inverted index for the bibliographic databases a specified file for use with refer, lookbib, and lkbib.

## lkbib

lkbib searches bibliographic databases for references that contain specified keys and prints any references found on the standard output.

## lookbib

lookbib prints a prompt on the standard error (unless the standard input is not a terminal), reads from the standard input a line containing a set of keywords, searches the bibliographic databases in a specified file for references containing those keywords, prints any references found on the standard output, and repeats this process until the end of input.

## neqn

It is currently not known what neqn is and what it does.

## nroff

The nroff script emulates the nroff command using groff.

## pfbtops

pfbtops translates a PostScript font in .pfb format to ASCII.

## pic

pic compiles descriptions of pictures embedded within troff or TeX input files into commands that are understood by TeX or troff.

## psbb

psbb reads a file which should be a PostScript document conforming to the Document Structuring conventions and looks for a %%BoundingBox comment.

## refer

refer copies the contents of a file to the standard output, except that lines between .[ and .] are interpreted as citations, and lines between .R1 and .R2 are interpreted as commands about how citations are to be processed.

## soelim

soelim reads files and replaces lines of the form *.so file* by the contents of *file*.

## tbl

tbl compiles descriptions of tables embedded within troff input files into commands that are understood by troff.

---

## tfmtodit

tfmtodit creates a font file for use with **`groff -Tdvi`**

---

## troff

troff is highly compatible with Unix troff. Usually it should be invoked using the groff command, which will also run preprocessors and postprocessors in the appropriate order and with the appropriate options.

---

# Installing Man

## Installing Man

Install Man by running the following commands:

```
root:man-1.5h1#    ./configure -default
root:man-1.5h1#    make
root:man-1.5h1#    make install
```

---

## Contents

The Man package contains the man, apropos whatis and makewhatis programs.

---

## Description

### man

man formats and displays the on-line manual pages.

---

### apropos

apropos searches a set of database files containing short descriptions of system commands for keywords and displays the result on the standard output.

---

### whatis

whatis searches a set of database files containing short descriptions of system commands for keywords and displays the result on the standard output. Only complete word matches are displayed.

---

### makewhatis

makewhatis reads all the manual pages contained in given sections of manpath or the preformatted pages contained in the given sections of catpath. For each page, it writes a line in the whatis database; each line consists of the name of the page and a short description, separated by a dash. The description is extracted using the content of the NAME section of the manual page.

---

# Installing Perl

## Installing Perl

Install Perl by running the following commands:

```
root:perl-5.6.0#   ./Configure -Dprefix=/usr
root:perl-5.6.0#   make
root:perl-5.6.0#   make test
root:perl-5.6.0#   make install
```

If you don't want to answer all those questions Perl asks you, you can add the –d option to the configure script and Perl will use all the default settings.

Also note that a few tests during the make test phase will fail for various reasons. One being there's not network support yet and a few packages haven't been installed yet. It's ok if not every test succeeds. If there are between 5 and 10 failed tests you're just fine. You might want to reinstall perl after you're done with chapter 7.

---

## Contents

The Perl package contains Perl – Practical Extraction and Report Language

---

## Description

Perl combines the features and capabilities of C, awk, sed and sh into one powerful programming language.

---

# Installing M4

## Installing M4

Install M4 by running the following commands:

```
root:m4-1.4#    ./configure --prefix=/usr
root:m4-1.4#    make
root:m4-1.4#    make install
```

---

## Contents

The M4 package contains the M4 processor

---

## Description

M4 is a macro processor. It copies input to output expanding macros as it goes. Macros are either builtin or user-defined and can take any number of arguments. Besides just doing macro expansion m4 has builtin functions for including named files, running UNIX commands, doing integer arithmetic, manipulating text in various ways, recursion, etc. M4 can be used either as a front-end to a compiler or as a macro processor in its own right.

---

# Installing Texinfo

## Installing Texinfo

Install Texinfo by running the following commands:

```
root:texinfo-4.0#   ./configure --prefix=/usr
root:texinfo-4.0#   make
root:texinfo-4.0#   make install
```

---

## Contents

The Texinfo package contains the info, install–info, makeinfo, texi2dvi and texindex programs

---

## Description

### info

The info program reads Info documents, usually contained in your /usr/doc/info directory. Info documents are like man(ual) pages, but they tend to be more in depth than just explaining the options to a program.

---

### install–info

The install–info program updates the info entries. When you run the info program a list with available topics (ie: available info documents) will be presented. The install–info program is used to maintain this list of available topics. If you decice to remove info files manually, you need to delete the topic in the index file as well. This program is used for that. It also works the other way around when you add info documents.

---

### makeinfo

The makeinfo program translates Texinfo source documents into various formats. Available formats are: info files, plain text and HTML.

---

### texi2dvi

The texi2dvi program prints Texinfo documents

---

## texindex

The texindex program is used to sort Texinfo index files.

# Installing Autoconf

## Installing Autoconf

Install Autoconf by running the following commands:

```
root:autoconf-2.13#    ./configure --prefix=/usr
root:autoconf-2.13#    make
root:autoconf-2.13#    make install
```

---

## Contents

The Autoconf package contains the autoconf, autoheader, autoreconf, autoscan, autoupdate and ifnames programs

---

## Description

### autoconf

Autoconf is a tool for producing shell scripts that automatically configure software source code packages to adapt to many kinds of UNIX-like systems. The configuration scripts produced by Autoconf are independent of Autoconf when they are run, so their users do not need to have Autoconf.

---

### autoheader

The autoheader program can create a template file of C #define statements for configure to use

---

### autoreconf

If you have a lot of Autoconf-generated configure scripts, the autoreconf program can save you some work. It runs autoconf (and autoheader, where appropriate) repeatedly to remake the Autoconf configure scripts and configuration header templates in the directory tree rooted at the current directory.

---

### autoscan

The autoscan program can help you create a configure.in file for a software package. autoscan examines source files in the directory tree rooted at a directory given as a command line argument, or the current

directory if none is given.  It searches the source files for common portability problems and creates a file configure.scan which is a preliminary configure.in for that package.

## autoupdate

The autoupdate program updates a configure.in file that calls Autoconf macros by their old names to use the current macro names.

## ifnames

ifnames can help when writing a configure.in for a software package. It prints the identifiers that the package already uses in C preprocessor conditionals. If a package has already been set up to have some portability, this program can help you figure out what its configure needs to check for. It may help fill in some gaps in a configure.in generated by autoscan.

# Installing Automake

## Installing Automake

Install Automake by running the following commands:

```
root:automake-1.4#    ./configure --prefix=/usr
root:automake-1.4#    make install
```

---

## Contents

The Automake package contains the aclocal and automake programs

---

## Description

### aclocal

Automake includes a number of Autoconf macros which can be used in your package; some of them are actually required by Automake in certain situations. These macros must be defined in your aclocal.m4; otherwise they will not be seen by autoconf.

The aclocal program will automatically generate aclocal.m4 files based on the contents of configure.in. This provides a convenient way to get Automake−provided macros, without having to search around. Also, the aclocal mechanism is extensible for use by other packages.

---

### automake

To create all the Makefile.in's for a package, run the automake program in the top level directory, with no arguments. automake will automatically find each appropriate Makefile.am (by scanning configure.in) and generate the corresponding Makefile.in.

---

# Installing Bash

## Installing Bash

Install Bash by running the following commands:

```
root:bash-2.04#   ./configure --prefix=/usr --with-ncurses
root:bash-2.04#   make
root:bash-2.04#   make install
root:bash-2.04#   logout
root:~#   cd $LFS/usr/bin
root:~#   mv bash bashbug $LFS/bin
root:~#   chroot $LFS bash --login
```

---

## Contents

The Bash package contains the bash program

---

## Description

Bash is the Bourne-Again SHell, which is a widely used command interpreter on Unix systems. Bash is a program that reads from standard input, the keyboard. You type something and the program will evaluate what you have typed and do something with it, like running a program.

---

# Installing Flex

## Installing Flex

Install Flex by running the following commands:

```
root:flex-2.5.4a#   ./configure --prefix=/usr
root:flex-2.5.4a#   make
root:flex-2.5.4a#   make install
```

---

## Contents

The Flex package contains the flex program

---

## Description

Flex is a tool for generating programs which regognize patterns in text. Pattern recognition is very useful in many applications. You set up rules what to look for and flex will make a program that looks for those patterns. The reason people use flex is that it is much easier to set up rules for what to look for than to write the actual program that finds the text.

---

# Installing File

## Installing File

Install File by running the following commands:

```
root:file-3.31#    ./configure --prefix=/usr
--datadir=/usr/share/misc
root:file-3.31#    make
root:file-3.31#    make install
```

---

## Contents

The File package contains the file program.

---

## Description

File tests each specified file in an attempt to classify it. There are three sets of tests, performed in this order: filesystem tests, magic number tests, and language tests. The first test that succeeds causes the file type to be printed.

---

# Installing Gettext

## Installing Gettext

Install Gettext by running the following commands:

```
root:gettext-0.10.35#   ./configure --prefix=/usr
root:gettext-0.10.35#   make
root:gettext-0.10.35#   make install
```

---

## Contents

The gettext package contains the gettext, gettextize, msgcmp, msgcomm, msgfmt, msgmerge, msgunfmt and xgettext programs.

---

## Description

### gettext

The gettext package is used for internationalization (also known as i18n) and for localization (also known as l10n). Programs can be compiled with Native Language Support (NLS) which enable them to output messages in your native language rather than in the default English languge.

---

# Installing Libtool

## Installing Libtool

Install Libtool by running the following commands:

```
root:libtool-1.3.5#   ./configure --prefix=/usr
root:libtool-1.3.5#   make
root:libtool-1.3.5#   make install
```

## Contents

The Libtool package contains the libtool and libtoolize programs. It also contains the ltdl library.

## Description

### libtool

Libtool provides generalized library−building support services.

### libtoolize

libtoolize provides a standard way to add libtool support to your  package.

### ltdl library

Libtool provides a small library, called `libltdl', that aims at hiding  the various difficulties of dlopening libraries from programmers.

# Installing Consoletools

## Installing Console−tools

Before you start installing Console−tools you have to unpack the console−tools−0.2.3.patch file.

Install Console−tools by running the following commands:

```
root:console-tools-0.2.3#   patch -Np1 -i
../console-tools-0.2.3.patch
root:console-tools-0.2.3#   ./configure --prefix=/usr
root:console-tools-0.2.3#   make
root:console-tools-0.2.3#   make install
```

---

## Contents

The Console−tools package contains the charset, chvt, consolechars, deallocvt, dumpkeys, fgconsole, fix_bs_and_del, font2psf, getkeycodes, kbd_mode, loadkeys, loadunimap, mapscrn, mk_modmap, openvt, psfaddtable, psfgettable, psfstriptable, resizecons, saveunimap, screendump, setfont, setkeycodes, setleds, setmetamode, setvesablank, showcfont, showkey, splitfont, unicode_start, unicode_stop, vcstime, vt−is−URF8, writevt

---

## Description

### charset

charset sets an ACM for use in one of the G0/G1 charsets slots.

---

### chvt

chvt changes foreground virtual terminal.

---

### codepage

No description available.

---

## consolechars

consolechars loads EGA/VGA console screen fonts, screen font maps and/or application−charset maps.

## deallocvt

deallocvt deallocates unused virtual terminals.

## dumpkeys

dumpkeys dumps keyboard translation tables.

## fgconsole

fgconsole prints the number of the active virtual terminal.

## fix_bs_and_del

No description available.

## font2psf

No description available.

## getkeycodes

getkeycodes prints the kernel scancode−to−keycode mapping table.

## kbd_mode

kbd_mode reports or sets the keyboard mode.

## loadkeys

loadkeys loads keyboard translation tables.

## loadunimap

No description available.

## mapscrn

No description available.

## mk_modmap

No description available.

## openvt

openvt starts a program on a new virtual terminal.

## psfaddtable

psfaddtable adds a Unicode character table to a console font.

## psfgettable

psfgettable extracts the embedded Unicode character table from a console font.

## psfstriptable

psfstriptable removes the embedded Unicode character table from a console font.

## resizecons

resizecons changes the kernel idea of the console size.

## saveunimap

No description available.

## screendump

No description available.

## setfont

No description available.

## setkeycodes

setkeycodes loads kernel scancode−to−keycode mapping table entries.

## setleds

setleds sets the keyboard leds.

## setmetamode

setmetamode defines the keyboard meta key handling.

## setvesablank

No description available.

## showcfont

showcfont displays all character in the current screenfont.

## showkey

showkey examines the scancodes and keycodes sent by the keyboard.

## splitfont

No description available.

## unicode_start

unicode_start puts the console in Unicode mode.

## unicode_end

No description available.

## vcstime

No description available.

## vt−is−UTF8

vt−is−UTF8 checks whether the current virtual terminal is in UTF8− or byte−mode.

## writevt

No description available.

# Installing Consoledata

## Installing Console–data

Install Console–data by running the following commands:

```
root:console-data-1999.08.29#   ./configure --prefix=/usr
root:console-data-1999.08.29#   make
root:console-data-1999.08.29#   make install
```

---

## Contents

The console–data package contains the data files that are used and needed by the console–tools package.

---

# Installing Binutils

## Installing Binutils

Install Binutils by running the following commands:

```
root:binutils-2.10#    ./configure --prefix=/usr
root:binutils-2.10#    make -e tooldir=/usr
root:binutils-2.10#    make -e tooldir=/usr install
```

---

## Description

The Binutils package contains the ld, as, ar, nm, objcopy, objdump, ranlib, size, strings, strip, c++filt, addr2line and nlmconv programs

---

## Description

### ld

ld combines a number of object and archive files, relocates their data and ties up symbol references. Often the last step in building a new compiled program to run is a call to ld.

---

### as

as is primarily intended to assemble the output of the GNU C compiler gcc for use by the linker ld.

---

### ar

The ar program creates, modifies, and extracts from archives. An archive is a single file holding a collection of other files in a structure that makes it possible to retrieve the original individual files (called members of the archive).

---

### nm

nm lists the symbols from object files.

---

## objcopy

objcopy utility copies the contents of an object file to another. objcopy uses the GNU BFD Library to read and write the object files. It can write the destination object file in a format different from that of the source object file.

---

## objdump

objdump displays information about one or more object files. The options control what particular information to display. This information is mostly useful to programmers who are working on the compilation tools, as opposed to programmers who just want their program to compile and work.

---

## ranlib

ranlib generates an index to the contents of an archive, and stores it in the archive. The index lists each symbol defined by a member of an archive that is a relocatable object file.

---

## size

size lists the section sizes −−and the total size−− for each of the object files objfile in its argument list. By default, one line of output is generated for each object file or each module in an archive.

---

## strings

For each file given, strings prints the printable character sequences that are at least 4 characters long (or the number specified with an option to the program) and are followed by an unprintable character. By default, it only prints the strings from the initialized and loaded sections of object files; for other types of files, it prints the strings from the whole file.

strings is mainly useful for determining the contents of non−text files.

---

## strip

strip discards all or specific symbols from object files. The list of object files may include archives. At least one object file must be given. strip modifies the files named in its argument, rather than writing modified copies under different names.

---

## c++filt

The C++ language provides function overloading, which means that you can write many functions with the same name (providing each takes parameters of different types). All C++ function names are encoded into a low−level assembly label (this process is known as mangling). The c++filt program does the inverse

mapping: it decodes (demangles) low−level names into user−level names so that the linker can keep these overloaded functions from clashing.

## addr2line

addr2line translates program addresses into file names and line numbers. Given an address and an executable, it uses the debugging information in the executable to figure out which file name and line number are associated with a given address.

## nlmconv

nlmconv converts relocatable object files into the NetWare Loadable Module files, optionally reading header files for NLM header information.

# Installing Bzip2

## Installing Bzip2

Install Bzip2 by running the following commands:

```
root:bzip2-1.0.1#   make -f Makefile-libbz2_so
root:bzip2-1.0.1#   make bzip2recover libbz2.a
root:bzip2-1.0.1#   cp bzip2-shared /bin/bzip2
root:bzip2-1.0.1#   cp bzip2recover /bin
root:bzip2-1.0.1#   cp bzip2.1 /usr/share/man/man1
root:bzip2-1.0.1#   cp bzlib.h /usr/include
root:bzip2-1.0.1#   cp -a libbz2.so* libbz2.a /lib
root:bzip2-1.0.1#   rm /usr/lib/libbz2.a
root:bzip2-1.0.1#   cd /bin
root:bin#   rm bunzip2 && ln -s bzip2 bunzip2
root:bin#   rm bzcat && ln -s bzip2 bzcat
```

Although it's not strictly a part of a basic LFS system it's worth mentioning that you can donwload a patch for Tar which enables the tar program to compress and uncompress using bzip2/bunzip2 easily. With a plain tar you'll have to use constructions like bzcat file.tar.bz|tar xv or tar --use-compress-prog=bunzip2 -xvf file.tar.bz2 to use bzip2 and bunzip2 with tar. This patch gives you the -y option so you can unpack a Bzip2 archive with tar xvfy file.tar.bz2. Applying this patch will be mentioned later on when you re-install the Tar package.

---

## Contents

The Bzip2 packages contains the bzip2, bunzip2, bzcat and bzip2recover programs.

---

## Description

### Bzip2

bzip2 compresses files using the Burrows-Wheeler block sorting text compression algorithm, and Huffman coding. Compression is generally considerably better than that achieved by more conventional LZ77/LZ78-based compressors, and approaches the performance of the PPM family of statistical compressors.

---

## Bunzip2

Bunzip2 decompresses files that are compressed with bzip2.

---

## bzcat

bzcat (or bzip2 −dc) decompresses all specified files to the standard output.

---

## bzip2recover

bzip2recover recovers data from damaged bzip2 files.

---

# Installing Diffutils

## Installing Diffutils

Install Diffutils by running the following commands:

```
root:diffutils-2.7#   ./configure --prefix=/usr
root:diffutils-2.7#   make
root:diffutils-2.7#   make install
```

---

## Contents

The Diffutils packagec contains the cmp, diff, diff3 and sdiff programs.

---

## Description

### cmp and diff

cmp and diff both compare two files and report their differences. Both programs have extra options which compare files in different situations.

---

### diff3

The difference between diff and diff3 is that diff comprares 2 files, diff3 compares 3 files.

---

### sdiff

sdiff merges two two files and interactively outputs the results.

---

# Installing E2fsprogs

## Installing E2fsprogs

Install E2fsprogs by running the following commands:

```
root:e2fsprogs-1.18#    ./configure --prefix=/usr
--with-root-prefix=/ \
> --enable-elf-shlibs
root:e2fsprogs-1.18#    make
root:e2fsprogs-1.18#    make install
```

---

## Contents

The e2fsprogs package contains the chattr, lsattr, uuidgen, badblocks, debugfs, dumpe2fs, e2fsck, e2label, fsck, fsck.ext2, mke2fs, mkfs.ext2, mklost+found and tune2fs programs.

---

## Description

### chattr

chattr changes the file attributes on a Linux second extended file system.

---

### lsattr

lsattr lists the file attributes on a second extended file system.

---

### uuidgen

The uuidgen program creates a new universally unique identifier (UUID) using the libuuid library. The new UUID can reasonably be considered unique among all UUIDs created on the local system, and among UUIDs created on other systems in the past and in the future.

---

### badblocks

badblocks is used to search for bad blocks on a device (usually a disk partition).

---

## debugfs

The debugfs program is a file system debugger. It can be used to examine and change the state of an ext2 file system.

---

## dumpe2fs

dumpe2fs prints the super block and blocks group information for the filesystem present on a specified device.

---

## e2fsck and fsck.ext2

e2fsck is used to check a Linux second extended file system. fsck.ext2 does the same as e2fsck.

---

## e2label

e2label will display or change the filesystem label on the ext2 filesystem located on the specified device.

---

## fsck

fsck is used to check and optionally repair a Linux file system.

---

## mke2fs and mkfs.ext2

mke2fs is used to create a Linux second extended file system on a device (usually a disk partition). mkfs.ext2 does the same as mke2fs.

---

## mklost+found

mklost+found is used to create a lost+found directory in the current working directory on a Linux second extended file system. mklost+found pre−allocates disk blocks to the directory to make it usable by e2fsck.

---

## tune2fs

tune2fs adjusts tunable filesystem parameters on a Linux second extended filesystem.

---

# Installing Fileutils

## Installing Fileutils

Install Fileutils by running the following commands:

```
root:fileutils-4.0#    ./configure --prefix=/usr
root:fileutils-4.0#    make
root:fileutils-4.0#    make install
root:fileutils-4.0#    cd /usr/bin
root:bin#    mv chgrp chmod chown cp dd df dir /bin
root:bin#    mv dircolors du install ln ls mkdir mkfifo /bin
root:bin#    mv mknod rm rmdir sync touch vdir /bin
root:bin#    cp mv /bin && rm mv
```

---

## Contents

The Fileutils package contains the chgrp, chmod, chown, cp, dd, df, dir, dircolors, du, install, ln, ls, mkdir, mkfifo, mknod, mv, rm, rmdir, sync, touch and vdir programs.

---

## Description

### chgrp

chgrp changes the group ownership of each given file to the named group, which can be either a group name or a numeric group ID.

---

### chmod

chmod changes the permissions of each given file according to mode, which can be either a symbolic representation of changes to make, or an octal number representing the bit pattern for the new permissions.

---

### chown

chown changes the user and/or group ownership of each given file.

---

## cp

cp copies files from one place to another.

---

## dd

dd copies a file (from the standard input to the standard output, by default) with a user−selectable blocksize, while optionally performing conversions on it.

---

## df

df displays the amount of disk space available on the filesystem containing each file name argument. If no file name is given, the space available on all currently mounted filesystems is shown.

---

## ls, dir and vdir

dir and vdir are versions of ls with different default output formats. These programs list each given file or directory name. Directory contents are sorted alphabetically. For ls, files are by default listed in columns, sorted vertically, if the standard output is a terminal; otherwise they are listed one per line. For dir, files are by default listed in columns, sorted vertically. For vdir, files are by default listed in long format.

---

## dircolors

dircolors outputs commands to set the LS_COLOR environment variable. The LS_COLOR variable is use to change the default color scheme used by ls and related utilities.

---

## du

du displays the amount of disk space used by each argument and for each subdirectory of directory arguments.

---

## install

install copies files and sets their permission modes and, if possible, their owner and group.

---

## ln

ln makes hard or soft (symbolic) links between files.

---

## mkdir

mkdir creates directories with a given name.

## mkfifo

mkfifo creates a FIFO with each given name.

## mknod

mknod creates a FIFO, character special file, or block special file with the given file name.

## mv

mv moves files from one directory to another or renames files, depending on the arguments given to mv.

## rm

rm removes files or directories.

## rmdir

rmdir removes directories, if they are empty.

## sync

sync forces changed blocks to disk and updates the super block.

## touch

touch changes the access and modification times of each given file to the current time. Files that do not exist are created empty.

# Installing Grep

## Installing Grep

Install Grep by running the following commands:

```
root:grep-2.4.2#    ./configure --prefix=/usr
root:grep-2.4.2#    make
root:grep-2.4.2#    make install
```

---

## Contents

The grep package contains the egrep, fgrep and grep programs.

---

## Description

### egrep

egrep prints lines from files matching an extended regular expression pattern.

---

### fgrep

fgrep prints lines from files matching a list of fixed strings, separated by newlines, any of which is to be matched.

---

### grep

grep prints lines from files matching a basic regular expression pattern.

---

# Installing Gzip

## Installing Gzip

Install Gzip by running the following commands:

```
root:gzip-1.2.4a#   ./configure --prefix=/usr
root:gzip-1.2.4a#   make
root:gzip-1.2.4a#   make install
root:gzip-1.2.4a#   cd /usr/bin
root:bin#    cp gunzip gzip /bin
root:bin#   rm gunzip gzip
```

---

## Contents

The Gzip package contains the gunzip, gzexe, gzip, zcat, zcmp, zdiff, zforece, zgrep, zmore and znew programs.

---

## Description

### gunzip

gunzip decompresses files that are compressed with gzip.

---

### gzexe

gzexe allows you to compress executables in place and have them automatically uncompress and execute when you run them (at a penalty in performance).

---

### gzip

gzip reduces the size of the named files using Lempel–Ziv coding (LZ77).

---

### zcat

zcat uncompresses either a list of files on the command line or its standard input and writes the uncompressed data on standard output

## zcmp

zcmp invokes the cmp program on compressed files.

## zdiff

zdiff invokes the diff program on compressed files.

## zforce

zforce forces a .gz extension on all gzip files so that gzip will not compress them twice. This can be useful for files with names truncated after a file transfer.

## zgrep

zgrep invokes the grep program on compressed files.

## zmore

Zmore is a filter which allows examination of compressed or plain text files one screenful at a time on a soft−copy terminal (similar to the more program).

## znew

Znew recompresses files from .Z (compress) format to .gz (gzip) format.

# Installing Ldso

## Installing Ld.so

Install Ld.so by running the following commands:

```
root:ld.so-1.9.9#   cd util
root:util#   make ldd ldconfig
root:util#   cp ldd /bin
root:util#   cp ldconfig /sbin
root:util#   cd ../man
root:man#   cp ldd.1 /usr/share/man/man1
root:man#   cp *.8 /usr/share/man/man8
root:man#   rm /usr/bin/ldd
root:man#   hash -r
```

The "hash –r" command is to make bash forget about the locations of previously executed commands. If you have executed ldd before, bash expects it to be found in /usr/bin. Since we moved it to /bin, the cache needs to be purged so bash can find it in /bin when you want to execute it again.

You might have noticed that we don't use the compiler optimizations for this package. The reason is that overriding the CFLAGS variable causes compilation problems. You would have to edit the Config.mk file and add the proper values to the CFLAGS variable and then compile the package. If you want to do that it's up to you. I don't think it's worth the trouble though. The ld and ldd programs usually are only rarely used.

---

## Contents

From the Ld.so package we're using the ldconfig and ldd programs.

---

## Description

### ldconfig

ldconfig creates the necessary links and cache (for use by the run–time linker, ld.so) to the most recent shared libraries found in the directories specified on the command line, in the file /etc/ld.so.conf, and in the trusted directories (/usr/lib and /lib). ldconfig checks the header and file names of the libraries it encounters when determining which versions should have their links updated.

---

## ldd

ldd prints the shared libraries required by each program or shared library  specified on the command line.

# Installing Bin86

## Installing Bin86

Install Linux86 by running the following commands:

```
root:bin86#     make
root:bin86#    make PREFIX=/usr install
```

---

## Contents

The Bin86 contains the as86, as86_encap, ld86, objdump86, nm86 and size86 programs.

---

## Description

### as86

as86 is an assembler for the 8086...80386 processors.

---

### as86_encap

as86_encap is a shell script to call as86 and convert the created binary into a C file prog.v to be included in or linked with programs like boot block installers.

---

### ld86

ld86 understands only the object files produced by the as86 assembler, it can link them into either an impure or a separate I&D executable.

---

### objdump86

No description available.

---

## nm86

No description available.

## size86

No description available.

# Installing Lilo

## Installing Lilo

Install Lilo by running the following commands:

```
root:lilo-21.5#   make
root:lilo-21.5#   make install
```

## Contents

The Lilo package contains the lilo program.

## Description

lilo installs the Linux boot loader which is used to start a Linux system.

# Installing Make

## Installing Make

Install Make by running the following commands:

```
root:make-3.79.1#    ./configure --prefix=/usr
root:make-3.79.1#    make
root:make-3.79.1#    make install
```

---

## Contents

The Make package contains the make program.

---

## Description

make determine automatically which pieces of a large program need to be recompiled, and issue the commands to recompile them.

---

# Installing Shellutils

## Installing Shell Utils

Install Shellutils by running the following commands:

```
root:sh-utils-2.0#   ./configure --prefix=/usr
root:sh-utils-2.0#   make
root:sh-utils-2.0#   make install
root:sh-utils-2.0#   cd /usr/bin
root:bin#   mv date echo false pwd stty /bin
root:bin#   mv su true uname hostname /bin
```

---

## Contents

The Shellutils package contains the basename, chroot, date, dirname, echo, env, expr, factor, false, groups, hostid, hostname, id, logname, nice, nohup, pathchk, pinky, printenv, printf, pwd, seq, sleep, stty, su, tee, test, true, tty, uname, uptime, users, who, whoami and yes programs.

---

## Description

### basename

basename strips directory and suffixes from filenames.

---

### chroot

chroot runs a command or interactive shell with special root directory.

---

### date

date displays the current time in a specified format, or sets the system date.

---

### dirname

dirname strips non−directory suffixes from file name.

---

## echo

echo displays a line of text.

## env

env runs a program in a modified environment.

## expr

expr evaluates expressions.

## factor

factor prints the prime factors of all specified integer numbers.

## false

false always exits with a status code indicating failure.

## groups

groups prints the groups a user is in.

## hostid

hostid prints the numeric identifier (in hexadecimal) for the current host.

## hostname

hostname sets or prints the name of the current host system

## id

id prints the real and effective UIDs and GIDs of a user or the current user.

## logname

logname prints the current user's login name.

## nice

nice runs a program with modified scheduling priority.

## nohup

nohup runs a command immune to hangups, with output to a non−tty

## pathchk

pathchk checks whether file names are valid or portable.

## pinky

pinky is a lightweight finger utility which retrieves information about a certain user

## printenv

printenv prints all or part of the environment.

## printf

printf formats and print data (the same as the printf C function).

## pwd

pwd prints the name of the current/working directory

## seq

seq prints numbers in a certain range with a certain increment.

## sleep

sleep delays for a specified amount of time.

## stty

stty changes and prints terminal line settings.

## su

su runs a shell with substitute user and group IDs

## tee

tee reads from standard input and write to standard output and files.

## test

test checks file types and compares values.

## true

True always exitx with a status code indicating success.

## tty

tty prints the file name of the terminal connected to standard input.

## uname

uname prints system information.

## uptime

uptime tells how long the system has been running.

## users

users prints the user names of users currently logged in to the  current host.

---

## who

who shows who is logged on.

---

## whoami

whoami prints your effective userid.

---

## yes

yes outputs a string repeatedly until killed.

---

# Installing Shadowpwd

## Installing Shadow Password Suite

Install the Shadow Password Suite by running the following commands:

```
root:shadow-19990827#   ./configure --prefix=/usr
root:shadow-19990827#   make
root:shadow-19990827#   make install
root:shadow-19990827#   cd etc
root:etc#   cp limits login.access login.defs.linux shells
suauth /etc
root:etc#   mv /etc/login.defs.linux /etc/login.defs
```

---

## Contents

The Shadow Password Suite contains the chage, chfn, chsh, expiry, faillog, gpasswd, lastlog, login, newgrp, passwd, sg, su, chpasswd, dpasswd, groupadd, groupdel, groupmod, grpck, grpconv, grpunconv, logoutd, mkpasswd, newusers, pwck, pwconv, pwunconv, useradd, userdel, usermod and vipw programs.

---

## Description

### chage

chage changes the number of days between password changes and the date of the last password change.

---

### chfn

chfn changes user fullname, office number, office extension, and home phone number information for a user's account.

---

### chsh

chsh changes the user login shell.

---

## expiry

It's currently unknown what this program is for.

---

## faillog

faillog formats the contents of the failure log,/var/log/faillog, and maintains failure counts and limits.

---

## gpasswd

gpasswd is used to administer the /etc/group file

---

## lastlog

lastlog formats and prints the contents of the last login log, /var/log/lastlog. The login−name, port, and last login time will be printed.

---

## login

login is used to establish a new session with the system.

---

## newgrp

newgrp is used to change the current group ID during a login session.

---

## passwd

passwd changes passwords for user and group accounts.

---

## sg

sg executes command as a different group ID.

---

## su

Change the effective user id and group id to that of a user. This replaces the su programs that's installed from the Shellutils package.

---

## chpasswd

chpasswd reads a file of user name and password pairs from standard input and uses this information to update a group of existing users.

---

## dpasswd

dpasswd adds, deletes, and updates dialup passwords for user login shells.

---

## groupadd

The groupadd command creates a new group account using the values specified on the command line and the default values from the system.

---

## groupdel

The groupdel command modifies the system account files, deleting all entries that refer to group.

---

## groupmod

The groupmod command modifies the system account files to reflect the changes that are specified on the command line.

---

## grpck

grpck verifies the integrity of the system authentication information.

---

## grpconv

grpunconv converts to shadow group files from normal group files.

---

## grpunconv

grpunconv converts from shadow group files to normal group files.

---

## logoutd

logoutd enforces the login time and port restrictions specified in /etc/porttime.

---

## mkpasswd

mkpasswd reads a file in the format given by the flags and converts it to the corresponding database file format.

---

## newusers

newusers reads a file of user name and cleartext password pairs and uses this information to update a group of existing users or to create new users.

---

## pwck

pwck verifies the integrity of the system authentication information.

---

## pwconv

pwconv converts to shadow passwd files from normal passwd files.

---

## pwunconv

pwunconv converts from shadow passwd files to normal files.

---

## useradd

useradd creates a new user or update default new user information.

---

## userdel

userdel modifies the system account files, deleting all entries that refer to a specified login name.

---

## usermod

usermod modifies the system account files to reflect the changes that are specified on the command line.

---

## vipw and vigr

vipw and vigr will edit the files /etc/passwd and /etc/group, respectively. With the –s flag, they will edit the shadow versions of those files, /etc/shadow and /etc/gshadow, respectively.

---

# Installing Modutils

## Installing Modutils

Install Modutils by running the following commands:

```
root:modutils-2.3.12#    ./configure
root:modutils-2.3.12#    make
root:modutils-2.3.12#    make install
```

---

## Contents

The Modutils package contains the depmod, genksyms, insmod, insmod_ksymoops_clean, kerneld, kernelversion, ksyms, lsmod, modinfo, modprobe and rmmod programs.

---

## Description

### depmod

depmod handles dependency descriptions for loadable kernel modules.

---

### genksyms

genksyms reads (on standard input) the output from gcc –E source.c and generates a file containing version information.

---

### insmod

insmod installs a loadable module in the running kernel.

---

### insmod_ksymoops_clean

insmod_ksymoops_clean deletes saved ksyms and modules not accessed in 2 days.

---

## kerneld

kerneld performs kernel action in user space (such as on−demand loading of modules)

## kernelversion

kernelversion reports the major version of the running kernel.

## ksyms

ksyms displays exported kernel symbols.

## lsmod

lsmod shows information about all loaded modules.

## modinfo

modinfo examines an object file associated with a kernel module and displays any information that it can glean.

## modprobe

Modprobe uses a Makefile−like dependency file, created by depmod, to automatically load the relevant module(s) from the set of modules available in predefined directory trees.

## rmmod

rmmod unloads loadable modules from the running kernel.

# Installing Procinfo

## Installing Procinfo

Install Procinfo by running the following commands:

```
root:procinfo-17#   sed s/"-ltermcap"/"-lncurses"/ Makefile
>Makefile2
root:procinfo-17#   mv Makefile2 Makefile
root:procinfo-17#   make
root:procinfo-17#   make install
```

---

## Contents

The Procinfo package contains the procinfo program.

---

## Description

procinfo gathers some system data from the /proc directory and prints it nicely formatted on the standard output device.

---

# Installing Procps

## Installing Procps

Edit the `Makefile` file and edit the CFLAGS variable if you want to add compiler optimizations to this package.

Install Procps by running the following commands:

```
root:procps-2.0.7#   sed s/XConsole/#XConsole/ Makefile
>Makefile2
root:procps-2.0.7#   mv Makefile2 Makefile
root:procps-2.0.7#   gcc -c watch.c
root:procps-2.0.7#   make
root:procps-2.0.7#   make install
root:procps-2.0.7#   mv /usr/bin/kill /bin
```

---

## Contents

The Procps package contains the free, kill, oldps, ps, skill, snice, sysctl, tload, top, uptime, vmstat, w and watch programs.

---

## Description

### free

free displays the total amount of free and used physical and swap memory in the system, as well as the shared memory and buffers used by the kernel.

---

### kill

kills sends signals to processes.

---

### oldps and ps

ps gives a snapshot of the current processes.

---

## skill

skill sends signals to process matching a criteria.

---

## snice

snice changes the scheduling priority for process matching a criteria.

---

## sysctl

sysctl modifies kernel parameters at runtime.

---

## tload

tload prints a graph of the current system load average to the specified tty (or the tty of the tload process if none is specified).

---

## top

top provides an ongoing look at processor activity in real time.

---

## uptime

uptime gives a one line display of the following information: the current time, how long the system has been running, how many users are currently logged on, and the system load averages for the past 1, 5, and 15 minutes.

---

## vmstat

vmstat reports information about processes, memory, paging, block IO, traps, and cpu activity.

---

## w

w displays information about the users currently on the machine, and their processes.

---

## watch

watch runs command repeatedly, displaying its output (the first screenfull).

---

# Installing Psmisc

## Installing Psmisc

Edit the `Makefile` file and edit the CFLAGS variable if you want to add compiler optimizations to this package.

Install Psmisc by running the following commands:

```
root:psmisc#   sed s/-ltermcap/-lncurses/ Makefile >Makefile2
root:psmisc#   mv Makefile2 Makefile
root:psmisc#   make
root:psmisc#   make install
```

---

## Contents

The Psmisc package contains the fuser, killall and pstree programs.

---

## Description

### fuser

fuser displays the PIDs of processes using the specified files or file systems.

---

### killall

killall sends a signal to all processes running any of the specified commands.

---

### pstree

pstree shows running processes as a tree.

---

# Installing Sed

## Installing Sed

Install Sed by running the following commands:

```
root:sed-3.02#   ./configure --prefix=/usr
root:sed-3.02#   make
root:sed-3.02#   make install
root:sed-3.02#   mv /usr/bin/sed /bin
```

---

## Contents

The Sed package contains the sed program.

---

## Description

sed is a stream editor. A stream editor is used to perform basic text transformations on an input stream (a file or input from a pipeline).

---

# Installing Vim

## Installing Vim

You need to unpack both the vim−rt and vim−src packages to install Vim. Install Vim by running the following commands:

```
root:vim-5.6#   ./configure --prefix=/usr
root:vim-5.6#   make
root:vim-5.6#   make install
root:vim-5.6#   cd /usr/bin
root:bin#   ln -s vim vi
```

If you are planning on installing the X Window system on your LFS system, you might want to re−compile Vim after you have installed X. Vim comes with a nice GUI version of the editor which requires X and a few other libraries to be installed. For more information read the Vim documentation.

---

## Contents

The Vim package contains the ctags, etags, ex, gview, gvim, rgview, rgvim, rview, rvim, view, vim, vimtutor and xxd programs.

---

## Description

### ctags

ctags generate tag files for source code.

---

### etags

etags does the same as ctags but it can generate cross reference files which list information about the various source objects found in a set of lanugage files.

---

### ex

ex starts vim in Ex mode.

---

## gview

gview is the GUI version of view.

## gvim

gvim is the GUI version of vim.

## rgview

rgview is teh GUI version of rview.

## rgvim

rgvim is the GUI version of rvim.

## rview

rview is a restricted version of view. No shell commands can be started and Vim can't be suspended.

## rvim

rvim is the restricted version of vim. No shell commands can be started and Vim can't be suspended.

## view

view starts vim in read−only mode.

## vim

vim starts vim in the normal, default way.

## vimtutor

vimtutor starts the Vim tutor.

## xxd

xxd makes a hexdump or does the reverse.

# Installing Sysklogd

## Installing Sysklogd

Edit the `Makefile` file and find this line: *CFLAGS= $(RPM_OPT_FLAGS) −O3 −DSYSV −fomit−frame−pointer −Wall −fno−strength−reduce*. Add the proper −mcpu= and −march= option to this variable and save the file.

Install Sysklogd by running the following commands:

```
root:sysklogd-1.3-31#   make
root:sysklogd-1.3-31#   make install
```

## Contents

The Sysklogd package contains the klogd and syslogd programs.

## Description

### klogd

klogd is a system daemon which intercepts and logs Linux kernel messages.

### syslogd

Syslogd provides a kind of logging that many modern programs use.Every logged message contains at least a time and a hostname field, normally a program name field, too, but that depends on how trusty the logging program is.

# Installing Sysvinit

## Installing Sysvinit

Edit the `src/Makefile` file and edit the CFLAGS variable if you want to add compiler optimizations to this package.

Install Sysvinit by running the following commands:

```
root:sysvinit-2.78#   cd src
root:sysvinit-2.78#   make
root:sysvinit-2.78#   make install
```

---

## Contents

The Sysvinit package contains the pidof, last, lastb, mesg, utmpdump, wall, halt, init, killall5, poweroff, reboot, runlevel, shutdown, sulogin and telinit programs.

---

## Description

### pidof

Pidof finds the process id's (pids) of the named programs and prints those id's on standard output.

---

### last

last searches back through the file /var/log/wtmp (or the file designated by the –f flag) and displays a list of all users logged in (and out) since that file was created.

---

### lastb

lastb is the same as last, except that by default it shows a log of the file /var/log/btmp, which contains all the bad login attempts.

---

### mesg

Mesg controls the access to your terminal by others. It's typically used to allow or disallow other users to

write to your terminal.

## utmpdump

utmpdumps prints the content of a file (usually /var/run/utmp) on standard output in a user friendly format.

## wall

Wall sends a message to everybody logged in with their mesg permission set to yes.

## halt

Halt notes that the system is being brought down in the file /var/log/wtmp, and then either tells the kernel to halt, reboot or poweroff the system. If halt or reboot is called when the system is not in runlevel 0 or 6, shutdown will be invoked instead (with the flag –h or –r).

## init

Init is the parent of all processes. Its primary role is to create processes from a script stored in the file /etc/inittab. This file usually has entries which cause init to spawn gettys on each line that users can log in. It also controls autonomous processes required by any particular system.

## killall5

killall5 is the SystemV killall command. It sends a signal to all processes except the processes in its own session, so it won't kill the shell that is running the script it was called from.

## poweroff

poweroff is equivalent to shutdown –h –p now. It halts the computer and switches off the computer (when using an APM compliant BIOS and APM is enabled in the kernel).

## reboot

reboot is equivalent to shutdown –r now. It reboots the computer.

## runlevel

Runlevel reads the system utmp file (typically /var/run/utmp) to locate the runlevel record, and then prints

the previous and current system runlevel on its standard output, separated by a single space.

## shutdown

shutdown brings the system down in a secure way. All logged−in users are notified that the system is going down, and login is blocked.

## sulogin

sulogin is invoked by init when the system goes into single user mode (this is done through an entry in /etc/inittab). Init also tries to execute sulogin when it is passed the −b flag from the bootmonitor (eg, LILO).

## telinit

telinit sends appropriate signals to init, telling it which runlevel to change to.

# Installing Tar

## Installing Tar

Install Tar by running the following commands:

```
root:tar-1.13#   ./configure --prefix=/usr
root:tar-1.13#   make
root:tar-1.13#   make install
root:tar-1.13#   mv /usr/bin/tar /bin
```

If you want to apply the Bzip2 tar patch which gives you the -y option to tar so you can use bzip2 files with tar, first download the patch from http://sourceware.cygnus.com/bzip2/ and apply it by running the following command within the src directory under the tar-1.13 directory:

```
root:src#   patch -i ../../gnutarpatch.txt
```

---

## Contents

The tar package contains the tar and rmt programs.

---

## Description

### tar

tar is an archiving program designed to store and extract files from an archive file known as a tarfile.

---

### rmt

rmt is a program used by the remote dump and restore programs in manipulating a magnetic tape drive through an interprocess communication connection.

---

# Installing Textutils

## Installing Textutils

Install Textutuils by running the following commands:

```
root:textutils-2.0#   ./configure --prefix=/usr
root:textutils-2.0#   make
root:textutils-2.0#   make install
root:textutils-2.0#   mv /usr/bin/cat /bin
```

---

## Contents

The Textutils package contains the cat, cksum, comm, split, cut, expand, fmt, fold, head, join, md5sum, nl, od, paste, pr, ptx, sort, split, sum, tac, tail, tr, tsort, unexpand, uniq and wc programs.

---

## Description

### cat

cat concatenates file(s) or standard input to standard output.

---

### cksum

cksum prints CRC checksum and byte counts of each specified file.

---

### comm

comm compares two sorted files line by line.

---

### csplit

cplit outputs pieces of a file separated by (a) pattern(s) to files xx01, xx02, ..., and outputs byte counts of each piece to standard output.

---

## cut

cut prints selected parts of lines from specified files to standard output.

## expand

expand converts tabs in files to spaces, writing to standard output.

## fmt

fmt reformats each paragraph in the specified file(s), writing to standard output.

## fold

fold wraps input lines in each specified file (standard input by default), writing to standard output.

## head

Print first xx (10 by default) lines of each specified file to standard output.

## join

join joins lines of two files on a common field.

## md5sum

md5sum prints or checks MD5 checksums.

## nl

nl writes each specified file to standard output, with line numbers added.

## od

od writes an unambiguous representation, octal bytes by default, of a specified file to standard output.

## paste

paste writes lines consisting of the sequentially corresponding lines from each specified file, separated by TABs, to standard output.

## pr

pr paginates or columnates files for printing.

## ptx

ptx produces a permuted index of file contents.

## sort

sort writes sorted concatenation of files to standard output.

## split

split outputs fixed−size pieces of an input file to PREFIXaa, PREFIXab, ...

## sum

sum prints checksum and block counts for each specified file.

## tac

tac writes each specified file to standard output, last line first.

## tail

tail print the last xx (10 by default) lines of each specified file to standard output.

## tr

tr translates, squeezes, and/or deletes characters from standard input, writing to standard output.

## tsort

tsort writes totally ordered lists consistent with the partial ordering in specified files.

## unexpand

unexpand converts spaces in each file to tabs, writing to standard output.

## uniq

uniq discards all but one of successive identical lines from files or standard input and writes to files or standard output.

## wc

wc prints line, word, and byte counts for each specified file, and a total line if more than one file is specified.

# Installing Utillinux

## Installing Util−Linux

Before we can install the package we have to edit the MCONFIG file, find and modify the following variables as follows:

*HAVE_SLN=yes*
*HAVE_TSORT=yes*

Now find the following lines in the MCONFIG file:

```
ifeq "$(CPU)" "intel"
  OPT=        −pipe −O2 −m486 −fomit−frame−pointer
else
  ifeq "$(CPU)" "arm"
    OPT=      −pipe −O2 −fsigned−char −fomit−frame−pointer
  else
    OPT=      −O2 −fomit−frame−pointer
  endif
endif
```

Modify the proper OPT variable to include the −mcpu= and −march= options. If you modify the first OPT variable, replace *−m486* with the *−mcpu* variable.

Install Util−Linux by running the following commands:

```
root:util−linux−2.10m#    ./configure
root:util−linux−2.10m#    make
root:util−linux−2.10m#    make install
```

---

# Contents

The Util−linux package contains the arch, dmesg, kill, more, mount, umount, agetty, blockdev, cfdisk, ctrlaltdel, elvtune, fdisk, fsck.minix, hwclock, kbdrate, losetup, mkfs, mkfs.bfs, mkfs.minix, mkswap, sfdisk, swapoff, swapon, cal, chkdupexe, col, colcrt, colrm, column, cytune, ddate, fdformat, getopt, hexdump, ipcrm, ipcs, logger, look, mcookie, namei, rename, renice, rev, script, setfdprm, setsid, setterm, ul, whereis,

write, ramsize, rdev, readprofile, rootflags, swapdev, tunelp and vidmode programs.

# Description

## arch

arch prints the machine architecture.

## dmesg

dmesg is used to examine or control the kernel ring buffer (boot messages from the kernel).

## kill

kill sends a specified signal to the specified process.

## more

more is a filter for paging through text one screenful at a time.

## mount

mount mounts a filesystem from a device to a directory (mount point).

## umount

umount unmounts a mounted filesystem.

## agetty

agetty opens a tty port, prompts for a login name and invokes the /bin/login command.

## blockdev

No description available.

## cfdisk

cfdisk is an libncurses based disk partition table manipulator.

## ctrlaltdel

ctrlaltdel sets the function of the CTRL+ALT+DEL key combination (hard or soft reset).

## elvtune

elvtune allows to tune the I/O elevator per blockdevice queue basis.

## fdisk

fdisk is a disk partition table manipulator.

## fsck.minix

fsck.minix performs a consistency check for the Linux MINIX filesystem.

## hwclock

hwclock queries and sets the hardware clock (Also called the RTC or BIOS clock).

## kbdrate

kbdrate resets the keyboard repeat rate and delay time.

## losetup

losetup sets up and controls loop devices.

## mkfs

mkfs builds a Linux filesystem on a device, usually a harddisk partition.

## mkfs.bfs

mkfs.bfs creates a SCO bfs file system on a device, usually a harddisk partition.

## mkfs.minix

mkfs.minix creates a Linux MINIX filesystem on a device, usually a harddisk partition.

## mkswap

mkswap sets up a Linux swap area on a device or in a file.

## sfdisk

sfdisk is a disk partition table manipulator.

## swapoff

swapoff disables devices and files for paging an swapping.

## swapon

swapon enables devices and files for paging and swapping.

## cal

cal displays a simple calender.

## chkdupexe

chkdupexe finds duplicate executables.

## col

col filters reverse line feeds from input.

## colcrt

colcrt filters nroff output for CRT previewing.

## colrm

colrm removes columns from a file.

## column

column columnates lists.

## cytune

cytune queries and modifies the interruption threshold for the Cyclades driver.

## ddate

ddate converts Gregorian dates to Discordian dates.

## fdformat

fdformat low−level formats a floppy disk.

## getopt

getops parses command options the same way as the getopt C command.

## hexdump

hexdump displays specified files, or standard input, in a user specified format (ascii, decimal, hexadecimal, octal).

## ipcrm

ipcrm removes a specified resource.

## ipcs

ipcs provides information on ipc facilities.

## logger

logger makes entries in the system log.

## look

look displays lines beginning with a given string.

## mcookie

mcookie generates magic cookies for xauth.

## namei

namei follows a pathname until a terminal point is found.

## rename

rename renames files.

## renice

renice alters priority of running processes.

## rev

rev reverses lines of a file.

## script

script makes typescript of terminal session.

## setfdprm

setfdprm sets user−provides floppy disk parameters.

## setsid

setsid runs programs in a new session.

## setterm

setterm sets terminal attributes.

## ul

ul reads a file and translates occurences of underscores to the sequence which indicates underlining for the terminal in use.

## whereis

whereis locates a binary, source and manual page for a command.

## write

write sends a message to another user.

## ramsize

ramsize queries and sets RAM disk size.

## rdev

rdev queries and sets image root device, swap device, RAM disk size, or video mode.

## readprofile

readprofile reads kernel profiling information.

## rootflags

rootflags queries and sets extra information used when mounting root.

---

## swapdev

swapdev queries and sets swap device.

---

## tunelp

tunelp sets various paramters for the lp device.

---

## vidmode

vidmode queries and sets the video mode.

---

# Installing Man–pages

## Installing Man–pages

Install Man–pages by running the following commands:

```
root:man-pages-1.30#   cp -av man2 man3 man4 \
> man5 man6 man7 /usr/share/man
root:man-pages-1.30#   cd man8
root:man8#   cp tzselect.8 zdump.8 \
> zic.8 /usr/share/man/man8
```

## Contents

The Man–pages package contains various manual pages that don't come with the packages.

## Description

Examples of provided manual pages are the manual pages describing all the C and C++ functions, few important /dev/ files and more.

# Removing old NSS library files

If you have copied the NSS Library files from your normal Linux system to the LFS system (because your normal system runs glibc−2.0) it's time to remove them now by running:

```
root:~#     rm /lib/libnss*.so.1 /lib/libnss*2.0*
```

---

# Configuring essential software

Now that all software is installed, all that we need to do to get a few programs running properly is to create their configuration files.

---

## Configuring Glibc

We need to create the /etc/nsswitch.conf file. Although glibc should provide defaults when this file is missing or corrupt, it's defaults don't work work well with networking which will be dealt with in a later chapter. Also, our timezone needs to be setup.

Create a new file `/etc/nsswitch.conf` containing the following:

```
# Begin /etc/nsswitch.conf

passwd: files
group: files
shadow: files

hosts: files dns
networks: files

protocols: db files
services: db files
ethers: db files
rpc: db files

netgroup: db files

# End /etc/nsswitch.conf
```

Run the **`tzselect`** script and answer the questions regarding your timezone. When you're done, the script will give you the location of the timezone file you need.

Create the `/etc/localtime` symlink by running:

```
root:~#   cd /etc
root:etc#   rm localtime
root:etc#   ln -s ../usr/share/zoneinfo/<tzselect's output> \
> localtime
```

tzselect's output can be something like *EST5EDT* or *Canada/Eastern*. The symlink you would create with that information would be *ln −s ../usr/share/zoneinfo/EST5EDT localtime* or *ln −s ../usr/share/zoneinfo/Canada/Eastern localtime*

---

# Configuring Dynamic Loader

By default the dynamic loader searches a few default paths for dynamic libraries, so there normally isn't a need for the `/etc/ld.so.conf` file unless you have extra directories in which you want the system to search for paths. The `/usr/local/lib` directory isn't searched through for dynamic libraries by default, so we want to add this path so when you install software you won't be suprised by them not running for some reason.

Create a new file `/etc/ld.so.conf` containing the following:

```
# Begin /etc/ld.so.conf

/lib
/usr/lib
/usr/local/lib

# End /etc/ld.so.conf
```

Although it's not necessary to add the `/lib` and `/usr/lib` directories it doesn't hurt. This way you see right away what's being searched and don't have to remeber the default search paths if you don't want to.

---

# Configuring Lilo

We're not going to create lilo's configuration file from scratch, but we'll use the file from your normal Linux system. This file is different on every machine and thus I can't create it here. Since you would want to have the same options regarding lilo as you have when you're using your normal Linux system you would create the file exactly as it is on the normal system.

Copy the Lilo configuration file and kernel images that Lilo uses by running the following commands from a shell on your normal Linux system. Don't execute these commands from your chroot'ed shell.

```
root:~#   cp /etc/lilo.conf $LFS/etc
root:~#   cp /boot/<kernel images> $LFS/boot
```

Before you can execute the second command you need to know the names of the kernel images. You can't just copy all files from the /boot directory. The /etc/lilo.conf file contains the names of the kernel images you're using. Open the file and look for lines like this:

```
image=/boot/vmlinuz
```

Look for all *image* variables and their values represent the name and location of the image files. These files will usually be in /boot but they might be in other directories as well, depending on your distribution's conventions.

---

# Configuring Sysklogd

Create a new file `/etc/syslog.conf` containing the following:

```
# Begin /etc/syslog.conf

auth,authpriv.* –/var/log/auth.log
*.*;auth,authpriv.none –/var/log/sys.log
daemon.* –/var/log/daemon.log
kern.* –/var/log/kern.log
mail.* –/var/log/mail.log
user.* –/var/log/user.log
*.emerg *

# End /etc/syslog.conf
```

---

# Configuring Shadow Password Suite

This package contains the utilities to modify user's passwords, add new users/groups, delete users/groups and more. I'm not going to explain to you what 'password shadowing' means. You can read all about that in the doc/HOWTO file. There's one thing you should keep in mind, if you decide to use shadow support, that programs that need to verify passwords (examples are xdm, ftp daemons, pop3 daemons, etc) need to be 'shadow–compliant', eg. they need to be able to work with shadowed passwords.

If you decide you don't want to use shadowed passwords (after you're read the doc/HOWTO document), you still use this archive since the utilities in this archive are also used on system which have shadowed passwords disabled. You can read all about this in the HOWTO. Also note that you can switch between shadow and non–shadow at any point you want.

Now is a very good moment to read chapter 5 of the doc/HOWTO file. You can read how you can test if shadowing works and if not, how to disable it. If it doesn't work and you haven't tested it, you'll end up with

an unusable system after you logout of all your consoles, since you won't be able to login anymore. You can easily fix this by passing the init=/sbin/sulogin parameter to the kernel, unpack the util−linux archive, go to the login−utils directory, build the login program and replace the /bin/login by the one in the util−linux package. Things are never hopelessly messed up (at least not under Linux), but you can avoid a hassle by testing properly and reading manuals ;)

## Configuring Sysvinit

Create a new file `/etc/inittab` containing the following:

```
# Begin /etc/inittab

id:3:initdefault:

si::sysinit:/etc/init.d/rcS

su:S:wait:/sbin/sulogin

l0:0:wait:/etc/init.d/rc 0
l1:1:wait:/etc/init.d/rc 1
l2:2:wait:/etc/init.d/rc 2
l3:3:wait:/etc/init.d/rc 3
l4:4:wait:/etc/init.d/rc 4
l5:5:wait:/etc/init.d/rc 5
l6:6:wait:/etc/init.d/rc 6

f1:0:respawn:/sbin/sulogin
f2:6:respawn:/sbin/sulogin

ca:12345:ctrlaltdel:/sbin/shutdown −t1 −a −r now

1:2345:respawn:/sbin/agetty /dev/tty1 9600
2:2345:respawn:/sbin/agetty /dev/tty2 9600
3:2345:respawn:/sbin/agetty /dev/tty3 9600
4:2345:respawn:/sbin/agetty /dev/tty4 9600
5:2345:respawn:/sbin/agetty /dev/tty5 9600
6:2345:respawn:/sbin/agetty /dev/tty6 9600

# End /etc/inittab
```

## Creating the /var/run/utmp file

Programs like login, shutdown, uptime and others want to read from and write to the /var/run/utmp file.

This file contains information about who is currently logged in. It also contains information on when the computer was last booted and shutdown.

Create the `/var/run/utmp` and give it the proper permissions by running the following commands:

```
root:~# touch /var/run/utmp
root:~# chmod 0644 /var/run/utmp
```

## Configuring Vim

By default Vim runs in vi compatible mode. Some people might like this, but I have a high preference to run vim in vim mode (else I wouldn't have included Vim in this book but the original Vi). Create the `/root/.vimrc` containing the following:

```
set nocompatible
set bs=2
```

## Creating root password

Choose a password for user root and create it by running the following command:

```
root:~#   passwd root
```

# Chapter 6. Creating system boot scripts

# What is being done here

This chapter will create the necessary scripts that are run at boottime. These scripts perform tasks such as remounting the root file system mounted read−only by the kernel into read−write mode, activiating the swap partition(s), running a check on the root file system to make sure it's intact and starting the daemons that the system uses.

---

# Creating directories

We need to start by creating a few extra directories that are used by the boot scripts. Create these directories by running:

```
root:~#   cd /etc
root:etc#   mkdir sysconfig rc0.d rc1.d rc2.d rc3.d
root:etc#   mkdir rc4.d rc5.d rc6.d init.d rcS.d
```

# Creating the rc script

The first main bootscript is the `/etc/init.d/rc` script. Create a new file `/etc/init.d/rc` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/rc
#
# By Jason Pearce  – jason.pearce@linux.org
# Modified by Gerard Beekmans – gerard@linuxfromscratch.org
#

# Un–comment the following for debugging.
# debug=echo

#
# Start script or program.
#
startup() {
case "$1" in
        *.sh)
                $debug sh "$@"
                ;;
        *)
                $debug "$@"
                ;;
esac
}

# Ignore CTRL–C only in this shell, so we can interrupt subprocesses.
trap ":" INT QUIT TSTP

# Set onlcr to avoid staircase effect.
stty onlcr 0>&1

# Now find out what the current and what the previous runlevel are.
runlevel=$RUNLEVEL
# Get first argument. Set new runlevel to this argument.

[ "$1" != "" ] && runlevel=$1
if [ "$runlevel" = "" ]
then
        echo "Usage: $0 <runlevel>" >&2
        exit 1
fi

previous=$PREVLEVEL
```

```
[ "$previous" = "" ] && previous=N

export runlevel previous

# Is there an rc directory for this new runlevel?

if [ −d /etc/rc$runlevel.d ]
then
      # First, run the KILL scripts for this runlevel.
      if [ $previous != N ]
      then
            for i in /etc/rc$runlevel.d/K*
      do
            [ ! −f $i ] && continue

                  suffix=${i#/etc/rc$runlevel.d/K[0−9][0−9]}
                  previous_start=/etc/rc$previous.d/S[0−9][0−9]$suffix
                  sysinit_start=/etc/rcS.d/S[0−9][0−9]$suffix

                  # Stop the service if there is a start script
                  # in the previous run level.
                  [ ! −f $previous_start ] && [ ! −f sysinit_start] && continue

                  startup $i stop
            done
      fi

      # Now run the START scripts for this runlevel.
      for i in /etc/rc$runlevel.d/S*
      do
            [ ! −f $i ] && continue

            if [ $previous != N ]
      then
                  # Find start script in previous runlevel and
                  # stop script in this runlevel.
                  suffix=${i#/etc/rc$runlevel.d/S[0−9][0−9]}
                  stop=/etc/rc$runlevel.d/K[0−9][0−9]$suffix
                  previous_start=/etc/rc$previous.d/S[0−9][0−9]$suffix

                  # If there is a start script in the previous
                  # level
                  # and _no_ stop script in this level, we don't
                  # have to re−start the service.
                  [ −f $previous_start ] && [ ! −f $stop ] && continue
            fi

            case "$runlevel" in
                  0|6)
                        startup $i stop
                        ;;
```

```
                *)
                        startup $i start
                        ;;
        esac
    done
fi

# End /etc/init.d/rc
```

# Creating the rcS script

The second main bootscript is the `rcS` script. Create a new file `/etc/init.d/rcS` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/rcS

runlevel=S
prevlevel=N
umask 022
export runlevel prevlevel

trap ":" INT QUIT TSTP

for i in /etc/rcS.d/S??*
do
        [ ! –f  "$i" ] && continue;
                $i start
done

# End /etc/init.d/rcS
```

# Creating the functions script

Create a new file `/etc/init.d/functions` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/functions

COL=70
SET_COL="echo –en \\033[${COL}G"
NORMAL="echo –en \\033[0;39m"
SUCCESS="echo –en \\033[1;32m"
FAILURE="echo –en \\033[1;31m"

evaluate_retval()
{
if [ $? = 0 ]
then
print_status success
else
print_status failure
fi
}

print_status()
{
if [ $# = 0 ]
then
echo "Usage: print_status {success|failure}"
exit 1
fi

case "$1" in
success)
$SET_COL
echo –n "[  "
$SUCCESS
echo –n "OK"
$NORMAL
echo "  ]"
echo –en "\r"
;;
failure)
$SET_COL
echo –n "["
$FAILURE
echo –n "FAILED"
$NORMAL
```

```
echo −n "]"
echo −en "\r"
;;
esac

}

loadproc()
{
if [ $# = 0 ]
then
echo "Usage: loadproc {program}"
exit 1
fi

base=`basename $1`

pidlist=`pidof −o $$ −o $PPID −o %PPID −x $base`

pid=""

for apid in $pidlist
do
if [ −d /proc/$apid ]
then
pid="$pid $apid"
fi
done

if [ ! −n "$pid" ]
then
$*

evaluate_retval
else
print_status failure
fi

}

killproc()
{

if [ $# = 0 ]
then
echo "Usage: killproc {program} [signal]"
exit 1
fi

base=`basename $1`
```

```
if [ "$2" != "" ]
then
killlevel=$2
else
nolevel=1
fi

pidlist=`pidof −o $$ −o $PPID −o %PPID −x $base`

pid=""

for apid in $pidlist
do
if [ −d /proc/$apid ]
then
pid="$pid $apid"
fi
done

if [ −n "$pid" ]
then
if [ "$nolevel" = 1 ]
then
kill −TERM $pid
if ps h $pid >/dev/null 2>&1
then
kill −KILL $pid
fi
ps h $pid >/dev/null 2>&1
if [ $? = 0 ]
then
print_status failure
else
rm −f /var/run/$base.pid
print_status success
fi
else
kill $killlevel $pid
ps h $pid >/dev/null 2>&1
if [ $? = 0 ]
then
print_status failure
else
rm −f /var/run/$base.pid
print_status success
fi
fi
else
print_status failure
fi
}
```

```
reloadproc()
{
if [ $# = 0 ]
then
echo "Usage: reloadproc {program} [signal]"
exit 1
fi

base=`basename $1`

if [ −n "$2" ]
then
killlevel=$2
else
nolevel=1
fi

pidlist=`pidof −o $$ −o $PPID −o %PPID −x $base`

pid=""

for apid in $pidlist
do
if [ −d /proc/$apid ]
then
pid="$pid $apid"
fi
done

if [ −n "$pid" ]
then
if [ "$nolevel" = 1 ]
then
kill −SIGHUP $pid
evaluate_retval
else
kill $killlevel $pid
evaluate_retval
fi
else
print_status failure
fi
}

statusproc()
{
        if [ $# = 0 ]
        then
                echo "Usage: status {program}"
                return 1
```

```
        fi

        pid=`pidof -o $$ -o $PPID -o %PPID -x $1`
        if [ -n "$pid" ]
        then
                echo "$1 running with Process ID $pid"
                return 0
        fi

        if [ -f /var/run/$1.pid ]
        then
                pid=`head -1 /var/run/$1.pid`
                if [ -n "$pid" ]
                then
                        echo "$1 not running but /var/run/$1.pid exists"
                        return 1
                fi
        fi

}

# End /etc/init.d/functions
```

# Creating the checkfs script

Create a new file `/etc/init.d/checkfs` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/checkfs

source /etc/init.d/functions

echo −n "Activating swap..."
/sbin/swapon −a
evaluate_retval

if [ −f /fastboot ]
then
        echo "Fast boot, no file system check"
        rm /fastboot
else
        /bin/mount −n −o remount,ro /
        if [ $? = 0 ]
        then
                if [ −f /forcefsck ]
                then
echo "/forcefsck exists, forcing file system check"
                        force="−f"
                else
                        force=""
                fi

                echo "Checking file systems..."
                /sbin/fsck $force −a −A −C −T −V

                if [ $? −gt 1 ]
                then
                        $FAILURE
echo
                        echo −n "fsck failed. Please repair your file "
                        echo "systems manually by running /sbin/fsck"
                        echo "without the −a option"
                        echo
                        echo −n "Please note that the root file system is "
                        echo "currently mounted in read−only mode."
                        echo
                        echo −n "I will start sulogin now. When you  "
                        echo "logout I will reboot your system."
                        echo
$NORMAL
```

```
                /sbin/sulogin
                /sbin/reboot -f
else
print_status success
fi

    else
        echo -n "Cannot check root file system because it "
        echo "could not be mounted in read-only mode."
    fi
fi

# End /etc/init.d/checkfs
```

# Creating the halt script

Create a new file `/etc/init.d/halt` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/halt

/sbin/halt –d –f –i –p

# End /etc/init.d/halt
```

# Creating the loadkeys script

You only need to create this script if you don't have a default 101 keys US keyboard layout. Create a new file `/etc/init.d/loadkeys` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/loadkeys

source /etc/init.d/functions

echo –n "Loading keymap..."
/usr/bin/loadkeys /usr/share/keymaps/<arch>/<layout>/<keymap> >/dev/null
evaluate_retval

# End /etc/init.d/loadkeys
```

Replace <arch>, <layout> and <keymap> with the proper directories and filenames to match your system and language.

---

# Creating the mountfs script

Create a new file `/etc/init.d/mountfs` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/mountfs

source /etc/init.d/functions

echo −n "Remounting root file system in read−write mode..."
/bin/mount −n −o remount,rw /
evaluate_retval

echo > /etc/mtab
/bin/mount −f −o remount,rw /

/bin/rm −f /fastboot /forcefsck

echo −n "Mounting other file systems..."
/bin/mount −a
evaluate_retval

# End /etc/init.d/mountfs
```

# Creating the reboot script

Create a new file `/etc/init.d/reboot` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/reboot

echo "System reboot in progress..."

/sbin/reboot –d –f –i

# End /etc/init.d/reboot
```

# Creating the sendsignals script

Create a new file `/etc/init.d/sendsignals` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/sendsignals

. /etc/init.d/functions

echo −n "Sending all processes the TERM signal..."
/sbin/killall5 −15
evaluate_retval

echo −n "Sending all processes the KILL signal..."
/sbin/killall5 −9
evaluate_retval

# End /etc/init.d/sendsignals
```

# Creating the setclock script

The following script is only for real use when your hardware clock (also known as BIOS or CMOS clock) isn't set to GMT time. The recommended setup is setting your hardware clock to GMT and have the time converted to localtime using the /etc/localtime symbolic link. But if you run an OS that doesn't understand a clock set to GMT (most notable are Microsoft OS'es) you might want to set your clock to localtime so that the time is properly displayed on those OS'es. This script will reset the kernel time to the hardware clock without converting the time using the /etc/localtime symlink.

If you want to use this script on your system even if you have your hardware clock set to GMT, then change the UTC variable below to the value of *1*.

```
#!/bin/sh
# Begin /etc/init.d/setclock

source /etc/init.d/functions
source /etc/sysconfig/clock

CLOCKPARAMS="−−hctosys"

case "$UTC" in
yes|true|1)
CLOCKPARAMS="$CLOCKPARAMS −u"
;;
esac

echo −n "Setting clock..."
/sbin/hwclock $CLOCKPARAMS
evaluate_retval

# End /etc/init.d/setclock
```

---

# Creating the /etc/sysconfig/clock file

Create a new file `/etc/sysconfig/clock` containing the following:

```
UTC=0
```

If your hardware clock (also known as BIOS or CMOS clock) is not set to GMT time, than set the UTC variable in the /etc/sysconfig/clock file to the value *0* (zero).

# Creating the sysklogd script

Create a new file `/etc/init.d/sysklogd` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/sysklogd

source /etc/init.d/functions

case "$1" in
start)
echo −n "Starting system log daemon..."
loadproc /usr/sbin/syslogd −m 0

echo −n "Starting kernel log daemon..."
loadproc /usr/sbin/klogd
;;

stop)
echo −n "Stopping kernel log daemon..."
killproc klogd

echo −n "Stopping system log daemon..."
killproc syslogd
;;

reload)
echo −n "Reloading system log daemon configuration file..."
reloadproc syslogd −1
;;

restart)
$0 stop
sleep 1
$0 start
;;

status)
statusproc /usr/sbin/syslogd
statusproc /usr/sbin/klogd
;;

*)
echo "Usage: $0 {start|stop|reload|restart|status}"
exit 1
;;
```

```
esac

# End /etc/init.d/sysklogd
```

---

# Creating the umountfs script

Create a new file `/etc/init.d/umountfs` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/umountfs

source /etc/init.d/functions

echo −n "Deactivating swap..."
/sbin/swapoff −a
evaluate_retval

echo −n "Unmounting file systems..."
/bin/umount −a −r
evaluate_retval

# End /etc/init.d/umountfs
```

---

# Setting up symlinks and permissions

Give these files the proper permissions and create the necessary symlinks by running the following commands:

```
root:~#   cd /etc/init.d
root:init.d#   chmod 754 rc rcS functions checkfs halt
loadkeys mountfs
root:init.d#   chmod 754 reboot sendsignals setclock sysklogd
umountfs
root:init.d#   cd ../rc0.d
root:rc0.d#   ln -s ../init.d/sysklogd K90sysklogd
root:rc0.d#   ln -s ../init.d/sendsignals S80sendsignals
root:rc0.d#   ln -s ../init.d/umountfs S90umountfs
root:rc0.d#   ln -s ../init.d/halt S99halt
root:rc0.d#   cd ../rc6.d
root:rc6.d#   ln -s ../init.d/sysklogd K90sysklogd
root:rc6.d#   ln -s ../init.d/sendsignals S80sendsignals
root:rc6.d#   ln -s ../init.d/umountfs S90umountfs
root:rc6.d#   ln -s ../init.d/reboot S99reboot
root:rc6.d#   cd ../rcS.d
root:rcS.d#   ln -s ../init.d/setclock S01setclock
root:rcS.d#   ln -s ../init.d/checkfs S05checkfs
root:rcS.d#   ln -s ../init.d/mountfs S10mountfs
root:rcS.d#   ln -s ../init.d/loadkeys S20loadkeys
root:rcS.d#   cd ../rc1.d
root:rc1.d#   ln -s ../init.d/sysklogd K90sysklogd
root:rc1.d#   cd ../rc2.d
root:rc2.d#   ln -s ../init.d/sysklogd S03sysklogd
root:rc2.d#    cd ../rc3.d
root:rc3.d#    ln -s ../init.d/sysklogd S03sysklogd
root:rc3.d#    cd ../rc4.d
root:rc4.d#    ln -s ../init.d/sysklogd S03sysklogd
root:rc4.d#    cd ../rc5.d
root:rc5.d#    ln -s ../init.d/sysklogd S03sysklogd
```

# Creating the /etc/fstab file

In order for certain programs to be able to determine where certain partitions are supposed to be mounted by default, the /etc/fstab file is used. Create a new file `/etc/fstab` containing the following:

```
# Begin /etc/fstab

/dev/<LFS−partition designation> / ext2 defaults 1 1
/dev/<swap−partition designation> none swap sw 0 0
proc /proc proc defaults 0 0

# End /etc/fstab
```

Replace <LFS−partition designation> and <swap−partition designation> with the appropriate devices (/dev/hda5 and /dev/hda6 in my case).

---

# Chapter 7. Setting up basic networking

# Introduction

This chapter will setup basic networking. Although you might not be connected to a network, Linux software uses network functions anyway. We'll be installing at least the local loopback device and a network card as well if applicable. Also the proper bootscripts will be created so that networking will be enabled during boot time.

---

# Installing network software

## Installing Netkit–base

Install Netkit–base by running the following commands:

```
root:netkit-base-0.16#    ./configure --prefix=/usr
root:netkit-base-0.16#    make -e
root:netkit-base-0.16#    make install
root:netkit-base-0.16#    cd etc.sample
root:netkit-base-0.16/etc.sample#    cp services protocols /etc
```

---

## Installing Net–tools

Edit the `Makefile` file and edit the CFLAGS variable if you want to add compiler optimzations.

Install Net–tools by running the following commands:

```
root:net-tools-1.57#    make
root:net-tools-1.57#    make install
```

You might have noticed that we don't use the compiler optimizations for this package. The reason is that overriding the CFLAGS variable causes compilation problems. You would have to edit the Makefile file and add the proper values to the CFLAGS variable and then compile the package. If you want to do that it's up to you. I don't think it's worth the trouble though. The programs in this package aren't that big that optimization would have any noticable effect on the performance.

---

# Creating network boot scripts

## Creating the /etc/init.d/localnet bootscript

Create a new file `/etc/init.d/localnet` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/localnet

source /etc/init.d/functions
source /etc/sysconfig/network

case "$1" in
        start)
                echo –n "Bringing up the loopback interface..."
                /sbin/ifconfig lo 127.0.0.1
                evaluate_retval

                echo –n "Setting up hostname..."
                /bin/hostname $HOSTNAME
                evaluate_retval
                ;;

        stop)
                echo –n "Bringing down the loopback interface..."
                /sbin/ifconfig lo down
                evaluate_retval
                ;;

        *)
                echo "Usage: $0: {start|stop}"
                exit 1
                ;;
esac

# End /etc/init.d/localnet
```

---

## Setting up permissions and symlink

Set the proper file permissions and create the necessary symlink by running the following commands:

```
root:~#    cd /etc/init.d
root:init.d#    chmod 754 /etc/init.d/localnet
root:init.d#    cd ../rcS.d
root:rcS.d#    ln -s ../init.d/localnet S03localnet
```

---

## Creating the /etc/sysconfig/network file

Create a new file `/etc/sysconfig/network` and put the hostname in it by running:

```
root:~#   echo "HOSTNAME=lfs" > /etc/sysconfig/network
```

Replace "lfs" by the name you wish to call your computer. Please not that you should not enter the FQDN (Fully Qualified Domain Name) here. That information will be put in the `/etc/hosts` file later.

---

## Creating the /etc/hosts file

If you want to configure a network card, you have to decide on the IP−address, FQDN and possible aliases for use in the /etc/hosts file. An example is:

```
<my−IP> myhost.mydomain.org aliases
```

Make sure the IP−address is in the private network IP−address range. Valid ranges are:

```
Class Networks
A    10.0.0.0
B    172.16.0.0 through 172.31.0.0
C    192.168.0.0 through 192.168.255.0
```

A valid IP address could be 192.168.1.1. A valid FQDN for this IP could be www.linuxfromscratch.org

If you're not going to use a network card, you still need to come up with a FQDN. This is necessary for programs like Sendmail to operate correctly (in fact; Sendmail won't run when it can't determine the FQDN).

If you don't configure a network card, create a new file `/etc/hosts` containing:

```
# Begin /etc/hosts (no network card version)

127.0.0.1 www.mydomain.com <value of HOSTNAME> localhost

# End /etc/hosts (no network card version)
```

If you do configure a network card, create a new file `/etc/hosts` containing:

```
# Begin /etc/hosts (network card version)

127.0.0.1 localhost.localdomain localhost
192.168.1.1 www.mydomain.org <value of HOSTNAME>

# End /etc/hosts (network card version)
```

Of course, change the 192.168.1.1 and www.mydomain.org to your own liking (or requirements if you are assigned an IP−address by a network/system administrator and you plan on connecting this machine to that network).

---

## Creating the /etc/init.d/ethnet script

This section only applies if you are going to configure a network card. If you're not, skip this section.

Create a new file `/etc/init.d/ethnet` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/ethnet

source /etc/init.d/functions
source /etc/sysconfig/network

case "$1" in
        start)
                echo −n "Bringing up the eth0 interface..."
                /sbin/ifconfig eth0 $IPADDR broadcast $BROADCAST netmask $NETMASK
                evaluate_retval
                ;;

        stop)
```

```
            echo –n "Bringing down the eth0 interface..."
            /sbin/ifconfig eth0 down
            evaluate_retval
            ;;

        *)
            echo "Usage: $0 {start|stop}"
            exit 1
            ;;
esac

# End /etc/init.d/ethnet
```

---

## Editing the /etc/sysconfig/network file

Edit the `/etc/sysconfig/network` file and add the following lines to it. Don't remove the HOSTNAME= line.

```
IPADDR=192.168.1.1
NETMASK=255.255.255.0
BROADCAST=192.168.1.255
```

Chagne the IPADDR, NETMASK and BROADCAST values to match your network setup.

---

## Setting up permissions and symlink

Set the proper file permissions and create the necessary symlink by running the following commands:

```
root:~#    cd /etc/init.d
root:init.d#    chmod 754 /etc/init.d/ethnet
root:init.d#   cd ../rc1.d
root:rc1.d#   ln –s ../init.d/ethnet K90ethnet
root:rc1.d#   cd ../rc2.d
root:rc2.d#   ln –s ../init.d/ethnet K90ethnet
root:rc2.d#    cd ../rc3.d
root:rc3.d#    ln –s ../init.d/ethnet S10ethnet
root:rc3.d#    cd ../rc4.d
root:rc4.d#    ln –s ../init.d/ethnet S10ethnet
root:rc4.d#    cd ../rc5.d
```

```
root:rc5.d#    ln -s ../init.d/ethnet S10ethnet
```

# Chapter 8. Making the LFS system bootable

# Introduction

This chapter will make LFS bootable. This chapter deals with building a new kernel for our new LFS system and adding the proper entries to LILO so that you can select to boot the LFS system at the LILO: prompt.

---

# Installing a kernel

A kernel is the heart of a Linux system. We could use the kernel image from our normal system, but we might as well compile a new kernel from the most recent kernel sources available.

Building the kernel involves a few steps: configuring it and compiling it. There are a few ways to configure the kernel. If you don't like the way this book does it, read the `README` file and find out what your other options are. Run the following commands to build the kernel:

```
root:linux#   make mrproper
root:linux#    make menuconfig
root:linux#    make dep
root:linux#    make bzImage
root:linux#   make modules
root:linux#   make modules_install
root:linux#    cp arch/i386/boot/bzImage /boot/lfskernel
root:linux#   cp System.map /boot
```

# Adding an entry to LILO

In order to being able to boot from this partition, we need to update our /etc/lilo.conf file. Add the following lines to lilo.conf:

```
image=/boot/lfskernel
  label=lfs
  root=<partition>
  read-only
```

<partition> must be replaced by your partition's designation (which would be /dev/hda5 in my case).

Now update the boot loader by running:

```
root:~#    lilo
```

---

# Testing the system

Now that all software has been installed, bootscripts have been written and the local network is setup, it's time for you to reboot your computer and test these new scripts to verify that they actually work. You first want to execute them manually from the /etc/init.d directory so you can fix the most obvious problems (typos, wrong paths and such). When those scripts seem to work just fine manually they should also work during a system start or shutdown. There's only one way to test that. Shutdown your system with shutdown –r now and reboot into LFS. After the reboot you will have a normal login prompt like you have on your normal Linux system (unless you use XDM or some sort of other Display Manger (like KDM – KDE's version of XDM).

# III. Part III – Installing LFS on Apple PowerPC systems

***Table of Contents***

*9. Packages you need to download*
*10. Preparing a new partition*
*11. Installing basic system software*
*12. Creating system boot scripts*
*13. Setting up basic networking*
*14. Making the LFS system bootable*

---

# Chapter 9. Packages you need to download

Below is a list of all the packages you need to download for building the basic system. The version numbers printed correspond to versions of the software that is known to work and which this book is based on. If you experience problems which you can't solve yourself, download the version that is assumed in this book (in case you download a newer version).

The listed file sizes refer to the sizes of the .tar.gz archives. Sometimes you can find .tar.bz2 archives, but as .tar.gz is still the most widely used format, that size is listed.

- Bash (2.04) – 1,708,138 bytes: ftp://ftp.gnu.org/gnu/bash/
- Binutils (2.10) 7,210,401 bytes: ftp://ftp.gnu.org/gnu/binutils/
- Bzip2 (1.0.1) 464,991 bytes: http://sourceware.cygnus.com/bzip2/
- Diff Utils (2.7) 312,330 bytes: ftp://ftp.gnu.org/gnu/diffutils/
- File Utils (4.0) 1,181,464 bytes: ftp://ftp.gnu.org/gnu/fileutils/
- GCC (2.95.2) 12,973,458 bytes: ftp://ftp.gnu.org/gnu/gcc/
- Linux Kernel (2.2.16) 17,261,494 bytes: ftp://ftp.kernel.org/pub/linux/kernel/
- Kernel USB patch: 216.22.163.20/usb−2.3.50−1−for−2.2.14.diff.gz
- Glibc (2.1.3) 9,106,875 bytes: ftp://ftp.gnu.org/gnu/glibc/
- Glibc−crypt (2.1.3) 40,930 bytes: ftp://ftp.gwdg.de/pub/linux/glibc/
- Glibc−linuxthreads (2.1.3) 154,425 bytes: ftp://ftp.gnu.org/gnu/glibc/
- Glibc Patch (2.1.3) – 751 bytes: http://www.linuxfromscratch.org/download/glibc−2.1.3.patch.gz
- Glibc−ctype−patch: ftp://216.22.163.20/glibc−2.1.3−ctype.patch
-

Grep (2.4.2) 463,477 bytes: ftp://ftp.gnu.org/gnu/grep/

- Gzip (1.2.4a) 221,779 bytes: ftp://ftp.gnu.org/gnu/gzip/
- Make (3.79.1) 1,037,173 bytes: ftp://ftp.gnu.org/gnu/make/
- Sed (3.02) 265,549 bytes: ftp://ftp.gnu.org/gnu/sed/
- Shell Utils (2.0) 1,253,022 bytes: ftp://ftp.gnu.org/gnu/sh−utils/
- Tar (1.13) 1.058,280 bytes: ftp://ftp.gnu.org/gnu/tar/
- Text Utils (2.0) 1,547,106 bytes: ftp://ftp.gnu.org/gnu/textutils/
- MAKEDEV (2.5) − 11,562 bytes: ftp://ftp.ihg.uni−duisburg.de/Linux/system
- Ed (0.2) 185,913 bytes: ftp://ftp.gnu.org/gnu/ed/
- Patch (2.5.4) 187,675 bytes: ftp://ftp.gnu.org/gnu/patch/
- Bison (1.28) 422,864 bytes: ftp://ftp.gnu.org/gnu/bison/
- Mawk (1.3.3) 209,948 bytes: ftp://ftp.whidbey.net/pub/brennan/
- Find Utils (4.1) 294,512 bytes: ftp://ftp.gnu.org/gnu/findutils/
- Find Utils Patch (4.1) 985 bytes: http://www.linuxfromscratch.org/download/findutils−4.1.patch.gz
- Ncurses (4.2) 1,260,898 bytes: ftp://ftp.gnu.org/gnu/ncurses/ (newer versions than 4.2 are known not to work on PPC)
- Less (358) 231,140 bytes: ftp://ftp.gnu.org/gnu/less/
- Groff (1.16) 1,427,333 bytes: ftp://ftp.gnu.org/gnu/groff/

Man (1.5h1) 179,170 bytes: ftp://ftp.win.tue.nl/pub/linux−local/utils/man/

- Perl (5.6.0) 5,491,334 bytes: http://www.perl.com
- M4 (1.4) 319,084 bytes: ftp://ftp.gnu.org/gnu/m4/
- Texinfo (4.0) 1,140,565 bytes: ftp://ftp.gnu.org/gnu/texinfo/
- Autoconf (2.13) 445,493 bytes: ftp://ftp.gnu.org/gnu/autoconf/
- Automake (1.4) 355,529 bytes: ftp://ftp.gnu.org/gnu/automake/
- Flex (2.5.4a) 383,228 bytes: ftp://ftp.gnu.org/non−gnu/flex/
- File (3.31) 138,549 bytes: ftp://ftp.gw.com/mirrors/pub/unix/file/
- Gettext (0.10.35) 718.331 bytes: ftp://ftp.gnu.org/gnu/gettext/
- Libtool (1.3.5) 541,231 bytes: ftp://ftp.gnu.org/gnu/libtool/
- Console−tools (0.2.3) 673,736 bytes: ftp://metalab.unc.edu/pub/Linux/system/keyboards/
- Console−tools (0.2.3) Patch: 4,059 bytes: http://www.linuxfromscratch.org/download/console−tools−0.2.3.patch.gz
- Console−data (1999.08.29) 560,870 bytes: ftp://metalab.unc.edu/pub/Linux/system/keyboards/
- E2fsprogs (1.18) 835,075 bytes: ftp://tsx−11.mit.edu/pub/linux/packages/ext2fs/
- Ld.so (1.9.9) 356,800 bytes: ftp://tsx−11.mit.edu/pub/linux/packages/GCC/
- Bin86 (0.15.1) 142,195 bytes: http://www.cix.co.uk/~mayday/
- Shadow Password Suite (19990827) 727,755 bytes: ftp://ftp.ists.pwr.wroc.pl/pub/linux/shadow/
-

Modutils (2.3.12) 202,061 bytes: ftp://ftp.ocs.com.au/pub/modutils/

- Procinfo (17) 22,976 bytes: ftp://ftp.cistron.nl/pub/people/svm/
- Procps (2.0.7) 196,993 bytes: ftp://people.redhat.com/johnsonm/procps/
- Psmisc (19) 21,681 bytes: ftp://lrcftp.epfl.ch/pub/linux/local/psmisc/
- Vim−rt (5.7) 1,103,734 bytes: ftp://ftp.vim.org/pub/editors/vim/unix/
- Vim−src (5.7) 1,238.878 bytes: ftp://ftp.vim.org/pub/editors/vim/unix/
- Sysklogd (1.3.31) 96,281 bytes: ftp://sunsite.unc.edu/pub/Linux/system/daemons/
- Sysvinit (2.78) 109,524 bytes: ftp://ftp.cistron.nl/pub/people/miquels/sysvinit/
- Util Linux (2.10m) 1,207,247 bytes: ftp://ftp.win.tue.nl/pub/linux/utils/util−linux/
- Pmac Utils( (1.1.1): ftp://216.22.163.20/pmac−utils−1.1.1−patched.tar.gz
- Man−pages (1.30) 667,665 bytes: ftp://ftp.win.tue.nl/pub/linux/docs/manpages/
- Netkit−base (0.16) 52,943 bytes: ftp://ftp.uk.linux.org/pub/linux/Networking/netkit/
- Net−tools (1.57) 262,342 bytes: http://www.tazenda.demon.co.uk/phil/net−tools/

# Chapter 10. Preparing a new partition

# Introduction

In this chapter the partition that is going to host the LFS system is going to be prepared. A new partition will be created, an ext2 file system will be created on it and the directory structure will be created. When this is done, we can move on to the next chapter and start building a new Linux system from scratch.

# Creating a new partition

Before we can build our new Linux system, we need to have an empty Linux partition on which we can build our new system. I recommend a partition size of at least 750 MB. This gives you enough space to store all the tarballs and to compile all packages without worrying running out of the necessary temporary disk sapce. If you already have a Linux Native partition available, you can skip this subsection.

Start the pdisk program (or some other fdisk program you prefer) with the appropriate hard disk as the option (like /dev/shda if you want to create a new partition on the first SCSI disk). The partition that is available for partitioning is called *Apple_Free_Space*. To create a linux capable partition in that free space, type c followed by the partition designation of the free space p<n>, the size in MB of the desired partition <size>M and the name of the partition <name>. The example below creates a 1.8 GB partition name root starting at the beginning of the free space designated as partition 6: *c p6 1800M root*

---

# Mounting the new partition

Now that we have created the ext2 file system, it is ready for use. All we have to do to be able to access it (as in reading from and writing date to it) is mounting it. If you mount it under /mnt/lfs, you can access this partition by going to the /mnt/lfs directory and then do whatever you need to do. This document will assume that you have mounted the partition on a subdirectory under /mnt. It doesn't matter which directory you choose (or you can use just the /mnt directory as the mount point) but this book will assume /mnt/lfs in the commands it tells you to execute.

Create the /mnt/lfs directory by runnning:

```
root:~#    mkdir -p /mnt/lfs
```

Now mount the LFS partition by running:

```
root:~#    mount /dev/xxx /mnt/lfs
```

Replace "xxx" by your partition's designation.

This directory (/mnt/lfs) is the $LFS variable you have read about earlier. So if you read somewhere to "cp inittab $LFS/etc" you actually will type "cp inittab /mnt/lfs/etc".

---

# Creating directories

Let's create the directory tree on the LFS partition according to the FHS standard which can be found at http://www.pathname.com/fhs/. Issuing the following commands will create the necessary directories:

```
root:~#   cd $LFS
root:lfs#   mkdir bin boot dev etc home lib mnt proc root
sbin tmp usr  var
root:lfs#   cd $LFS/usr
root:usr#   mkdir bin etc include lib local sbin share src
tmp var
root:usr#   ln -s share/man man
root:usr#   ln -s share/doc doc
root:usr#   ln -s share/info info
root:usr#   cd $LFS/usr/share
root:share#   mkdir dict doc info locale man nls misc
terminfo zoneinfo
root:share#   cd $LFS/usr/share/man
root:man#   mkdir man1 man2 man3 man4 man5 man6 man7 man8
root:man#   cd $LFS/usr/local
root:local#    mkdir bin etc include lib local sbin share src
tmp var
root:local#    ln -s share/man man
root:local#    ln -s share/doc doc
root:local#    ln -s share/info info
root:local#    cd $LFS/usr/local/share
root:share#    mkdir dict doc info locale man nls misc
terminfo zoneinfo
root:share#    cd $LFS/usr/local/share/man
root:man#    mkdir man1 man2 man3 man4 man5 man6 man7 man8
root:man#   cd $LFS/var
root:var#   mkdir lock log run spool tmp
```

Normally directories are created with permission mode 755, which isn't desired for all directories. I haven't checked the FHS if they suggest default modes for certain directories, so I'll just change the modes for two directories. The first change is a mode 0750 for the $LFS/root directory. This is to make sure that not just everybody can enter the /root directory (the same you would do with /home/username directories). The second change is a mode 1777 for the $LFS/tmp directory. This way every user can write stuff to the /tmp directory if they need to. The sticky (1) bit makes sure users can't delete other user's file which they normally can do because the directory is set in such a way that every body (owner, group, world) can write to that directory.

```
root:~#   cd $LFS
```

```
root:lfs#   chmod 0750 root
root:lfs#   chmod 0555 proc
root:lfs#   chmod 1777 tmp usr/tmp
```

Now that the directories are created, copy the source files you have downloaded in chapter 3 to some subdirectory under $LFS/usr/src (you will need to create this subdirectory yourself).

---

# Chapter 11. Installing basic system software

# How and why things are done

In this chapter we will install all the software that belongs to a basic Linux system. After you're done with this chapter you have a fully working Linux system. The remaining chapters deal with setting up networking, creating the boot scripts and adding an entry to lilo.conf so that you can boot your LFS system.

This chapter is devided in two chunks. The first part installs a few necessary programs on the LFS system. These programs are needed to install the rest of the programs that belong to a basic system. When the first part is done, we will enter a chroot'ed environment. This means that we start a shell with $LFS as the root directory (instead of the usual / directory as the root directory). This has the same effect as rebooting the computer into the LFS system, but this way we don't have to reboot. If something goes wrong, you don't need to reboot back in the normal Linux system to fix whatever you need to fix. You just open a new shell on a virtual console, or start a new xterm and you can do what you need to do.

The software in the first part will be linked statically. These programs will be re−installed in the second part and linked dynamically. The reason for the static version first is that there is a chance that our normal Linux system and your LFS system aren't using the same C Library versions. If the programs in the first part are linked against an older C library version, those program might not work well on the LFS system.

The key to learn what makes Linux tick is to know exactly what packages are used for and why you or the system needs them. In depth descriptions of the package are provided in Appendix A.

---

# Debugging symbols and compiler optimizations

Most programs and libraries by default are compiled with debugging symbols and optimizing level 2 (gcc options −g and −O2) and are compiled for a specific CPU. On Intel platforms software is compiled for i386 processors by default. If you don't wish to run software on other machines other than your own, you might want to change the default compiler options so that they will be compiled with a higher optimization level, no debugging symbols and generate code for your specific architecture. Let me first explain what debugging symbols are.

A program compiled with debugging symbols means you can run a program or library through a debugger and the debugger's output will be user friendlier. These debugging symbols also enlarge the program or library significantly.

To remove debugging symbols from a binary (must be an a.out or ELF binary) run **`strip --strip-debug filename`** You can use wild cards if you need to strip debugging symbols from multiple files (use something like strip −−strip−debug $LFS/usr/bin/*). Another, easier, options is just not to compile programs with debugging symbols. Most people will probably never use a debugger on software, so by leaving those symbols out you can save a lot of diskspace.

Before you wonder if these debugging symbols would make a big difference, here are some statistics:

- A static Bash binary with debugging symbols: 2.3MB
- A static Bash binary without debugging symbols: 645KB
- A dynamic Bash binary with debugging symbols: 1.2MB
- A dynamic Bash binary without debugging symbols: 478KB
- $LFS/lib and $LFS/usr/lib (glibc and gcc files) with debugging symbols: 87MB
- $LFS/lib and $LFS/usr/lib (glibc and gcc files) without debugging symbols: 16MB

Sizes may vary depending on which compiler was used and which C library version was used to link dynamic programs against, but your results will be similar if you compare programs with and without debugging symbols. After I was done with this chapter and stripped all debugging symbols from all LFS binaries and libraries I regained a little over 102 MB of disk space. Quite the difference.

There are a few ways to change the default compiler options. One way is to edit every Makefile file you can find in a package, look for the CFLAGS and CXXFLAGS variables (a well designed package uses the CFLAGS variable to define gcc compiler options and CXXFLAGS to define g++ compiler options) and change their values. Packages like binutils, gcc, glibc and others have a lot of Makefile files in a lot of subdirectories so this would take a lot of time to do. Instead there's an easier way to do things: create the CFLAGS and CXXFLAGS environment variables. Most configure scripts read the CFLAGS and

CXXFLAGS variables and use them in the Makefile files. A few packages don't follow this convention and those package require manual editing.

The optimization options presented here are a minimal set of optimizations. This is to ensure that it will work on most platforms. Run the following command in the shell that you are going to use to compile the software in. If you exit the shell to, for example, pause compilation and continue later, make sure you execute the following commands again when you start compiling again (you only need to execute it once when you open a new virtual console, xterm, Eterm or some other terminal emulation program). Or you can insert these commands into your `/etc/profile`, `$HOME/.bashrc` or similar files. Run the following commands to setup the environment variables:

```
root:~#    export CFLAGS="-O3 -mcpu=xxx -march=yyy"
root:~#    export CXXFLAGS="-O3 -mcpu=xxx -march=yyy"
```

Replace xxx and yyy with the appropriate cpu idenfifiers such as i686. More information on what values these variables can have can be found in the GCC info page.

Please keep in mind that if you find that a package doesn't compile and gives errors like "segmentation fault, core dumped" it's most likely got to do with these compiler optimizations. Try lowering the optimizing level by changing −O3 to −O2. If that doesn't work try −O or leave it out all together. Also try changing the −mcpu and −march variables. Compilers are very sensitive to certain hardware too. Bad memory can cause compilation problems when a high level of optimization is used, like the −O3 setting. The fact that I don't have any problems compiling everything with −O3 doesn't mean you won't have any problems either. Another problem can be the Binutils version that's installed on your system which often causes compilation problems in Glibc (most noticable in RedHat because RedHat often uses beta software which aren't always very stable. "RedHat likes living on the bleeding edge, but leaves the bleeding up to you" (quoted from somebody on the lfs−discuss mailinglist).

---

# Preparing the LFS system

We're about to start with installing the first set of packages. These packages will be, as previously explained, linked statically.

Before we start, make sure you have the CFLAGS and CXXFLAGS environment variables setup if you plan on using compiler optimizations.

---

# Installing Bash

## Installing Bash

Install Bash by running the following commands:

```
root:bash-2.04#   ./configure --enable-static-link \
> --prefix=/usr --disable-nls
root:bash-2.04#   make
root:bash-2.04#   make prefix=$LFS/usr install
root:bash-2.04#   cd $LFS/usr/bin
root:bin#   mv bash bashbug $LFS/bin
root:bin#   cd $LFS/bin
root:bin#   ln -s bash sh
```

---

## Contents

The Bash package contains the bash program

---

## Description

Bash is the Bourne–Again SHell, which is a widely used command interpreter on Unix systems. Bash is a program that reads from standard input, the keyboard. You type something and the program will evaluate what you have typed and do something with it, like running a program.

---

# Installing Binutils

## Installing Binutils

Install Binutils by running the following commands:

```
root:binutils-2.10#    ./configure --prefix=/usr --disable-nls
root:binutils-2.10#    make -e LDFLAGS=-all-static tooldir=/usr
root:binutils-2.10#  make -e prefix=$LFS/usr tooldir=$LFS/usr
install
```

---

## Description

The Binutils package contains the ld, as, ar, nm, objcopy, objdump, ranlib, size, strings, strip, c++filt, addr2line and nlmconv programs

---

## Description

### ld

ld combines a number of object and archive files, relocates their data and ties up symbol references. Often the last step in building a new compiled program to run is a call to ld.

---

### as

as is primarily intended to assemble the output of the GNU C compiler gcc for use by the linker ld.

---

### ar

The ar program creates, modifies, and extracts from archives. An archive is a single file holding a collection of other files in a structure that makes it possible to retrieve the original individual files (called members of the archive).

---

### nm

nm lists the symbols from object files.

---

## objcopy

objcopy utility copies the contents of an object file to another. objcopy uses the GNU BFD Library to read and write the object files. It can write the destination object file in a format different from that of the source object file.

---

## objdump

objdump displays information about one or more object files. The options control what particular information to display. This information is mostly useful to programmers who are working on the compilation tools, as opposed to programmers who just want their program to compile and work.

---

## ranlib

ranlib generates an index to the contents of an archive, and stores it in the archive. The index lists each symbol defined by a member of an archive that is a relocatable object file.

---

## size

size lists the section sizes −−and the total size−− for each of the object files objfile in its argument list. By default, one line of output is generated for each object file or each module in an archive.

---

## strings

For each file given, strings prints the printable character sequences that are at least 4 characters long (or the number specified with an option to the program) and are followed by an unprintable character. By default, it only prints the strings from the initialized and loaded sections of object files; for other types of files, it prints the strings from the whole file.

strings is mainly useful for determining the contents of non−text files.

---

## strip

strip discards all or specific symbols from object files. The list of object files may include archives. At least one object file must be given. strip modifies the files named in its argument, rather than writing modified copies under different names.

---

## c++filt

The C++ language provides function overloading, which means that you can write many functions with the same name (providing each takes parameters of different types). All C++ function names are encoded into a low−level assembly label (this process is known as mangling). The c++filt program does the inverse

mapping: it decodes (demangles) low−level names into user−level names so that the linker can keep these overloaded functions from clashing.

## addr2line

addr2line translates program addresses into file names and line numbers. Given an address and an executable, it uses the debugging information in the executable to figure out which file name and line number are associated with a given address.

## nlmconv

nlmconv converts relocatable object files into the NetWare Loadable Module files, optionally reading header files for NLM header information.

# Installing Bzip2

## Installing Bzip2

Install Bzip2 by running the following commands:

```
root:bzip2-1.0.0#   sed \
> s/"\$(CC) \$(CFLAGS) -o"/"\$(CC) \$(CFLAGS) \$(LDFLAGS)
-o"/ \
> Makefile >Makefile2
root:bzip2-1.0.1#   mv Makefile2 Makefile
root:bzip2-1.0.1#   make LDFLAGS=-static
root:bzip2-1.0.1#   make PREFIX=$LFS/usr install
root:bzip2-1.0.1#   cd $LFS/usr/bin
root:bin#   mv bzcat bunzip2 bzip2 bzip2recover $LFS/bin
```

---

## Contents

The Bzip2 packages contains the bzip2, bunzip2, bzcat and bzip2recover programs.

---

## Description

### Bzip2

bzip2 compresses files using the Burrows–Wheeler block sorting text compression algorithm, and Huffman coding. Compression is generally considerably better than that achieved by more conventional LZ77/LZ78–based compressors, and approaches the performance of the PPM family of statistical compressors.

---

### Bunzip2

Bunzip2 decompresses files that are compressed with bzip2.

---

### bzcat

bzcat (or bzip2 –dc) decompresses all specified files to the standard output.

---

## bzip2recover

bzip2recover recovers data from damaged bzip2 files.

# Installing Diffutils

## Installing Diffutils

Install Diffutils by running the following commands:

```
root:diffutils-2.7#
CPPFLAGS=-Dre_max_failures=re_max_failures2 \
> ./configure --prefix=/usr --disable-nls
root:diffutils-2.7#   make LDFLAGS=-static
root:diffutils-2.7#   make prefix=$LFS/usr install
```

---

## Contents

The Diffutils packagec contains the cmp, diff, diff3 and sdiff programs.

---

## Description

### cmp and diff

cmp and diff both compare two files and report their differences. Both programs have extra options which compare files in different situations.

---

### diff3

The difference between diff and diff3 is that diff comprares 2 files, diff3 compares 3 files.

---

### sdiff

sdiff merges two two files and interactively outputs the results.

---

# Installing Fileutils

## Installing Fileutils

Install Fileutils by running the following commands:

```
root:fileutils-4.0#   ./configure --disable-nls --prefix=/usr
root:fileutils-4.0#   make -e LDFLAGS=-static
root:fileutils-4.0#   make -e prefix=$LFS/usr install
root:fileutils-4.0#   cd $LFS/usr/bin
root:bin#   mv chgrp chmod chown cp dd df dir $LFS/bin
root:bin#   mv dircolors du install ln ls mkdir mkfifo
$LFS/bin
root:bin#   mv mknod mv rm rmdir sync touch vdir $LFS/bin
```

---

## Contents

The Fileutils package contains the chgrp, chmod, chown, cp, dd, df, dir, dircolors, du, install, ln, ls, mkdir, mkfifo, mknod, mv, rm, rmdir, sync, touch and vdir programs.

---

## Description

### chgrp

chgrp changes the group ownership of each given file to the named group, which can be either a group name or a numeric group ID.

---

### chmod

chmod changes the permissions of each given file according to mode, which can be either a symbolic representation of changes to make, or an octal number representing the bit pattern for the new permissions.

---

### chown

chown changes the user and/or group ownership of each given file.

---

## cp

cp copies files from one place to another.

---

## dd

dd copies a file (from the standard input to the standard output, by default) with a user−selectable blocksize, while optionally performing conversions on it.

---

## df

df displays the amount of disk space available on the filesystem containing each file name argument. If no file name is given, the space available on all currently mounted filesystems is shown.

---

## ls, dir and vdir

dir and vdir are versions of ls with different default output formats. These programs list each given file or directory name. Directory contents are sorted alphabetically. For ls, files are by default listed in columns, sorted vertically, if the standard output is a terminal; otherwise they are listed one per line. For dir, files are by default listed in columns, sorted vertically. For vdir, files are by default listed in long format.

---

## dircolors

dircolors outputs commands to set the LS_COLOR environment variable. The LS_COLOR variable is use to change the default color scheme used by ls and related utilities.

---

## du

du displays the amount of disk space used by each argument and for each subdirectory of directory arguments.

---

## install

install copies files and sets their permission modes and, if possible, their owner and group.

---

## ln

ln makes hard or soft (symbolic) links between files.

---

## mkdir

mkdir creates directories with a given name.

## mkfifo

mkfifo creates a FIFO with each given name.

## mknod

mknod creates a FIFO, character special file, or block special file with the given file name.

## mv

mv moves files from one directory to another or renames files, depending on the arguments given to mv.

## rm

rm removes files or directories.

## rmdir

rmdir removes directories, if they are empty.

## sync

sync forces changed blocks to disk and updates the super block.

## touch

touch changes the access and modification times of each given file to the current time. Files that do not exist are created empty.

# Installing GCC on the normal system if necessary

## Installing GCC on the normal system if necessary

In order to compile Glibc−2.1.3 later on you need to have gcc−2.95.2 installed. Although any GCC version above 2.8 would do, 2.95.2 is the highly recommended version to use. egcs−2.91.x is also known to work. If you don't have gcc−2.95.x or egcs−2.91.x you need to install gcc−2.95.2 on your normal sytem before you can compile Glibc later in this chapter.

To find out which compiler version your systems has, run the following command:

```
root:~#   gcc --version
```

If you normal Linux system does not have gcc−2.95.x or egcs−2.91.x installed you need to install it now. We won't replace the current compiler on your system, but instead we will install gcc in a separate directory (/usr/local/gcc2952). This way no binaries or header files will be replaced.

After you unpacked the gcc−2.95.2 archive don't enter the newly created gcc−2.95.2 directory but stay in the $LFS/usr/src directory. Install GCC by running the following commands:

```
root:src#   mkdir $LFS/usr/src/gcc-build
root:src#   cd $LFS/usr/src/gcc-build
root:gcc-build#   ../gcc-2.95.2/configure \
> --prefix=/usr/local/gcc2952 \
> --with-local-prefix=/usr/local/gcc2952  \
> --with-gxx-include-dir=/usr/local/gcc2952/include/g++  \
> --enable-shared --enable-languages=c,c++
root:gcc-build#   make bootstrap
root:gcc-build#   make install
```

---

## Contents

The GCC package contains compilers, preprocessors and the GNU C++ Library.

---

## Description

## Compiler

A compiler translates source code in text format to a format that a computer understands. After a source code file is compiled into an object file, a linker will create an executable file from one or more of these compiler generated object files.

---

## Pre−processor

A pre−processor pre−processes a source file, such as including the contents of header files into the source file. You generally don't do this yourself to save yourself a lot of time. You just insert a line like #include <filename>. The pre−processor file insert the contents of that file into the source file. That's one of the things a pre−processor does.

---

## C++ Library

The C++ library is used by C++ programs. The C++ library contains functions that are frequently used in C++ programs. This way the programmer doens't have to write certain functions (such as writing a string of text to the screen) from scratch every time he creates a program.

---

# Installing GCC on the LFS system

## Installing GCC on the LFS system

After you unpacked the gcc−2.95.2 archive don't enter the newly created gcc−2.95.2 directory but stay in the $LFS/usr/src directory. Install GCC by running the following commands:

```
root:src#   mkdir $LFS/usr/src/gcc-build
root:src#   cd $LFS/usr/src/gcc-build
root:gcc-build#   ../gcc-2.95.2/configure --prefix=/usr \
> --with-gxx-include-dir=/usr/include/g++ \
> --enable-languages=c,c++ --disable-nls
root:gcc-build#   make -e LDFLAGS=-static bootstrap
root:gcc-build#   make prefix=$LFS/usr
local_prefix=$LFS/usr/local \
> gxx_include_dir=$LFS/usr/include/g++ install
```

---

### Creating necessary symlinks

The system needs a few symlinks to ensure every program is able to find the compiler and the pre−processor. Some programs run the cc program, others run the gcc program. Some programs expect the cpp program in /lib and others expect to find it in /usr/bin. Create those symlinks by running:

```
root:~#   cd $LFS/lib
root:lib#   ln -s ../usr/lib/gcc-lib/<host>/2.95.2/cpp cpp
root:lib#   cd $LFS/usr/lib
root:lib#   ln -s gcc-lib/<host>/2.95.2/cpp cpp
root:lib#   cd $LFS/usr/bin
root:bin#   ln -s gcc cc
```

Replace <host> with the directory where the gcc−2.95.2 files are installed (which is i686−unknown−linux in my case).

---

# Contents

The GCC package contains compilers, preprocessors and the GNU C++ Library.

---

# Description

## Compiler

A compiler translates source code in text format to a format that a computer understands. After a source code file is compiled into an object file, a linker will create an executable file from one or more of these compiler generated object files.

---

## Pre−processor

A pre−processor pre−processes a source file, such as including the contents of header files into the source file. You generally don't do this yourself to save yourself a lot of time. You just insert a line like #include <filename>. The pre−processor file insert the contents of that file into the source file. That's one of the things a pre−processor does.

---

## C++ Library

The C++ library is used by C++ programs. The C++ library contains functions that are frequently used in C++ programs. This way the programmer doens't have to write certain functions (such as writing a string of text to the screen) from scratch every time he creates a program.

---

# Installing Linux Kernel

## Installing Linux Kernel

We won't be compiling a new kernel image yet. We'll do that after we have finished the installation of the basic system software in this chapter. But because certain software need the kernel header files, we're going to unpack the kernel archive now and set it up so that we can compile package that need the kernel.

Create the kernel configuration file by running the following command:

```
root:linux#   yes "" | make config
```

Ignore the warning *Broken pipe* you might see at the end. Now run the following commands to set up all the dependencies correctly:

```
root:linux#   make dep
```

Now that that's done, we need to create the `$LFS/usr/include/linux` and the `$LFS/usr/include/asm` symlinks. Create them by running the following commands:

```
root:~#   cd $LFS/usr/include
root:include#   ln -s ../src/linux/include/linux linux
root:include#   ln -s ../src/linux/include/asm asm
```

---

## Contents

The Linux kernel package contains the Linux kernel.

---

## Description

The Linux kernel is at the core of every Linux system. It's what makes Linux tick. When you turn on your computer and boot a Linux system, the very first piece of Linux software that gets loaded is the kernel. The kernel initializes the system's hardware components such as serial ports, parallel ports, sound cards, network cards, IDE controllers, SCSI controllers and a lot more. In a nutshell the kernel makes the hardware available

so that the software can run.

---

# Installing Glibc

## Contents

The Glibc package contains the GNU C Library.

---

## Description

The C Library is a collection of commonly used functions in programs. This way a programmer doens't need to create his own functions for every single task. The most common things like writing a string to your screen are already present and at the disposal of the programmer.

The C library (actually almost every library) come in two flavours: dynamic ones and static ones. In short when a program uses a static C library, the code from the C library will be copied into the executable file. When a program uses a dynamic library, that executable will not contain the code from the C library, but instead a routine that loads the functions from the library at the time the program is run. This means a significant decrease in the file size of a program. If you don't understand this concept, you better read the documentation that comes with the C Library as it is too complicated to explain here in one or two lines.

---

## A note on the glibc−crypt package

An excerpt from the README file that is distributed with the glibc−crypt package:

The add−on is not included in the main distribution of the GNU C library because some governments, most notably those of France, Russia, and the US, have very restrictive rules governing the distribution and use of encryption software.  Please read the node "Legal Problems" in the manual for more details.

In particular, the US does not allow export of this software without a licence, including via the Internet.  So please do not download it from the main FSF FTP site at ftp.gnu.org if you are outside the US.  This software was completely developed outside the US.

"This software" refers to the glibc−crypt package at ftp://ftp.gwdg.de/pub/linux/glibc/. This law only affects people who don't live in the US. It's not prohibited to import DES software, so if you live in the US you can import the file safely from Germany without breaking cryptographic laws. This law is changing lately and I don't know what the status of it is at the moment. Better be safe than sory.

---

## Installing Glibc

Copy the Glibc−crypt and Glibc−linuxthreads archives into the unpacked glibc directory. Copy the glibc−2.1.3−ctype.patch file to $LFS/usr/src

Unpack the glibc−crypt and glibc−linuxthreads archives there, but don't enter the created directories. Just unpack and leave it with that.

A few default parameters of Glibc need to be changed, such as the directory where the shared libraries are supposed to be installed in and the directory that contains the system configuration files. For this purpose you need to create the `$LFS/usr/src/glibc-build` directory and in that directory you create a new file `configparms` containing:

```
# Begin configparms

slibdir=/lib
sysconfdir=/etc

# End configparms
```

Change to the `$LFS/usr/src/glibc-2.1.3` directory and install Glibc by running the following commands if your system already had a suitable GCC version installed:

```
root:glibc-2.1.3#   patch -p1 < ../glibc-2.1.3-ctype.patch
root:glibc-2.1.3#   cd ../glibc-build
root:glibc-build#   ../glibc-2.1.3/configure --prefix=/usr
--enable-add-ons \
> --with-headers=$LFS/usr/include
root:glibc-build#   make
root:glibc-build#   make install_root=$LFS install
```

If you're getting errors related to illegal character 45 in some variable name during the compilation, apply the Glibc patch.

Install this patch by running the following command:

```
root:glibc-build#    patch -Np1 -i ../glibc-2.1.3.patch
```

Change to the `$LFS/usr/src/glibc-build` directory and install Glibc by running the following command if your system did not already have a suitable GCC version installed and you just installed GCC–2.95.2 on your normal Linux system a little while ago:

```
root:glibc-2.1.3#   patch -p1 < ../glibc-2.1.3-ctype.patch
root:glibc-2.1.3#   cd ../glibc-build
```

```
root:glibc-build#   CC=/usr/local/gcc2952/bin/gcc \
> ../glibc-2.1.3/configure --prefix=/usr  --enable-add-ons \
> --with-headers=$LFS/usr/include
root:glibc-build#   make
root:glibc-build#   make install_root=$LFS install
```

If you're getting errors related to illegal character 45 in some variable name during the compilation, appy the Glibc patch.

Install this patch by running the following command:

```
root:glibc-build#    patch -Np1 -i ../glibc-2.1.3.patch
```

---

## Copying old NSS library files

If your normal Linux system runs glibc–2.0, you need to copy the NSS library files to the LFS partition. Certain statically linked programs still depend on the NSS library, especially programs that need to lookup usernames,userid's and groupid's. You can check which C library version your normal Linux system uses by running:

```
root:~# ls /lib/libc*
```

Your system uses glib–2.0 if there is a file that looks like *libc–2.0.7.so*

Your system uses glibc–2.1 if there is a file that looks like *libc–2.1.3.so*

Of course, the micro version number can be different (you could have libc–2.1.2 or libc–2.1.1 for example).

If you have a libc–2.0.x file copy the NSS library files by running:

```
root:~# cp -av /lib/libnss*  $LFS/lib
```

There are a few distributions that don't have files from which you can see which version of the C Library it is. If that's the case, it will be hard to determine which C library version you exactly have. Try to obtain this information using your distribution's installation tool. It often says which version it has available. If you can't figure out at all which C Library version is used, then copy the NSS files anyway and hope for the best.

That's the best advise I can give I'm afraid.

---

# Installing Grep

## Installing Grep

Install Grep by running the following commands:

```
root:grep-2.4.2#
CPPFLAGS=-Dre_max_failures=re_max_failures2 \
> ./configure --prefix=/usr --disable-nls
root:grep-2.4.2#   make LDFLAGS=-static
root:grep-2.4.2#   make prefix=$LFS/usr install
```

---

## Contents

The grep package contains the egrep, fgrep and grep programs.

---

## Description

### egrep

egrep prints lines from files matching an extended regular expression pattern.

---

### fgrep

fgrep prints lines from files matching a list of fixed strings, separated by newlines, any of which is to be matched.

---

### grep

grep prints lines from files matching a basic regular expression pattern.

---

# Installing Gzip

## Installing Gzip

Install Gzip by running the following commands:

```
root:gzip-1.2.4a#   ./configure --prefix=/usr --disable-nls
root:gzip-1.2.4a#   make LDFLAGS=-static
root:gzip-1.2.4a#   make prefix=$LFS/usr install
root:gzip-1.2.4a#   cd $LFS/usr/bin
root:bin#   cp gunzip gzip $LFS/bin
root:bin#   rm gunzip gzip
```

This package is known to cause compilation problems on certain platforms. If you're having trouble compiling this package as well, you can download a patch from
http://www.linuxfromscratch.org/download/gzip−1.2.4a.patch.gz

Install this patch by running the following command:

```
root:gzip-1.2.4a#   patch −Np1 −i ../gzip−1.2.4a.patch
```

Now recompile the package using the same commands as above.

---

## Contents

The Gzip package contains the gunzip, gzexe, gzip, zcat, zcmp, zdiff, zforece, zgrep, zmore and znew programs.

---

## Description

### gunzip

gunzip decompresses files that are compressed with gzip.

---

## gzexe

gzexe allows you to compress executables in place and have them automatically uncompress and execute when you run them (at a penalty in performance).

---

## gzip

gzip reduces the size of the named files using Lempel−Ziv coding (LZ77).

---

## zcat

zcat uncompresses either a list of files on the command line or its standard input and writes the uncompressed data on standard output

---

## zcmp

zcmp invokes the cmp program on compressed files.

---

## zdiff

zdiff invokes the diff program on compressed files.

---

## zforce

zforce forces a .gz extension on all gzip files so that gzip will not compress them twice. This can be useful for files with names truncated after a file transfer.

---

## zgrep

zgrep invokes the grep program on compressed files.

---

## zmore

Zmore is a filter which allows examination of compressed or plain text files one screenful at a time on a soft−copy terminal (similar to the more program).

---

## znew

Znew recompresses files from .Z (compress) format to .gz (gzip) format.

# Installing Make

## Installing Make

Install Make by running the following commands:

```
root:make-3.79.1#   ./configure --prefix=/usr --disable-nls
root:make-3.79.1#   make LDFLAGS=-static
root:make-3.79.1#   make prefix=$LFS/usr install
```

---

## Contents

The Make package contains the make program.

---

## Description

make determine automatically which pieces of a large program need to be recompiled, and issue the commands to recompile them.

---

# Installing Sed

## Installing Sed

Install Sed by running the following commands:

```
root:sed-3.02#   CPPFLAGS=-Dre_max_failures=re_max_failures2 \
> ./configure --prefix=/usr --disable-nls
root:sed-3.02#   make LDFLAGS=-static
root:sed-3.02#   make prefix=$LFS/usr install
root:sed-3.02#   mv $LFS/usr/bin/sed $LFS/bin
```

---

## Contents

The Sed package contains the sed program.

---

## Description

sed is a stream editor. A stream editor is used to perform basic text transformations on an input stream (a file or input from a pipeline).

---

# Installing Shellutils

## Installing Shellutils

Install Shellutils by running the following commands:

```
root:sh-utils-2.0#   ./configure --prefix=/usr --disable-nls
root:sh-utils-2.0#   make LDFLAGS=-static
root:sh-utils-2.0#   make prefix=$LFS/usr install
root:sh-utils-2.0#   cd $LFS/usr/bin
root:/bin#   mv date echo false pwd stty $LFS/bin
root:bin#   mv su true uname hostname $LFS/bin
```

---

## Contents

The Shellutils package contains the basename, chroot, date, dirname, echo, env, expr, factor, false, groups, hostid, hostname, id, logname, nice, nohup, pathchk, pinky, printenv, printf, pwd, seq, sleep, stty, su, tee, test, true, tty, uname, uptime, users, who, whoami and yes programs.

---

## Description

### basename

basename strips directory and suffixes from filenames.

---

### chroot

chroot runs a command or interactive shell with special root directory.

---

### date

date displays the current time in a specified format, or sets the system date.

---

### dirname

dirname strips non−directory suffixes from file name.

---

## echo

echo displays a line of text.

## env

env runs a program in a modified environment.

## expr

expr evaluates expressions.

## factor

factor prints the prime factors of all specified integer numbers.

## false

false always exits with a status code indicating failure.

## groups

groups prints the groups a user is in.

## hostid

hostid prints the numeric identifier (in hexadecimal) for the current host.

## hostname

hostname sets or prints the name of the current host system

## id

id prints the real and effective UIDs and GIDs of a user or the current user.

## logname

logname prints the current user's login name.

## nice

nice runs a program with modified scheduling priority.

## nohup

nohup runs a command immune to hangups, with output to a non−tty

## pathchk

pathchk checks whether file names are valid or portable.

## pinky

pinky is a lightweight finger utility which retrieves information about a certain user

## printenv

printenv prints all or part of the environment.

## printf

printf formats and print data (the same as the printf C function).

## pwd

pwd prints the name of the current/working directory

## seq

seq prints numbers in a certain range with a certain increment.

## sleep

sleep delays for a specified amount of time.

## stty

stty changes and prints terminal line settings.

## su

su runs a shell with substitute user and group IDs

## tee

tee reads from standard input and write to standard output and files.

## test

test checks file types and compares values.

## true

True always exitx with a status code indicating success.

## tty

tty prints the file name of the terminal connected to standard input.

## uname

uname prints system information.

## uptime

uptime tells how long the system has been running.

## users

users prints the user names of users currently logged in to the  current host.

---

## who

who shows who is logged on.

---

## whoami

whoami prints your effective userid.

---

## yes

yes outputs a string repeatedly until killed.

---

# Installing Tar

## Installing Tar

Install Tar by running the following commands:

```
root:tar-1.13#   ./configure --prefix=/usr --disable-nls
root:tar-1.13#   make LDFLAGS=-static
root:tar-1.13#   make prefix=$LFS/usr install
root:tar-1.13#   mv $LFS/usr/bin/tar $LFS/bin
```

---

## Contents

The tar package contains the tar and rmt programs.

---

## Description

### tar

tar is an archiving program designed to store and extract files from an archive file known as a tarfile.

---

### rmt

rmt is a program used by the remote dump and restore programs in manipulating a magnetic tape drive through an interprocess communication connection.

---

# Installing Textutils

## Installing Textutils

Install Textutils by running the following commands:

```
root:textutils-2.0#   ./configure --prefix=/usr --disable-nls
root:textutils-2.0#   make LDFLAGS=-static
root:textutils-2.0#   make prefix=$LFS/usr install
root:textutils-2.0#   mv $LFS/usr/bin/cat $LFS/bin
```

---

## Contents

The Textutils package contains the cat, cksum, comm, split, cut, expand, fmt, fold, head, join, md5sum, nl, od, paste, pr, ptx, sort, split, sum, tac, tail, tr, tsort, unexpand, uniq and wc programs.

---

## Description

### cat

cat concatenates file(s) or standard input to standard output.

---

### cksum

cksum prints CRC checksum and byte counts of each specified file.

---

### comm

comm compares two sorted files line by line.

---

### csplit

cplit outputs pieces of a file separated by (a) pattern(s) to files xx01, xx02, ..., and outputs byte counts of each piece to standard output.

---

## cut

cut prints selected parts of lines from specified files to standard output.

## expand

expand converts tabs in files to spaces, writing to standard output.

## fmt

fmt reformats each paragraph in the specified file(s), writing to standard output.

## fold

fold wraps input lines in each specified file (standard input by default), writing to standard output.

## head

Print first xx (10 by default) lines of each specified file to standard output.

## join

join joins lines of two files on a common field.

## md5sum

md5sum prints or checks MD5 checksums.

## nl

nl writes each specified file to standard output, with line numbers added.

## od

od writes an unambiguous representation, octal bytes by default, of a specified file to standard output.

## paste

paste writes lines consisting of the sequentially corresponding lines from each specified file, separated by TABs, to standard output.

---

## pr

pr paginates or columnates files for printing.

---

## ptx

ptx produces a permuted index of file contents.

---

## sort

sort writes sorted concatenation of files to standard output.

---

## split

split outputs fixed−size pieces of an input file to PREFIXaa, PREFIXab, ...

---

## sum

sum prints checksum and block counts for each specified file.

---

## tac

tac writes each specified file to standard output, last line first.

---

## tail

tail print the last xx (10 by default) lines of each specified file to standard output.

---

## tr

tr translates, squeezes, and/or deletes characters from standard input, writing to standard output.

---

## tsort

tsort writes totally ordered lists consistent with the partial ordering in specified files.

## unexpand

unexpand converts spaces in each file to tabs, writing to standard output.

## uniq

uniq discards all but one of successive identical lines from files or standard input and writes to files or standard output.

## wc

wc prints line, word, and byte counts for each specified file, and a total line if more than one file is specified.

# Creating passwd and group files

In order for user and group root to be recognized and to be able to logon it needs an entry in the /etc/passwd and /etc/group file. Besides the groupt root a couple of other groups are recommended and needed by packages. The groups with their GID's below aren't part of any standard. The LSB only recommends besides a group root a group bin to be present with GID 1. Other group names and GID's can be chosen by yourself. Well written packages don't depend on GID numbers but just use the group name, it doesn't matter all that much what GID a group has. Since there aren't any standards for groups I won't follow any conventions used by Debian, RedHat and others. The groups added here are the groups the MAKEDEV script (the script that creates the device files in the /dev directory) mentions.

Create a new file `$LFS/etc/passwd` by running the following command:

```
root:~#   echo "root:x:0:0:root:/root:/bin/bash" >
$LFS/etc/passwd
```

Create a new file `$LFS/etc/group` by running the following command:

```
root:~#   echo "root:x:0:" > $LFS/etc/group
root:~#   echo "bin:x:1:" >> $LFS/etc/group
root:~#   echo "sys:x:2:" >> $LFS/etc/group
root:~#   echo "kmem:x:3:" >> $LFS/etc/group
root:~#   echo "tty:x:4:" >> $LFS/etc/group
root:~#   echo "uucp:x:5:" >> $LFS/etc/group
root:~#   echo "daemon:x:6:" >> $LFS/etc/group
root:~#   echo "floppy:x:7:" >> $LFS/etc/group
root:~#   echo "disk:x:8:" >> $LFS/etc/group
```

---

# Copying /proc/devices

In order for the MAKEDEV script properly create device entries in /dev it needs access to /proc/devices. We can't mount the proc file system on our LFS system yet so instead we just copy the /proc/devices file to $LFS/proc. This means the $LFS/proc/devices file won't be updated when the kernel updates /proc/devices but I don't see any harm in doing it, since it's only needed during the execution of the MAKEDEV script. Just make sure you don't add or remove any hardware during the next 3 minutes by loading or unloading a kernel module or rebooting your computer before continuing with this book.

Copy the /proc/devices file by running the following command:

```
root:~#   cp /proc/devices $LFS/proc
```

---

# Installing basic system software

The installation of all the software is pretty straightforward and you'll think it's so much easier and shorter to give the generic installation instructions for each package and only explain how to install something if a certain package requires an alternate installation method. Although I agree with you on that, I, however, choose to give the full instructions for each and every package. This is simply to avoid any possible confusion and errors.

# Entering the chroot'ed environment

It's time to enter our chroot'ed environment in order to install the rest of the software we need.

Enter the following command to enter the chroot'ed environment. From this point on there's no need to use the $LFS variable anymore, because everything you do will be restricted to the LFS partition (since / is actually /mnt/lfs but the shell doesn't know that).

```
root:~#   chroot $LFS bash --login
```

Now that we are inside a chroot'ed environment, we can continue to install all the basic system software. Make sure you execute all the following commands in this chapter from within the chroot'ed environment.

---

# Creating device files

## Installing MAKEDEV

Install MAKEDEV by running the following commands:

```
root:MAKEDEV-2.5#     cp MAKEDEV /dev
root:MAKEDEV-2.5#     chmod 754 /dev/MAKEDEV
root:MAKEDEV-2.5#    sed s/"# 9"/9/ /dev/MAKEDEV >/dev/MAKEDEV2
root:MAKEDEV-2.5#    mv /dev/MAKEDEV2 /dev/MAKEDEV
```

---

## Creating the /dev entries

Create the device files by running the following commands:

```
root:~#     cd /dev
root:dev#     ./MAKEDEV -v generic
```

Now that the device file entries are created the /proc/devices file can be removed by running the following command:

```
root:~#    rm /proc/devices
```

Please note that this script dates back from 1997 and therefore can be outdated and not support newer hardware. If you need device files which aren't known by this script please read the Documentation/devices.txt file in a Linux source tree. This file lists all the major and minor numbers for all the device files that the kernel knows about. With this list you can create such device files yourself. See the mknod man page for more information on how to make device files yourself.

---

# Installing Ed

## Installing Ed

Install Ed by running the following commands:

```
root:ed-0.2#    ./configure --prefix=/usr
root:ed-0.2#    make
root:ed-0.2#    make install
root:ed-0.2#    cd /usr/bin
root:bin#    mv ed red /bin
```

## Contents

The Ed package contains the ed program.

## Description

Ed is a line−oriented text editor.  It is used to create, display, modify and otherwise manipulate text files.

# Installing Patch

## Installing Patch

Install Patch by running the following commands:

```
root:patch-2.5.4#   ./configure --prefix=/usr
root:patch-2.5.4#   make
root:patch-2.5.4#   make install
```

## Contents

The Patch package contains the patch program.

## Description

The patch program modifies a file according to a patch file. A patch file usually is a list created by the diff program that contains instructions on how an original file needs to be modified. Patch is used a lot for source code patches since it saves time and space. Imagine you have a package that is 1MB in size. The next version of that package only has changes in two files of the first version. You can ship an entirely new package of 1MB or provide a patch file of 1KB which will update the first version to make it identical to the second version. So if you have downloaded the first version already, a patch file can save you a second large download.

# Installing GCC

## Installing GCC

After you unpacked the gcc−2.95.2 archive don't enter the newly created gcc−2.95.2 directory but stay in the /usr/src directory. Install GCC by running the following commands:

```
root:src#   mkdir /usr/src/gcc-build
root:src#   cd /usr/src/gcc-build
root:gcc-build#   ../gcc-2.95.2/configure --prefix=/usr \
> --with-gxx-include-dir=/usr/include/g++ \
> --enable-shared --enable-languages=c,c++
root:gcc-build#   make bootstrap
root:gcc-build#   make install
```

---

## Contents

The GCC package contains compilers, preprocessors and the GNU C++ Library.

---

## Description

### Compiler

A compiler translates source code in text format to a format that a computer understands. After a source code file is compiled into an object file, a linker will create an executable file from one or more of these compiler generated object files.

---

### Pre−processor

A pre−processor pre−processes a source file, such as including the contents of header files into the source file. You generally don't do this yourself to save yourself a lot of time. You just insert a line like #include <filename>. The pre−processor file insert the contents of that file into the source file. That's one of the things a pre−processor does.

---

### C++ Library

The C++ library is used by C++ programs. The C++ library contains functions that are frequently used in C++ programs. This way the programmer doens't have to write certain functions (such as writing a string of text to the screen) from scratch every time he creates a program.

# Installing Bison

## Installing Bison

Install Bison by running the following commands:

```
root:bison-1.28#    ./configure --prefix=/usr \
> --datadir=/usr/share/bison
root:bison-1.28#    make
root:bison-1.28#    make install
```

---

## Contents

The Bison package contains the bison program.

---

## Description

Bison is a parser generator, a replacement for YACC. YACC stands for Yet Another Compiler Compiler. What is Bison then? It is a program that generates a program that analyses the structure of a textfile. Instead of writing the actual program you specify how things should be connected and with those rules a program is constructed that analyses the textfile.

There are alot of examples where structure is needed and one of them is the calculator.

Given the string :

```
1 + 2 * 3
```

You can easily come to the result 7. Why ? Because of the structure. You know how to interpretet the string. The computer doesn't know that and Bison is a tool to help it understand by presenting the string in the following way to the compiler:

```
  +
 / \
1   *
   / \
  2   3
```

You start at the bottom of a tree and you come across the numbers 2 and 3 which are joined by the multiplication symbol, so the computers multiplies 2 and 3. The result of that multiplication is remembered and the next thing that the computer sees is the result of 2*3 and the number 1 which are joined by the add symbol. Adding 1 to the previous result makes 7. In calculating the most complex calculations can be broken down in this tree format and the computer just starts at the bottom and works it's way up to the top and comes with the correct answer. Of course, Bison isn't only used for calculators alone.

---

# Installing Mawk

## Installing Mawk

Install Mawk by running the following commands:

```
root:mawk-1.3.3#    ./configure
root:mawk-1.3.3#    make
root:mawk-1.3.3#    make BINDIR=/usr/bin
MANDIR=/usr/share/man/man1 install
root:mawk-1.3.3#    cd /usr/bin
root:bin#    ln -s mawk awk
```

---

## Contents

The Mawk package contains the mawk program.

---

## Description

### gawk

Mawk is an interpreter for the AWK Programming Language. The AWK language is useful for manipulation of data files, text retrieval and processing, and for prototyping and experimenting with algorithms.

---

# Installing Findutils

## Installing Findutils

Install Findutils by running the following commands:

```
root:findutils-4.1#    ./configure --prefix=/usr
root:findutils-4.1#    make
root:findutils-4.1#    make install
```

This package is known to cause compilation problem. If you're having trouble compiling this package as well, apply the Findutils patch.

Install this patch by running the following command:

```
root:findutils-4.1#    patch -Np1 -i ../findutils-4.1.patch
```

Now recompile the package using the same commands as above.

---

## Contents

The Findutils package contains the find, locate, updatedb and xargs programs.

---

## Description

### Find

The find program searches for files in a directory hierarchy which match a certain criteria. If no criteria is given, it lists all files in the current directory and it's subdirectories.

---

### Locate

Locate scans a database which contain all files and directories on a filesystem. This program lists the files and directories in this database matching a certain criteria. If you're looking for a file this program will scan the database and tell you exactly where the files you requested are located. This only makes sense if your locate database is fairly up−to−date else it will provide you with out−of−date information.

## Updatedb

The updatedb program updates the locate database. It scans the entire file system (including other file system that are currently mounted unless you specify it not to) and puts every directory and file it finds into the database that's used by the locate program which retrieves this information. It's a good practice to update this database once a day so that you are ensured of a database that is up−to−date.

## Xargs

The xargs command applies a command to a list of files. If you need to perform the same command on multiple files, you can create a file that contains all these files (one per line) and use xargs to perform that command on the list.

# Installing Ncurses

## Installing Ncurses

Install Ncurses by running the following commands:

```
root:ncurses-4.2#   ./configure --prefix=/usr --with-shared
root:ncurses-4.2#   make
root:ncurses-4.2#   make install
```

---

## Contents

The Ncurses package contains the ncurses, panel, menu and form libraries. It also contains the tic, infocmp, clear, tput, toe and tset programs.

---

## Description

### The libraries

The libraries that make up the Ncurses library are used to display text (often in a fancy way) on your screen. An example where ncurses is used is in the kernel's "make menuconfig" process. The libraries contain routines to create panels, menu's, form and general text display routines.

---

### Tic

Tic is the terminfo entry-description compiler. The program translates a terminfo file from source format into the binary format for use with the ncurses library routines. Terminfo files contain information about the capabilities of your terminal.

---

### Infocmp

The infocmp program can be used to compare a binary terminfo entry with other terminfo entries, rewrite a terminfo description to take advantage of the use= terminfo field, or print out a terminfo description from the binary file (term) in a variety of formats (the opposite of what tic does).

---

## clear

The clear program clears your screen if this is possible. It looks in the environment for the terminal type and then in the terminfo database to figure out how to clear the screen.

---

## tput

The tput program uses the terminfo database to make the values of terminal−dependent capabilities and information available to the shell, to initialize or reset the terminal, or return the long name of the requested terminal type.

---

## toe

The toe program lists all available terminal types by primary name with descriptions.

---

## tset

The Tset program initializes terminals so they can be used, but it's not widely used anymore. It's provided for 4.4BSD compatibility.

---

# Installing Less

## Installing Less

Install Less by running the following commands:

```
root:less-358#   ./configure --prefix=/usr
root:less-358#   make
root:less-358#   make install
root:less-358#   mv /usr/bin/less /bin
```

---

## Contents

The Less package contains the less program

---

## Description

The less program is a file pager (or text viewer). It displays the contents of a file with the ability to scroll. Less is an improvement on the common pager called "more". Less has the ability to scroll backwards through files as well and it doesn't need to read the entire file when it starts, which makes it faster when you are reading large files.

---

# Installing Groff

## Installing Groff

Install Groff by running the following commands:

```
root:groff-1.16#    ./configure --prefix=/usr
root:groff-1.16#    make
root:groff-1.16#    make install
```

---

## Contents

The Groff packages contains the addftinfo, afmtodit, eqn, grodvi, groff, grog, grohtml, grolj4, grops, grotty, hpftodit, indxbib, lkbib, lookbib, neqn, nroff, pfbtops, pic, psbb, refer, soelim, tbl, tfmtodit and troff programs.

---

## Description

### addftinfo

addftinfo reads a troff font file and adds some additional font−metric information that is used by the groff system.

---

### afmtodit

afmtodit creates a font file for use with groff and grops.

---

### eqn

eqn compiles descriptions of equations embedded within troff input files into commands that are understood by troff.

---

### grodvi

grodvi is a driver for groff that produces TeX dvi format.

---

## groff

groff is a front−end to the groff document formatting system. Normally it runs the troff program and a postprocessor appropriate for the selected device.

## grog

grog reads files and guesses which of the groff options −e, −man, −me, −mm, −ms, −p, −s, and −t are required for printing files, and prints the groff command including those options on the standard output.

## grohtml

grohtml translates the output of GNU troff to html

## grolj4

grolj4 is a driver for groff that produces output in PCL5 format suitable for an HP Laserjet 4 printer.

## grops

grops translates the output of GNU troff to PostScript.

## grotty

grotty translates the output of GNU troff into a form suitable for typewriter−like devices.

## hpftodit

hpftodit creates a font file for use with groff −Tlj4 from an HP tagged font metric file.

## indxbib

indxbib makes an inverted index for the bibliographic databases a specified file for use with refer, lookbib, and lkbib.

## lkbib

lkbib searches bibliographic databases for references that contain specified keys and prints any references found on the standard output.

## lookbib

lookbib prints a prompt on the standard error (unless the standard input is not a terminal), reads from the standard input a line containing a set of keywords, searches the bibliographic databases in a specified file for references containing those keywords, prints any references found on the standard output, and repeats this process until the end of input.

## neqn

It is currently not known what neqn is and what it does.

## nroff

The nroff script emulates the nroff command using groff.

## pfbtops

pfbtops translates a PostScript font in .pfb format to ASCII.

## pic

pic compiles descriptions of pictures embedded within troff or TeX input files into commands that are understood by TeX or troff.

## psbb

psbb reads a file which should be a PostScript document conforming to the Document Structuring conventions and looks for a %%BoundingBox comment.

## refer

refer copies the contents of a file to the standard output, except that lines between .[ and .] are interpreted as citations, and lines between .R1 and .R2 are interpreted as commands about how citations are to be processed.

## soelim

soelim reads files and replaces lines of the form *.so file* by the contents of *file*.

## tbl

tbl compiles descriptions of tables embedded within troff input files into commands that are understood by troff.

---

## tfmtodit

tfmtodit creates a font file for use with **`groff -Tdvi`**

---

## troff

troff is highly compatible with Unix troff. Usually it should be invoked using the groff command, which will also run preprocessors and postprocessors in the appropriate order and with the appropriate options.

---

# Installing Man

## Installing Man

Install Man by running the following commands:

```
root:man-1.5h1#    ./configure -default
root:man-1.5h1#    make
root:man-1.5h1#    make install
```

---

## Contents

The Man package contains the man, apropos whatis and makewhatis programs.

---

## Description

### man

man formats and displays the on-line manual pages.

---

### apropos

apropos searches a set of database files containing short descriptions of system commands for keywords and displays the result on the standard output.

---

### whatis

whatis searches a set of database files containing short descriptions of system commands for keywords and displays the result on the standard output. Only complete word matches are displayed.

---

### makewhatis

makewhatis reads all the manual pages contained in given sections of manpath or the preformatted pages contained in the given sections of catpath. For each page, it writes a line in the whatis database; each line consists of the name of the page and a short description, separated by a dash. The description is extracted using the content of the NAME section of the manual page.

---

# Installing Perl

## Installing Perl

Install Perl by running the following commands:

```
root:perl-5.6.0#   ./Configure -Dprefix=/usr
root:perl-5.6.0#   make
root:perl-5.6.0#   make test
root:perl-5.6.0#   make install
```

If you don't want to answer all those questions Perl asks you, you can add the –d option to the configure script and Perl will use all the default settings.

Also note that a few tests during the make test phase will fail for various reasons. One being there's not network support yet and a few packages haven't been installed yet. It's ok if not every test succeeds. If there are between 5 and 10 failed tests you're just fine. You might want to reinstall perl after you're done with chapter 7.

---

## Contents

The Perl package contains Perl – Practical Extraction and Report Language

---

## Description

Perl combines the features and capabilities of C, awk, sed and sh into one powerful programming language.

---

# Installing M4

## Installing M4

Install M4 by running the following commands:

```
root:m4-1.4#    ./configure --prefix=/usr
root:m4-1.4#    make
root:m4-1.4#    make install
```

---

## Contents

The M4 package contains the M4 processor

---

## Description

M4 is a macro processor. It copies input to output expanding macros as it goes. Macros are either builtin or user-defined and can take any number of arguments. Besides just doing macro expansion m4 has builtin functions for including named files, running UNIX commands, doing integer arithmetic, manipulating text in various ways, recursion, etc. M4 can be used either as a front-end to a compiler or as a macro processor in its own right.

---

# Installing Texinfo

## Installing Texinfo

Install Texinfo by running the following commands:

```
root:texinfo-4.0#   ./configure --prefix=/usr
root:texinfo-4.0#   make
root:texinfo-4.0#   make install
```

---

## Contents

The Texinfo package contains the info, install−info, makeinfo, texi2dvi and texindex programs

---

## Description

### info

The info program reads Info documents, usually contained in your /usr/doc/info directory. Info documents are like man(ual) pages, but they tend to be more in depth than just explaining the options to a program.

---

### install−info

The install−info program updates the info entries. When you run the info program a list with available topics (ie: available info documents) will be presented. The install−info program is used to maintain this list of available topics. If you decice to remove info files manually, you need to delete the topic in the index file as well. This program is used for that. It also works the other way around when you add info documents.

---

### makeinfo

The makeinfo program translates Texinfo source documents into various formats. Available formats are: info files, plain text and HTML.

---

### texi2dvi

The texi2dvi program prints Texinfo documents

---

## texindex

The texindex program is used to sort Texinfo index files.

# Installing Autoconf

## Installing Autoconf

Install Autoconf by running the following commands:

```
root:autoconf-2.13#    ./configure --prefix=/usr
root:autoconf-2.13#    make
root:autoconf-2.13#    make install
```

---

## Contents

The Autoconf package contains the autoconf, autoheader, autoreconf, autoscan, autoupdate and ifnames programs

---

## Description

### autoconf

Autoconf is a tool for producing shell scripts that automatically configure software source code packages to adapt to many kinds of UNIX-like systems. The configuration scripts produced by Autoconf are independent of Autoconf when they are run, so their users do not need to have Autoconf.

---

### autoheader

The autoheader program can create a template file of C #define statements for configure to use

---

### autoreconf

If you have a lot of Autoconf-generated configure scripts, the autoreconf program can save you some work. It runs autoconf (and autoheader, where appropriate) repeatedly to remake the Autoconf configure scripts and configuration header templates in the directory tree rooted at the current directory.

---

### autoscan

The autoscan program can help you create a configure.in file for a software package. autoscan examines source files in the directory tree rooted at a directory given as a command line argument, or the current

directory if none is given.  It searches the source files for common portability problems and creates a file configure.scan which is a preliminary configure.in for that package.

## autoupdate

The autoupdate program updates a configure.in file that calls Autoconf macros by their old names to use the current macro names.

## ifnames

ifnames can help when writing a configure.in for a software package. It prints the identifiers that the package already uses in C preprocessor conditionals. If a package has already been set up to have some portability, this program can help you figure out what its configure needs to check for. It may help fill in some gaps in a configure.in generated by autoscan.

# Installing Automake

## Installing Automake

Install Automake by running the following commands:

```
root:automake-1.4#    ./configure --prefix=/usr
root:automake-1.4#    make install
```

---

## Contents

The Automake package contains the aclocal and automake programs

---

## Description

### aclocal

Automake includes a number of Autoconf macros which can be used in your package; some of them are actually required by Automake in certain situations. These macros must be defined in your aclocal.m4; otherwise they will not be seen by autoconf.

The aclocal program will automatically generate aclocal.m4 files based on the contents of configure.in. This provides a convenient way to get Automake−provided macros, without having to search around. Also, the aclocal mechanism is extensible for use by other packages.

---

### automake

To create all the Makefile.in's for a package, run the automake program in the top level directory, with no arguments. automake will automatically find each appropriate Makefile.am (by scanning configure.in) and generate the corresponding Makefile.in.

---

# Installing Bash

## Installing Bash

Install Bash by running the following commands:

```
root:bash-2.04#   ./configure --prefix=/usr --with-ncurses
root:bash-2.04#   make
root:bash-2.04#   make install
root:bash-2.04#   logout
root:~#   cd $LFS/usr/bin
root:~#   mv bash bashbug $LFS/bin
root:~#   chroot $LFS bash --login
```

---

## Contents

The Bash package contains the bash program

---

## Description

Bash is the Bourne-Again SHell, which is a widely used command interpreter on Unix systems. Bash is a program that reads from standard input, the keyboard. You type something and the program will evaluate what you have typed and do something with it, like running a program.

---

# Installing Flex

## Installing Flex

Install Flex by running the following commands:

```
root:flex-2.5.4a#   ./configure --prefix=/usr
root:flex-2.5.4a#   make
root:flex-2.5.4a#   make install
```

---

## Contents

The Flex package contains the flex program

---

## Description

Flex is a tool for generating programs which regognize patterns in text. Pattern recognition is very useful in many applications. You set up rules what to look for and flex will make a program that looks for those patterns. The reason people use flex is that it is much easier to set up rules for what to look for than to write the actual program that finds the text.

---

# Installing File

## Installing File

Install File by running the following commands:

```
root:file-3.31#    ./configure --prefix=/usr
--datadir=/usr/share/misc
root:file-3.31#    make
root:file-3.31#    make install
```

---

## Contents

The File package contains the file program.

---

## Description

File tests each specified file in an attempt to classify it. There are three sets of tests, performed in this order: filesystem tests, magic number tests, and language tests. The first test that succeeds causes the file type to be printed.

---

# Installing Gettext

## Installing Gettext

Install Gettext by running the following commands:

```
root:gettext-0.10.35#   ./configure --prefix=/usr
root:gettext-0.10.35#   make
root:gettext-0.10.35#   make install
```

---

## Contents

The gettext package contains the gettext, gettextize, msgcmp, msgcomm, msgfmt, msgmerge, msgunfmt and xgettext programs.

---

## Description

### gettext

The gettext package is used for internationalization (also known as i18n) and for localization (also known as l10n). Programs can be compiled with Native Language Support (NLS) which enable them to output messages in your native language rather than in the default English languge.

---

# Installing Libtool

## Installing Libtool

Install Libtool by running the following commands:

```
root:libtool-1.3.5#   ./configure --prefix=/usr
root:libtool-1.3.5#   make
root:libtool-1.3.5#   make install
```

## Contents

The Libtool package contains the libtool and libtoolize programs. It also contains the ltdl library.

## Description

### libtool

Libtool provides generalized library−building support services.

### libtoolize

libtoolize provides a standard way to add libtool support to your  package.

### ltdl library

Libtool provides a small library, called `libltdl', that aims at hiding  the various difficulties of dlopening libraries from programmers.

# Installing Consoletools

## Installing Console−tools

Before you start installing Console−tools you have to unpack the console−tools−0.2.3.patch file.

Install Console−tools by running the following commands:

```
root:console-tools-0.2.3#   patch -Np1 -i
../console-tools-0.2.3.patch
root:console-tools-0.2.3#   ./configure --prefix=/usr
root:console-tools-0.2.3#   make
root:console-tools-0.2.3#   make install
```

---

## Contents

The Console−tools package contains the charset, chvt, consolechars, deallocvt, dumpkeys, fgconsole, fix_bs_and_del, font2psf, getkeycodes, kbd_mode, loadkeys, loadunimap, mapscrn, mk_modmap, openvt, psfaddtable, psfgettable, psfstriptable, resizecons, saveunimap, screendump, setfont, setkeycodes, setleds, setmetamode, setvesablank, showcfont, showkey, splitfont, unicode_start, unicode_stop, vcstime, vt−is−URF8, writevt

---

## Description

### charset

charset sets an ACM for use in one of the G0/G1 charsets slots.

---

### chvt

chvt changes foreground virtual terminal.

---

### codepage

No description available.

---

## consolechars

consolechars loads EGA/VGA console screen fonts, screen font maps and/or application−charset maps.

## deallocvt

deallocvt deallocates unused virtual terminals.

## dumpkeys

dumpkeys dumps keyboard translation tables.

## fgconsole

fgconsole prints the number of the active virtual terminal.

## fix_bs_and_del

No description available.

## font2psf

No description available.

## getkeycodes

getkeycodes prints the kernel scancode−to−keycode mapping table.

## kbd_mode

kbd_mode reports or sets the keyboard mode.

## loadkeys

loadkeys loads keyboard translation tables.

## loadunimap

No description available.

## mapscrn

No description available.

## mk_modmap

No description available.

## openvt

openvt starts a program on a new virtual terminal.

## psfaddtable

psfaddtable adds a Unicode character table to a console font.

## psfgettable

psfgettable extracts the embedded Unicode character table from a console font.

## psfstriptable

psfstriptable removes the embedded Unicode character table from a console font.

## resizecons

resizecons changes the kernel idea of the console size.

## saveunimap

No description available.

## screendump

No description available.

## setfont

No description available.

## setkeycodes

setkeycodes loads kernel scancode−to−keycode mapping table entries.

## setleds

setleds sets the keyboard leds.

## setmetamode

setmetamode defines the keyboard meta key handling.

## setvesablank

No description available.

## showcfont

showcfont displays all character in the current screenfont.

## showkey

showkey examines the scancodes and keycodes sent by the keyboard.

## splitfont

No description available.

## unicode_start

unicode_start puts the console in Unicode mode.

## unicode_end

No description available.

## vcstime

No description available.

## vt−is−UTF8

vt−is−UTF8 checks whether the current virtual terminal is in UTF8− or byte−mode.

## writevt

No description available.

# Installing Consoledata

## Installing Console–data

Install Console–data by running the following commands:

```
root:console-data-1999.08.29#   ./configure --prefix=/usr
root:console-data-1999.08.29#   make
root:console-data-1999.08.29#   make install
```

## Contents

The console–data package contains the data files that are used and needed by the console–tools package.

# Installing Binutils

## Installing Binutils

Install Binutils by running the following commands:

```
root:binutils-2.10#    ./configure --prefix=/usr
root:binutils-2.10#    make -e tooldir=/usr
root:binutils-2.10#    make -e tooldir=/usr install
```

---

## Description

The Binutils package contains the ld, as, ar, nm, objcopy, objdump, ranlib, size, strings, strip, c++filt, addr2line and nlmconv programs

---

## Description

### ld

ld combines a number of object and archive files, relocates their data and ties up symbol references. Often the last step in building a new compiled program to run is a call to ld.

---

### as

as is primarily intended to assemble the output of the GNU C compiler gcc for use by the linker ld.

---

### ar

The ar program creates, modifies, and extracts from archives. An archive is a single file holding a collection of other files in a structure that makes it possible to retrieve the original individual files (called members of the archive).

---

### nm

nm lists the symbols from object files.

---

## objcopy

objcopy utility copies the contents of an object file to another. objcopy uses the GNU BFD Library to read and write the object files. It can write the destination object file in a format different from that of the source object file.

---

## objdump

objdump displays information about one or more object files. The options control what particular information to display. This information is mostly useful to programmers who are working on the compilation tools, as opposed to programmers who just want their program to compile and work.

---

## ranlib

ranlib generates an index to the contents of an archive, and stores it in the archive. The index lists each symbol defined by a member of an archive that is a relocatable object file.

---

## size

size lists the section sizes −−and the total size−− for each of the object files objfile in its argument list. By default, one line of output is generated for each object file or each module in an archive.

---

## strings

For each file given, strings prints the printable character sequences that are at least 4 characters long (or the number specified with an option to the program) and are followed by an unprintable character. By default, it only prints the strings from the initialized and loaded sections of object files; for other types of files, it prints the strings from the whole file.

strings is mainly useful for determining the contents of non−text files.

---

## strip

strip discards all or specific symbols from object files. The list of object files may include archives. At least one object file must be given. strip modifies the files named in its argument, rather than writing modified copies under different names.

---

## c++filt

The C++ language provides function overloading, which means that you can write many functions with the same name (providing each takes parameters of different types). All C++ function names are encoded into a low−level assembly label (this process is known as mangling). The c++filt program does the inverse

mapping: it decodes (demangles) low−level names into user−level names so that the linker can keep these overloaded functions from clashing.

## addr2line

addr2line translates program addresses into file names and line numbers. Given an address and an executable, it uses the debugging information in the executable to figure out which file name and line number are associated with a given address.

## nlmconv

nlmconv converts relocatable object files into the NetWare Loadable Module files, optionally reading header files for NLM header information.

# Installing Bzip2

## Installing Bzip2

Install Bzip2 by running the following commands:

```
root:bzip2-1.0.1#   make -f Makefile-libbz2_so
root:bzip2-1.0.1#   make bzip2recover libbz2.a
root:bzip2-1.0.1#   cp bzip2-shared /bin/bzip2
root:bzip2-1.0.1#   cp bzip2recover /bin
root:bzip2-1.0.1#   cp bzip2.1 /usr/share/man/man1
root:bzip2-1.0.1#   cp bzlib.h /usr/include
root:bzip2-1.0.1#   cp -a libbz2.so* libbz2.a /lib
root:bzip2-1.0.1#   rm /usr/lib/libbz2.a
root:bzip2-1.0.1#   cd /bin
root:bin#   rm bunzip2 && ln -s bzip2 bunzip2
root:bin#   rm bzcat && ln -s bzip2 bzcat
```

Although it's not strictly a part of a basic LFS system it's worth mentioning that you can donwload a patch for Tar which enables the tar program to compress and uncompress using bzip2/bunzip2 easily. With a plain tar you'll have to use constructions like bzcat file.tar.bz|tar xv or tar --use-compress-prog=bunzip2 -xvf file.tar.bz2 to use bzip2 and bunzip2 with tar. This patch gives you the -y option so you can unpack a Bzip2 archive with tar xvfy file.tar.bz2. Applying this patch will be mentioned later on when you re-install the Tar package.

---

## Contents

The Bzip2 packages contains the bzip2, bunzip2, bzcat and bzip2recover programs.

---

## Description

### Bzip2

bzip2 compresses files using the Burrows-Wheeler block sorting text compression algorithm, and Huffman coding. Compression is generally considerably better than that achieved by more conventional LZ77/LZ78-based compressors, and approaches the performance of the PPM family of statistical compressors.

---

## Bunzip2

Bunzip2 decompresses files that are compressed with bzip2.

## bzcat

bzcat (or bzip2 −dc) decompresses all specified files to the standard output.

## bzip2recover

bzip2recover recovers data from damaged bzip2 files.

# Installing Diffutils

## Installing Diffutils

Install Diffutils by running the following commands:

```
root:diffutils-2.7#    ./configure --prefix=/usr
root:diffutils-2.7#    make
root:diffutils-2.7#    make install
```

---

## Contents

The Diffutils packagec contains the cmp, diff, diff3 and sdiff programs.

---

## Description

### cmp and diff

cmp and diff both compare two files and report their differences. Both programs have extra options which compare files in different situations.

---

### diff3

The difference between diff and diff3 is that diff comprares 2 files, diff3 compares 3 files.

---

### sdiff

sdiff merges two two files and interactively outputs the results.

---

# Installing E2fsprogs

## Installing E2fsprogs

Install E2fsprogs by running the following commands:

```
root:e2fsprogs-1.18#    ./configure --prefix=/usr
--with-root-prefix=/ \
> --enable-elf-shlibs
root:e2fsprogs-1.18#    make
root:e2fsprogs-1.18#    make install
```

---

## Contents

The e2fsprogs package contains the chattr, lsattr, uuidgen, badblocks, debugfs, dumpe2fs, e2fsck, e2label, fsck, fsck.ext2, mke2fs, mkfs.ext2, mklost+found and tune2fs programs.

---

## Description

### chattr

chattr changes the file attributes on a Linux second extended file system.

---

### lsattr

lsattr lists the file attributes on a second extended file system.

---

### uuidgen

The uuidgen program creates a new universally unique identifier (UUID) using the libuuid library. The new UUID can reasonably be considered unique among all UUIDs created on the local system, and among UUIDs created on other systems in the past and in the future.

---

### badblocks

badblocks is used to search for bad blocks on a device (usually a disk partition).

---

## debugfs

The debugfs program is a file system debugger. It can be used to examine and change the state of an ext2 file system.

---

## dumpe2fs

dumpe2fs prints the super block and blocks group information for the filesystem present on a specified device.

---

## e2fsck and fsck.ext2

e2fsck is used to check a Linux second extended file system. fsck.ext2 does the same as e2fsck.

---

## e2label

e2label will display or change the filesystem label on the ext2 filesystem located on the specified device.

---

## fsck

fsck is used to check and optionally repair a Linux file system.

---

## mke2fs and mkfs.ext2

mke2fs is used to create a Linux second extended file system on a device (usually a disk partition). mkfs.ext2 does the same as mke2fs.

---

## mklost+found

mklost+found is used to create a lost+found directory in the current working directory on a Linux second extended file system. mklost+found pre−allocates disk blocks to the directory to make it usable by e2fsck.

---

## tune2fs

tune2fs adjusts tunable filesystem parameters on a Linux second extended filesystem.

---

# Installing Fileutils

## Installing Fileutils

Install Fileutils by running the following commands:

```
root:fileutils-4.0#    ./configure --prefix=/usr
root:fileutils-4.0#    make
root:fileutils-4.0#    make install
root:fileutils-4.0#    cd /usr/bin
root:bin#    mv chgrp chmod chown cp dd df dir /bin
root:bin#    mv dircolors du install ln ls mkdir mkfifo /bin
root:bin#    mv mknod rm rmdir sync touch vdir /bin
root:bin#    cp mv /bin && rm mv
```

---

## Contents

The Fileutils package contains the chgrp, chmod, chown, cp, dd, df, dir, dircolors, du, install, ln, ls, mkdir, mkfifo, mknod, mv, rm, rmdir, sync, touch and vdir programs.

---

## Description

### chgrp

chgrp changes the group ownership of each given file to the named group, which can be either a group name or a numeric group ID.

---

### chmod

chmod changes the permissions of each given file according to mode, which can be either a symbolic representation of changes to make, or an octal number representing the bit pattern for the new permissions.

---

### chown

chown changes the user and/or group ownership of each given file.

---

## cp

cp copies files from one place to another.

---

## dd

dd copies a file (from the standard input to the standard output, by default) with a user−selectable blocksize, while optionally performing conversions on it.

---

## df

df displays the amount of disk space available on the filesystem containing each file name argument. If no file name is given, the space available on all currently mounted filesystems is shown.

---

## ls, dir and vdir

dir and vdir are versions of ls with different default output formats. These programs list each given file or directory name. Directory contents are sorted alphabetically. For ls, files are by default listed in columns, sorted vertically, if the standard output is a terminal; otherwise they are listed one per line. For dir, files are by default listed in columns, sorted vertically. For vdir, files are by default listed in long format.

---

## dircolors

dircolors outputs commands to set the LS_COLOR environment variable. The LS_COLOR variable is use to change the default color scheme used by ls and related utilities.

---

## du

du displays the amount of disk space used by each argument and for each subdirectory of directory arguments.

---

## install

install copies files and sets their permission modes and, if possible, their owner and group.

---

## ln

ln makes hard or soft (symbolic) links between files.

---

## mkdir

mkdir creates directories with a given name.

## mkfifo

mkfifo creates a FIFO with each given name.

## mknod

mknod creates a FIFO, character special file, or block special file with the given file name.

## mv

mv moves files from one directory to another or renames files, depending on the arguments given to mv.

## rm

rm removes files or directories.

## rmdir

rmdir removes directories, if they are empty.

## sync

sync forces changed blocks to disk and updates the super block.

## touch

touch changes the access and modification times of each given file to the current time. Files that do not exist are created empty.

# Installing Grep

## Installing Grep

Install Grep by running the following commands:

```
root:grep-2.4.2#   ./configure --prefix=/usr
root:grep-2.4.2#   make
root:grep-2.4.2#   make install
```

---

## Contents

The grep package contains the egrep, fgrep and grep programs.

---

## Description

### egrep

egrep prints lines from files matching an extended regular expression pattern.

---

### fgrep

fgrep prints lines from files matching a list of fixed strings, separated by newlines, any of which is to be matched.

---

### grep

grep prints lines from files matching a basic regular expression pattern.

---

# Installing Gzip

## Installing Gzip

Install Gzip by running the following commands:

```
root:gzip-1.2.4a#   ./configure --prefix=/usr
root:gzip-1.2.4a#   make
root:gzip-1.2.4a#   make install
root:gzip-1.2.4a#   cd /usr/bin
root:bin#    cp gunzip gzip /bin
root:bin#   rm gunzip gzip
```

---

## Contents

The Gzip package contains the gunzip, gzexe, gzip, zcat, zcmp, zdiff, zforece, zgrep, zmore and znew programs.

---

## Description

### gunzip

gunzip decompresses files that are compressed with gzip.

---

### gzexe

gzexe allows you to compress executables in place and have them automatically uncompress and execute when you run them (at a penalty in performance).

---

### gzip

gzip reduces the size of the named files using Lempel–Ziv coding (LZ77).

---

### zcat

zcat uncompresses either a list of files on the command line or its standard input and writes the uncompressed data on standard output

## zcmp

zcmp invokes the cmp program on compressed files.

## zdiff

zdiff invokes the diff program on compressed files.

## zforce

zforce forces a .gz extension on all gzip files so that gzip will not compress them twice. This can be useful for files with names truncated after a file transfer.

## zgrep

zgrep invokes the grep program on compressed files.

## zmore

Zmore is a filter which allows examination of compressed or plain text files one screenful at a time on a soft−copy terminal (similar to the more program).

## znew

Znew recompresses files from .Z (compress) format to .gz (gzip) format.

# Installing Ldso

## Installing Ld.so

Install Ld.so by running the following commands:

```
root:ld.so-1.9.9#   cd util
root:util#   make ldd ldconfig
root:util#   cp ldd /bin
root:util#   cp ldconfig /sbin
root:util#   cd ../man
root:man#   cp ldd.1 /usr/share/man/man1
root:man#   cp *.8 /usr/share/man/man8
root:man#   rm /usr/bin/ldd
root:man#   hash -r
```

The "hash –r" command is to make bash forget about the locations of previously executed commands. If you have executed ldd before, bash expects it to be found in /usr/bin. Since we moved it to /bin, the cache needs to be purged so bash can find it in /bin when you want to execute it again.

You might have noticed that we don't use the compiler optimizations for this package. The reason is that overriding the CFLAGS variable causes compilation problems. You would have to edit the Config.mk file and add the proper values to the CFLAGS variable and then compile the package. If you want to do that it's up to you. I don't think it's worth the trouble though. The ld and ldd programs usually are only rarely used.

---

## Contents

From the Ld.so package we're using the ldconfig and ldd programs.

---

## Description

### ldconfig

ldconfig creates the necessary links and cache (for use by the run–time linker, ld.so) to the most recent shared libraries found in the directories specified on the command line, in the file /etc/ld.so.conf, and in the trusted directories (/usr/lib and /lib). ldconfig checks the header and file names of the libraries it encounters when determining which versions should have their links updated.

---

## ldd

ldd prints the shared libraries required by each program or shared library  specified on the command line.

# Installing Bin86

## Installing Bin86

Install Linux86 by running the following commands:

```
root:bin86#     make
root:bin86#    make PREFIX=/usr install
```

---

## Contents

The Bin86 contains the as86, as86_encap, ld86, objdump86, nm86 and size86 programs.

---

## Description

### as86

as86 is an assembler for the 8086...80386 processors.

---

### as86_encap

as86_encap is a shell script to call as86 and convert the created binary into a C file prog.v to be included in or linked with programs like boot block installers.

---

### ld86

ld86 understands only the object files produced by the as86 assembler, it can link them into either an impure or a separate I&D executable.

---

### objdump86

No description available.

---

## nm86

No description available.

## size86

No description available.

# Installing Make

## Installing Make

Install Make by running the following commands:

```
root:make-3.79.1#    ./configure --prefix=/usr
root:make-3.79.1#    make
root:make-3.79.1#    make install
```

---

## Contents

The Make package contains the make program.

---

## Description

make determine automatically which pieces of a large program need to be recompiled, and issue the commands to recompile them.

---

# Installing Shellutils

## Installing Shell Utils

Install Shellutils by running the following commands:

```
root:sh-utils-2.0#    ./configure --prefix=/usr
root:sh-utils-2.0#    make
root:sh-utils-2.0#    make install
root:sh-utils-2.0#    cd /usr/bin
root:bin#    mv date echo false pwd stty /bin
root:bin#    mv su true uname hostname /bin
```

---

## Contents

The Shellutils package contains the basename, chroot, date, dirname, echo, env, expr, factor, false, groups, hostid, hostname, id, logname, nice, nohup, pathchk, pinky, printenv, printf, pwd, seq, sleep, stty, su, tee, test, true, tty, uname, uptime, users, who, whoami and yes programs.

---

## Description

### basename

basename strips directory and suffixes from filenames.

---

### chroot

chroot runs a command or interactive shell with special root directory.

---

### date

date displays the current time in a specified format, or sets the system date.

---

### dirname

dirname strips non−directory suffixes from file name.

---

## echo

echo displays a line of text.

## env

env runs a program in a modified environment.

## expr

expr evaluates expressions.

## factor

factor prints the prime factors of all specified integer numbers.

## false

false always exits with a status code indicating failure.

## groups

groups prints the groups a user is in.

## hostid

hostid prints the numeric identifier (in hexadecimal) for the current host.

## hostname

hostname sets or prints the name of the current host system

## id

id prints the real and effective UIDs and GIDs of a user or the current user.

## logname

logname prints the current user's login name.

## nice

nice runs a program with modified scheduling priority.

## nohup

nohup runs a command immune to hangups, with output to a non−tty

## pathchk

pathchk checks whether file names are valid or portable.

## pinky

pinky is a lightweight finger utility which retrieves information about a certain user

## printenv

printenv prints all or part of the environment.

## printf

printf formats and print data (the same as the printf C function).

## pwd

pwd prints the name of the current/working directory

## seq

seq prints numbers in a certain range with a certain increment.

## sleep

sleep delays for a specified amount of time.

---

## stty

stty changes and prints terminal line settings.

---

## su

su runs a shell with substitute user and group IDs

---

## tee

tee reads from standard input and write to standard output and files.

---

## test

test checks file types and compares values.

---

## true

True always exitx with a status code indicating success.

---

## tty

tty prints the file name of the terminal connected to standard input.

---

## uname

uname prints system information.

---

## uptime

uptime tells how long the system has been running.

---

## users

users prints the user names of users currently logged in to the  current host.

---

## who

who shows who is logged on.

---

## whoami

whoami prints your effective userid.

---

## yes

yes outputs a string repeatedly until killed.

---

# Installing Shadowpwd

## Installing Shadow Password Suite

Install the Shadow Password Suite by running the following commands:

```
root:shadow-19990827#   ./configure --prefix=/usr
root:shadow-19990827#   make
root:shadow-19990827#   make install
root:shadow-19990827#   cd etc
root:etc#   cp limits login.access login.defs.linux shells
suauth /etc
root:etc#   mv /etc/login.defs.linux /etc/login.defs
```

---

## Contents

The Shadow Password Suite contains the chage, chfn, chsh, expiry, faillog, gpasswd, lastlog, login, newgrp, passwd, sg, su, chpasswd, dpasswd, groupadd, groupdel, groupmod, grpck, grpconv, grpunconv, logoutd, mkpasswd, newusers, pwck, pwconv, pwunconv, useradd, userdel, usermod and vipw programs.

---

## Description

### chage

chage changes the number of days between password changes and the date of the last password change.

---

### chfn

chfn changes user fullname, office number, office extension, and home phone number information for a user's account.

---

### chsh

chsh changes the user login shell.

---

## expiry

It's currently unknown what this program is for.

---

## faillog

faillog formats the contents of the failure log,/var/log/faillog, and maintains failure counts and limits.

---

## gpasswd

gpasswd is used to administer the /etc/group file

---

## lastlog

lastlog formats and prints the contents of the last login log, /var/log/lastlog. The login−name, port, and last login time will be printed.

---

## login

login is used to establish a new session with the system.

---

## newgrp

newgrp is used to change the current group ID during a login session.

---

## passwd

passwd changes passwords for user and group accounts.

---

## sg

sg executes command as a different group ID.

---

## su

Change the effective user id and group id to that of a user. This replaces the su programs that's installed from the Shellutils package.

---

## chpasswd

chpasswd reads a file of user name and password pairs from standard input and uses this information to update a group of existing users.

---

## dpasswd

dpasswd adds, deletes, and updates dialup passwords for user login shells.

---

## groupadd

The groupadd command creates a new group account using the values specified on the command line and the default values from the system.

---

## groupdel

The groupdel command modifies the system account files, deleting all entries that refer to group.

---

## groupmod

The groupmod command modifies the system account files to reflect the changes that are specified on the command line.

---

## grpck

grpck verifies the integrity of the system authentication information.

---

## grpconv

grpunconv converts to shadow group files from normal group files.

---

## grpunconv

grpunconv converts from shadow group files to normal group files.

---

## logoutd

logoutd enforces the login time and port restrictions specified in /etc/porttime.

---

## mkpasswd

mkpasswd reads a file in the format given by the flags and converts it to the corresponding database file format.

---

## newusers

newusers reads a file of user name and cleartext password pairs and uses this information to update a group of existing users or to create new users.

---

## pwck

pwck verifies the integrity of the system authentication information.

---

## pwconv

pwconv converts to shadow passwd files from normal passwd files.

---

## pwunconv

pwunconv converts from shadow passwd files to normal files.

---

## useradd

useradd creates a new user or update default new user information.

---

## userdel

userdel modifies the system account files, deleting all entries that refer to a specified login name.

---

## usermod

usermod modifies the system account files to reflect the changes that are specified on the command line.

---

## vipw and vigr

vipw and vigr will edit the files /etc/passwd and /etc/group, respectively. With the –s flag, they will edit the shadow versions of those files, /etc/shadow and /etc/gshadow, respectively.

---

# Installing Modutils

## Installing Modutils

Install Modutils by running the following commands:

```
root:modutils-2.3.12#    ./configure
root:modutils-2.3.12#    make
root:modutils-2.3.12#    make install
```

---

## Contents

The Modutils package contains the depmod, genksyms, insmod, insmod_ksymoops_clean, kerneld, kernelversion, ksyms, lsmod, modinfo, modprobe and rmmod programs.

---

## Description

### depmod

depmod handles dependency descriptions for loadable kernel modules.

---

### genksyms

genksyms reads (on standard input) the output from gcc –E source.c and generates a file containing version information.

---

### insmod

insmod installs a loadable module in the running kernel.

---

### insmod_ksymoops_clean

insmod_ksymoops_clean deletes saved ksyms and modules not accessed in 2 days.

---

## kerneld

kerneld performs kernel action in user space (such as on−demand loading of modules)

## kernelversion

kernelversion reports the major version of the running kernel.

## ksyms

ksyms displays exported kernel symbols.

## lsmod

lsmod shows information about all loaded modules.

## modinfo

modinfo examines an object file associated with a kernel module and displays any information that it can glean.

## modprobe

Modprobe uses a Makefile−like dependency file, created by depmod, to automatically load the relevant module(s) from the set of modules available in predefined directory trees.

## rmmod

rmmod unloads loadable modules from the running kernel.

# Installing Procinfo

## Installing Procinfo

Install Procinfo by running the following commands:

```
root:procinfo-17#   sed s/"-ltermcap"/"-lncurses"/ Makefile
>Makefile2
root:procinfo-17#   mv Makefile2 Makefile
root:procinfo-17#   make
root:procinfo-17#   make install
```

---

## Contents

The Procinfo package contains the procinfo program.

---

## Description

procinfo gathers some system data from the /proc directory and prints it nicely formatted on the standard output device.

---

# Installing Procps

## Installing Procps

Edit the `Makefile` file and edit the CFLAGS variable if you want to add compiler optimizations to this package.

Install Procps by running the following commands:

```
root:procps-2.0.7#   sed s/XConsole/#XConsole/ Makefile
>Makefile2
root:procps-2.0.7#   mv Makefile2 Makefile
root:procps-2.0.7#   gcc -c watch.c
root:procps-2.0.7#   make
root:procps-2.0.7#   make install
root:procps-2.0.7#   mv /usr/bin/kill /bin
```

---

## Contents

The Procps package contains the free, kill, oldps, ps, skill, snice, sysctl, tload, top, uptime, vmstat, w and watch programs.

---

## Description

### free

free displays the total amount of free and used physical and swap memory in the system, as well as the shared memory and buffers used by the kernel.

---

### kill

kills sends signals to processes.

---

### oldps and ps

ps gives a snapshot of the current processes.

---

## skill

skill sends signals to process matching a criteria.

---

## snice

snice changes the scheduling priority for process matching a criteria.

---

## sysctl

sysctl modifies kernel parameters at runtime.

---

## tload

tload prints a graph of the current system load average to the specified tty (or the tty of the tload process if none is specified).

---

## top

top provides an ongoing look at processor activity in real time.

---

## uptime

uptime gives a one line display of the following information: the current time, how long the system has been running, how many users are currently logged on, and the system load averages for the past 1, 5, and 15 minutes.

---

## vmstat

vmstat reports information about processes, memory, paging, block IO, traps, and cpu activity.

---

## w

w displays information about the users currently on the machine, and their processes.

---

## watch

watch runs command repeatedly, displaying its output (the first screenfull).

---

# Installing Psmisc

## Installing Psmisc

Edit the `Makefile` file and edit the CFLAGS variable if you want to add compiler optimizations to this package.

Install Psmisc by running the following commands:

```
root:psmisc#   sed s/-ltermcap/-lncurses/ Makefile >Makefile2
root:psmisc#   mv Makefile2 Makefile
root:psmisc#   make
root:psmisc#   make install
```

---

## Contents

The Psmisc package contains the fuser, killall and pstree programs.

---

## Description

### fuser

fuser displays the PIDs of processes using the specified files or file systems.

---

### killall

killall sends a signal to all processes running any of the specified commands.

---

### pstree

pstree shows running processes as a tree.

---

# Installing Sed

## Installing Sed

Install Sed by running the following commands:

```
root:sed-3.02#   ./configure --prefix=/usr
root:sed-3.02#   make
root:sed-3.02#   make install
root:sed-3.02#   mv /usr/bin/sed /bin
```

---

## Contents

The Sed package contains the sed program.

---

## Description

sed is a stream editor. A stream editor is used to perform basic text transformations on an input stream (a file or input from a pipeline).

---

# Installing Vim

## Installing Vim

You need to unpack both the vim−rt and vim−src packages to install Vim. Install Vim by running the following commands:

```
root:vim-5.6#   ./configure --prefix=/usr
root:vim-5.6#   make
root:vim-5.6#   make install
root:vim-5.6#   cd /usr/bin
root:bin#   ln -s vim vi
```

If you are planning on installing the X Window system on your LFS system, you might want to re−compile Vim after you have installed X. Vim comes with a nice GUI version of the editor which requires X and a few other libraries to be installed. For more information read the Vim documentation.

---

## Contents

The Vim package contains the ctags, etags, ex, gview, gvim, rgview, rgvim, rview, rvim, view, vim, vimtutor and xxd programs.

---

## Description

### ctags

ctags generate tag files for source code.

---

### etags

etags does the same as ctags but it can generate cross reference files which list information about the various source objects found in a set of lanugage files.

---

### ex

ex starts vim in Ex mode.

---

## gview

gview is the GUI version of view.

## gvim

gvim is the GUI version of vim.

## rgview

rgview is teh GUI version of rview.

## rgvim

rgvim is the GUI version of rvim.

## rview

rview is a restricted version of view. No shell commands can be started and Vim can't be suspended.

## rvim

rvim is the restricted version of vim. No shell commands can be started and Vim can't be suspended.

## view

view starts vim in read−only mode.

## vim

vim starts vim in the normal, default way.

## vimtutor

vimtutor starts the Vim tutor.

## xxd

xxd makes a hexdump or does the reverse.

# Installing Sysklogd

## Installing Sysklogd

Edit the `Makefile` file and find this line: *CFLAGS= $(RPM_OPT_FLAGS) −O3 −DSYSV −fomit−frame−pointer −Wall −fno−strength−reduce*. Add the proper −mcpu= and −march= option to this variable and save the file.

Install Sysklogd by running the following commands:

```
root:sysklogd-1.3-31#   make
root:sysklogd-1.3-31#   make install
```

---

## Contents

The Sysklogd package contains the klogd and syslogd programs.

---

## Description

### klogd

klogd is a system daemon which intercepts and logs Linux kernel messages.

---

### syslogd

Syslogd provides a kind of logging that many modern programs use.Every logged message contains at least a time and a hostname field, normally a program name field, too, but that depends on how trusty the logging program is.

---

# Installing Sysvinit

## Installing Sysvinit

Edit the `src/Makefile` file and edit the CFLAGS variable if you want to add compiler optimizations to this package.

Install Sysvinit by running the following commands:

```
root:sysvinit-2.78#   cd src
root:sysvinit-2.78#   make
root:sysvinit-2.78#   make install
```

---

## Contents

The Sysvinit package contains the pidof, last, lastb, mesg, utmpdump, wall, halt, init, killall5, poweroff, reboot, runlevel, shutdown, sulogin and telinit programs.

---

## Description

### pidof

Pidof finds the process id's (pids) of the named programs and prints those id's on standard output.

---

### last

last searches back through the file /var/log/wtmp (or the file designated by the –f flag) and displays a list of all users logged in (and out) since that file was created.

---

### lastb

lastb is the same as last, except that by default it shows a log of the file /var/log/btmp, which contains all the bad login attempts.

---

### mesg

Mesg controls the access to your terminal by others. It's typically used to allow or disallow other users to

write to your terminal.

## utmpdump

utmpdumps prints the content of a file (usually /var/run/utmp) on standard output in a user friendly format.

## wall

Wall sends a message to everybody logged in with their mesg permission set to yes.

## halt

Halt notes that the system is being brought down in the file /var/log/wtmp, and then either tells the kernel to halt, reboot or poweroff the system. If halt or reboot is called when the system is not in runlevel 0 or 6, shutdown will be invoked instead (with the flag –h or –r).

## init

Init is the parent of all processes. Its primary role is to create processes from a script stored in the file /etc/inittab. This file usually has entries which cause init to spawn gettys on each line that users can log in. It also controls autonomous processes required by any particular system.

## killall5

killall5 is the SystemV killall command. It sends a signal to all processes except the processes in its own session, so it won't kill the shell that is running the script it was called from.

## poweroff

poweroff is equivalent to shutdown –h –p now. It halts the computer and switches off the computer (when using an APM compliant BIOS and APM is enabled in the kernel).

## reboot

reboot is equivalent to shutdown –r now. It reboots the computer.

## runlevel

Runlevel reads the system utmp file (typically /var/run/utmp) to locate the runlevel record, and then prints

the previous and current system runlevel on its standard output, separated by a single space.

## shutdown

shutdown brings the system down in a secure way. All logged−in users are notified that the system is going down, and login is blocked.

## sulogin

sulogin is invoked by init when the system goes into single user mode (this is done through an entry in /etc/inittab). Init also tries to execute sulogin when it is passed the −b flag from the bootmonitor (eg, LILO).

## telinit

telinit sends appropriate signals to init, telling it which runlevel to change to.

# Installing Tar

## Installing Tar

Install Tar by running the following commands:

```
root:tar-1.13#   ./configure --prefix=/usr
root:tar-1.13#   make
root:tar-1.13#   make install
root:tar-1.13#   mv /usr/bin/tar /bin
```

If you want to apply the Bzip2 tar patch which gives you the -y option to tar so you can use bzip2 files with tar, first download the patch from http://sourceware.cygnus.com/bzip2/ and apply it by running the following command within the src directory under the tar-1.13 directory:

```
root:src#   patch -i ../../gnutarpatch.txt
```

---

## Contents

The tar package contains the tar and rmt programs.

---

## Description

### tar

tar is an archiving program designed to store and extract files from an archive file known as a tarfile.

---

### rmt

rmt is a program used by the remote dump and restore programs in manipulating a magnetic tape drive through an interprocess communication connection.

---

# Installing Textutils

## Installing Textutils

Install Textutuils by running the following commands:

```
root:textutils-2.0#   ./configure --prefix=/usr
root:textutils-2.0#   make
root:textutils-2.0#   make install
root:textutils-2.0#   mv /usr/bin/cat /bin
```

---

## Contents

The Textutils package contains the cat, cksum, comm, split, cut, expand, fmt, fold, head, join, md5sum, nl, od, paste, pr, ptx, sort, split, sum, tac, tail, tr, tsort, unexpand, uniq and wc programs.

---

## Description

### cat

cat concatenates file(s) or standard input to standard output.

---

### cksum

cksum prints CRC checksum and byte counts of each specified file.

---

### comm

comm compares two sorted files line by line.

---

### csplit

cplit outputs pieces of a file separated by (a) pattern(s) to files xx01, xx02, ..., and outputs byte counts of each piece to standard output.

---

## cut

cut prints selected parts of lines from specified files to standard output.

## expand

expand converts tabs in files to spaces, writing to standard output.

## fmt

fmt reformats each paragraph in the specified file(s), writing to standard output.

## fold

fold wraps input lines in each specified file (standard input by default), writing to standard output.

## head

Print first xx (10 by default) lines of each specified file to standard output.

## join

join joins lines of two files on a common field.

## md5sum

md5sum prints or checks MD5 checksums.

## nl

nl writes each specified file to standard output, with line numbers added.

## od

od writes an unambiguous representation, octal bytes by default, of a specified file to standard output.

## paste

paste writes lines consisting of the sequentially corresponding lines from each specified file, separated by TABs, to standard output.

## pr

pr paginates or columnates files for printing.

## ptx

ptx produces a permuted index of file contents.

## sort

sort writes sorted concatenation of files to standard output.

## split

split outputs fixed−size pieces of an input file to PREFIXaa, PREFIXab, ...

## sum

sum prints checksum and block counts for each specified file.

## tac

tac writes each specified file to standard output, last line first.

## tail

tail print the last xx (10 by default) lines of each specified file to standard output.

## tr

tr translates, squeezes, and/or deletes characters from standard input, writing to standard output.

## tsort

tsort writes totally ordered lists consistent with the partial ordering in specified files.

## unexpand

unexpand converts spaces in each file to tabs, writing to standard output.

## uniq

uniq discards all but one of successive identical lines from files or standard input and writes to files or standard output.

## wc

wc prints line, word, and byte counts for each specified file, and a total line if more than one file is specified.

# Installing Utillinux

## Installing Util−Linux

Before we can install the package we have to edit the MCONFIG file, find and modify the following variables as follows:

*HAVE_SLN=yes*
*HAVE_TSORT=yes*

Now find the following lines in the MCONFIG file:

```
ifeq "$(CPU)" "intel"
  OPT=        −pipe −O2 −m486 −fomit−frame−pointer
else
  ifeq "$(CPU)" "arm"
    OPT=      −pipe −O2 −fsigned−char −fomit−frame−pointer
  else
    OPT=      −O2 −fomit−frame−pointer
  endif
endif
```

Modify the proper OPT variable to include the −mcpu= and −march= options. If you modify the first OPT variable, replace *−m486* with the *−mcpu* variable.

Install Util−Linux by running the following commands:

```
root:util−linux−2.10m#    ./configure
root:util−linux−2.10m#    make
root:util−linux−2.10m#    make install
```

---

# Contents

The Util−linux package contains the arch, dmesg, kill, more, mount, umount, agetty, blockdev, cfdisk, ctrlaltdel, elvtune, fdisk, fsck.minix, hwclock, kbdrate, losetup, mkfs, mkfs.bfs, mkfs.minix, mkswap, sfdisk, swapoff, swapon, cal, chkdupexe, col, colcrt, colrm, column, cytune, ddate, fdformat, getopt, hexdump, ipcrm, ipcs, logger, look, mcookie, namei, rename, renice, rev, script, setfdprm, setsid, setterm, ul, whereis,

write, ramsize, rdev, readprofile, rootflags, swapdev, tunelp and vidmode programs.

# Description

## arch

arch prints the machine architecture.

## dmesg

dmesg is used to examine or control the kernel ring buffer (boot messages from the kernel).

## kill

kill sends a specified signal to the specified process.

## more

more is a filter for paging through text one screenful at a time.

## mount

mount mounts a filesystem from a device to a directory (mount point).

## umount

umount unmounts a mounted filesystem.

## agetty

agetty opens a tty port, prompts for a login name and invokes the /bin/login command.

## blockdev

No description available.

## cfdisk

cfdisk is an libncurses based disk partition table manipulator.

## ctrlaltdel

ctrlaltdel sets the function of the CTRL+ALT+DEL key combination (hard or soft reset).

## elvtune

elvtune allows to tune the I/O elevator per blockdevice queue basis.

## fdisk

fdisk is a disk partition table manipulator.

## fsck.minix

fsck.minix performs a consistency check for the Linux MINIX filesystem.

## hwclock

hwclock queries and sets the hardware clock (Also called the RTC or BIOS clock).

## kbdrate

kbdrate resets the keyboard repeat rate and delay time.

## losetup

losetup sets up and controls loop devices.

## mkfs

mkfs builds a Linux filesystem on a device, usually a harddisk partition.

## mkfs.bfs

mkfs.bfs creates a SCO bfs file system on a device, usually a harddisk partition.

## mkfs.minix

mkfs.minix creates a Linux MINIX filesystem on a device, usually a harddisk partition.

## mkswap

mkswap sets up a Linux swap area on a device or in a file.

## sfdisk

sfdisk is a disk partition table manipulator.

## swapoff

swapoff disables devices and files for paging an swapping.

## swapon

swapon enables devices and files for paging and swapping.

## cal

cal displays a simple calender.

## chkdupexe

chkdupexe finds duplicate executables.

## col

col filters reverse line feeds from input.

## colcrt

colcrt filters nroff output for CRT previewing.

## colrm

colrm removes columns from a file.

## column

column columnates lists.

## cytune

cytune queries and modifies the interruption threshold for the Cyclades driver.

## ddate

ddate converts Gregorian dates to Discordian dates.

## fdformat

fdformat low−level formats a floppy disk.

## getopt

getops parses command options the same way as the getopt C command.

## hexdump

hexdump displays specified files, or standard input, in a user specified format (ascii, decimal, hexadecimal, octal).

## ipcrm

ipcrm removes a specified resource.

## ipcs

ipcs provides information on ipc facilities.

## logger

logger makes entries in the system log.

## look

look displays lines beginning with a given string.

## mcookie

mcookie generates magic cookies for xauth.

## namei

namei follows a pathname until a terminal point is found.

## rename

rename renames files.

## renice

renice alters priority of running processes.

## rev

rev reverses lines of a file.

## script

script makes typescript of terminal session.

## setfdprm

setfdprm sets user−provides floppy disk parameters.

## setsid

setsid runs programs in a new session.

## setterm

setterm sets terminal attributes.

## ul

ul reads a file and translates occurences of underscores to the sequence which indicates underlining for the terminal in use.

## whereis

whereis locates a binary, source and manual page for a command.

## write

write sends a message to another user.

## ramsize

ramsize queries and sets RAM disk size.

## rdev

rdev queries and sets image root device, swap device, RAM disk size, or video mode.

## readprofile

readprofile reads kernel profiling information.

## rootflags

rootflags queries and sets extra information used when mounting root.

## swapdev

swapdev queries and sets swap device.

## tunelp

tunelp sets various paramters for the lp device.

## vidmode

vidmode queries and sets the video mode.

# Installing Pmac–utils

Install Pmac–utils by running the following commands:

```
root:pmac-utils-1.1.1#    make clock
root:pmac-utils-1.1.1#    cp clock /sbin
root:pmac-utils-1.1.1#    rm /sbin/hwclock
```

Create a new file `/sbin/hwclock` containing the following:

```
#!/bin/sh
# Begin /sbin/hwclock

/sbin/clock –s

# End /sbin/hwclock
```

Set the right permissions by running the following command:

```
root:~#   chmod 755 /sbin/hwclock
```

# Installing Man–pages

## Installing Man–pages

Install Man–pages by running the following commands:

```
root:man-pages-1.30#   cp -av man2 man3 man4 \
> man5 man6 man7 /usr/share/man
root:man-pages-1.30#   cd man8
root:man8#   cp tzselect.8 zdump.8 \
> zic.8 /usr/share/man/man8
```

## Contents

The Man–pages package contains various manual pages that don't come with the packages.

## Description

Examples of provided manual pages are the manual pages describing all the C and C++ functions, few important /dev/ files and more.

# Removing old NSS library files

If you have copied the NSS Library files from your normal Linux system to the LFS system (because your normal system runs glibc−2.0) it's time to remove them now by running:

```
root:~#     rm /lib/libnss*.so.1 /lib/libnss*2.0*
```

---

# Configuring essential software

Now that all software is installed, all that we need to do to get a few programs running properly is to create their configuration files.

---

## Configuring Glibc

We need to create the /etc/nsswitch.conf file. Although glibc should provide defaults when this file is missing or corrupt, it's defaults don't work work well with networking which will be dealt with in a later chapter. Also, our timezone needs to be setup.

Create a new file `/etc/nsswitch.conf` containing the following:

```
# Begin /etc/nsswitch.conf

passwd: files
group: files
shadow: files

hosts: files dns
networks: files

protocols: db files
services: db files
ethers: db files
rpc: db files

netgroup: db files

# End /etc/nsswitch.conf
```

Run the **`tzselect`** script and answer the questions regarding your timezone. When you're done, the script will give you the location of the timezone file you need.

Create the `/etc/localtime` symlink by running:

```
root:~#   cd /etc
root:etc#   rm localtime
root:etc#   ln -s ../usr/share/zoneinfo/<tzselect's output> \
> localtime
```

tzselect's output can be something like *EST5EDT* or *Canada/Eastern*. The symlink you would create with that information would be *ln −s ../usr/share/zoneinfo/EST5EDT localtime* or *ln −s ../usr/share/zoneinfo/Canada/Eastern localtime*

---

# Configuring Dynamic Loader

By default the dynamic loader searches a few default paths for dynamic libraries, so there normally isn't a need for the `/etc/ld.so.conf` file unless you have extra directories in which you want the system to search for paths. The `/usr/local/lib` directory isn't searched through for dynamic libraries by default, so we want to add this path so when you install software you won't be suprised by them not running for some reason.

Create a new file `/etc/ld.so.conf` containing the following:

```
# Begin /etc/ld.so.conf

/lib
/usr/lib
/usr/local/lib

# End /etc/ld.so.conf
```

Although it's not necessary to add the `/lib` and `/usr/lib` directories it doesn't hurt. This way you see right away what's being searched and don't have to remeber the default search paths if you don't want to.

---

# Configuring Sysklogd

Create a new file `/etc/syslog.conf` containing the following:

```
# Begin /etc/syslog.conf

auth,authpriv.* –/var/log/auth.log
*.*;auth,authpriv.none –/var/log/sys.log
daemon.* –/var/log/daemon.log
kern.* –/var/log/kern.log
mail.* –/var/log/mail.log
user.* –/var/log/user.log
*.emerg *
```

```
# End /etc/syslog.conf
```

## Configuring Shadow Password Suite

This package contains the utilities to modify user's passwords, add new users/groups, delete users/groups and more. I'm not going to explain to you what 'password shadowing' means. You can read all about that in the doc/HOWTO file. There's one thing you should keep in mind, if you decide to use shadow support, that programs that need to verify passwords (examples are xdm, ftp daemons, pop3 daemons, etc) need to be 'shadow−compliant', eg. they need to be able to work with shadowed passwords.

If you decide you don't want to use shadowed passwords (after you're read the doc/HOWTO document), you still use this archive since the utilities in this archive are also used on system which have shadowed passwords disabled. You can read all about this in the HOWTO. Also note that you can switch between shadow and non−shadow at any point you want.

Now is a very good moment to read chapter 5 of the doc/HOWTO file. You can read how you can test if shadowing works and if not, how to disable it. If it doesn't work and you haven't tested it, you'll end up with an unusable system after you logout of all your consoles, since you won't be able to login anymore. You can easily fix this by passing the init=/sbin/sulogin parameter to the kernel, unpack the util−linux archive, go to the login−utils directory, build the login program and replace the /bin/login by the one in the util−linux package. Things are never hopelessly messed up (at least not under Linux), but you can avoid a hassle by testing properly and reading manuals ;)

## Configuring Sysvinit

Create a new file `/etc/inittab` containing the following:

```
# Begin /etc/inittab

id:3:initdefault:

si::sysinit:/etc/init.d/rcS

su:S:wait:/sbin/sulogin

l0:0:wait:/etc/init.d/rc 0
l1:1:wait:/etc/init.d/rc 1
l2:2:wait:/etc/init.d/rc 2
l3:3:wait:/etc/init.d/rc 3
l4:4:wait:/etc/init.d/rc 4
l5:5:wait:/etc/init.d/rc 5
l6:6:wait:/etc/init.d/rc 6
```

```
f1:0:respawn:/sbin/sulogin
f2:6:respawn:/sbin/sulogin

ca:12345:ctrlaltdel:/sbin/shutdown –t1 –a –r now

1:2345:respawn:/sbin/agetty /dev/tty1 9600
2:2345:respawn:/sbin/agetty /dev/tty2 9600
3:2345:respawn:/sbin/agetty /dev/tty3 9600
4:2345:respawn:/sbin/agetty /dev/tty4 9600
5:2345:respawn:/sbin/agetty /dev/tty5 9600
6:2345:respawn:/sbin/agetty /dev/tty6 9600

# End /etc/inittab
```

## Creating the /var/run/utmp file

Programs like login, shutdown, uptime and others want to read from and write to the /var/run/utmp file. This file contains information about who is currently logged in. It also contains information on when the computer was last booted and shutdown.

Create the `/var/run/utmp` and give it the proper permissions by running the following commands:

```
root:~# touch /var/run/utmp
root:~# chmod 0644 /var/run/utmp
```

## Configuring Vim

By default Vim runs in vi compatible mode. Some people might like this, but I have a high preference to run vim in vim mode (else I wouldn't have included Vim in this book but the original Vi). Create the `/root/.vimrc` containing the following:

```
set nocompatible
set bs=2
```

## Creating root password

Choose a password for user root and create it by running the following command:

```
root:~#    passwd root
```

# Chapter 12. Creating system boot scripts

# What is being done here

This chapter will create the necessary scripts that are run at boottime. These scripts perform tasks such as remounting the root file system mounted read−only by the kernel into read−write mode, activiating the swap partition(s), running a check on the root file system to make sure it's intact and starting the daemons that the system uses.

---

# Creating directories

We need to start by creating a few extra directories that are used by the boot scripts. Create these directories by running:

```
root:~#   cd /etc
root:etc#   mkdir sysconfig rc0.d rc1.d rc2.d rc3.d
root:etc#   mkdir rc4.d rc5.d rc6.d init.d rcS.d
```

# Creating the rc script

The first main bootscript is the `/etc/init.d/rc` script. Create a new file `/etc/init.d/rc` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/rc
#
# By Jason Pearce  – jason.pearce@linux.org
# Modified by Gerard Beekmans – gerard@linuxfromscratch.org
#

# Un–comment the following for debugging.
# debug=echo

#
# Start script or program.
#
startup() {
case "$1" in
        *.sh)
                $debug sh "$@"
                ;;
        *)
                $debug "$@"
                ;;
esac
}

# Ignore CTRL–C only in this shell, so we can interrupt subprocesses.
trap ":" INT QUIT TSTP

# Set onlcr to avoid staircase effect.
stty onlcr 0>&1

# Now find out what the current and what the previous runlevel are.
runlevel=$RUNLEVEL
# Get first argument. Set new runlevel to this argument.

[ "$1" != "" ] && runlevel=$1
if [ "$runlevel" = "" ]
then
        echo "Usage: $0 <runlevel>" >&2
        exit 1
fi

previous=$PREVLEVEL
```

```
[ "$previous" = "" ] && previous=N

export runlevel previous

# Is there an rc directory for this new runlevel?

if [ −d /etc/rc$runlevel.d ]
then
      # First, run the KILL scripts for this runlevel.
      if [ $previous != N ]
      then
            for i in /etc/rc$runlevel.d/K*
      do
            [ ! −f $i ] && continue

                  suffix=${i#/etc/rc$runlevel.d/K[0−9][0−9]}
                  previous_start=/etc/rc$previous.d/S[0−9][0−9]$suffix
                  sysinit_start=/etc/rcS.d/S[0−9][0−9]$suffix

                  # Stop the service if there is a start script
                  # in the previous run level.
                  [ ! −f $previous_start ] && [ ! −f sysinit_start] && continue

                  startup $i stop
            done
      fi

      # Now run the START scripts for this runlevel.
      for i in /etc/rc$runlevel.d/S*
      do
            [ ! −f $i ] && continue

            if [ $previous != N ]
      then
                  # Find start script in previous runlevel and
                  # stop script in this runlevel.
                  suffix=${i#/etc/rc$runlevel.d/S[0−9][0−9]}
                  stop=/etc/rc$runlevel.d/K[0−9][0−9]$suffix
                  previous_start=/etc/rc$previous.d/S[0−9][0−9]$suffix

                  # If there is a start script in the previous
                  # level
                  # and _no_ stop script in this level, we don't
                  # have to re−start the service.
                  [ −f $previous_start ] && [ ! −f $stop ] && continue
            fi

            case "$runlevel" in
                  0|6)
                        startup $i stop
                        ;;
```

```
                *)
                        startup $i start
                        ;;
        esac
    done
fi

# End /etc/init.d/rc
```

# Creating the rcS script

The second main bootscript is the `rcS` script. Create a new file `/etc/init.d/rcS` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/rcS

runlevel=S
prevlevel=N
umask 022
export runlevel prevlevel

trap ":" INT QUIT TSTP

for i in /etc/rcS.d/S??*
do
        [ ! –f  "$i" ] && continue;
                $i start
done

# End /etc/init.d/rcS
```

# Creating the functions script

Create a new file `/etc/init.d/functions` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/functions

COL=70
SET_COL="echo –en \\033[${COL}G"
NORMAL="echo –en \\033[0;39m"
SUCCESS="echo –en \\033[1;32m"
FAILURE="echo –en \\033[1;31m"

evaluate_retval()
{
if [ $? = 0 ]
then
print_status success
else
print_status failure
fi
}

print_status()
{
if [ $# = 0 ]
then
echo "Usage: print_status {success|failure}"
exit 1
fi

case "$1" in
success)
$SET_COL
echo –n "[  "
$SUCCESS
echo –n "OK"
$NORMAL
echo "  ]"
echo –en "\r"
;;
failure)
$SET_COL
echo –n "["
$FAILURE
echo –n "FAILED"
$NORMAL
```

```
echo −n "]"
echo −en "\r"
;;
esac

}

loadproc()
{
if [ $# = 0 ]
then
echo "Usage: loadproc {program}"
exit 1
fi

base=`basename $1`

pidlist=`pidof −o $$ −o $PPID −o %PPID −x $base`

pid=""

for apid in $pidlist
do
if [ −d /proc/$apid ]
then
pid="$pid $apid"
fi
done

if [ ! −n "$pid" ]
then
$*

evaluate_retval
else
print_status failure
fi

}

killproc()
{

if [ $# = 0 ]
then
echo "Usage: killproc {program} [signal]"
exit 1
fi

base=`basename $1`
```

```
if [ "$2" != "" ]
then
killlevel=$2
else
nolevel=1
fi

pidlist=`pidof −o $$ −o $PPID −o %PPID −x $base`

pid=""

for apid in $pidlist
do
if [ −d /proc/$apid ]
then
pid="$pid $apid"
fi
done

if [ −n "$pid" ]
then
if [ "$nolevel" = 1 ]
then
kill −TERM $pid
if ps h $pid >/dev/null 2>&1
then
kill −KILL $pid
fi
ps h $pid >/dev/null 2>&1
if [ $? = 0 ]
then
print_status failure
else
rm −f /var/run/$base.pid
print_status success
fi
else
kill $killlevel $pid
ps h $pid >/dev/null 2>&1
if [ $? = 0 ]
then
print_status failure
else
rm −f /var/run/$base.pid
print_status success
fi
fi
else
print_status failure
fi
}
```

```
reloadproc()
{
if [ $# = 0 ]
then
echo "Usage: reloadproc {program} [signal]"
exit 1
fi

base=`basename $1`

if [ −n "$2" ]
then
killlevel=$2
else
nolevel=1
fi

pidlist=`pidof −o $$ −o $PPID −o %PPID −x $base`

pid=""

for apid in $pidlist
do
if [ −d /proc/$apid ]
then
pid="$pid $apid"
fi
done

if [ −n "$pid" ]
then
if [ "$nolevel" = 1 ]
then
kill −SIGHUP $pid
evaluate_retval
else
kill $killlevel $pid
evaluate_retval
fi
else
print_status failure
fi
}

statusproc()
{
        if [ $# = 0 ]
        then
                echo "Usage: status {program}"
                return 1
```

```
        fi

        pid=`pidof -o $$ -o $PPID -o %PPID -x $1`
        if [ -n "$pid" ]
        then
                echo "$1 running with Process ID $pid"
                return 0
        fi

        if [ -f /var/run/$1.pid ]
        then
                pid=`head -1 /var/run/$1.pid`
                if [ -n "$pid" ]
                then
                        echo "$1 not running but /var/run/$1.pid exists"
                        return 1
                fi
        fi

}

# End /etc/init.d/functions
```

# Creating the checkfs script

Create a new file `/etc/init.d/checkfs` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/checkfs

source /etc/init.d/functions

echo −n "Activating swap..."
/sbin/swapon −a
evaluate_retval

if [ −f /fastboot ]
then
        echo "Fast boot, no file system check"
        rm /fastboot
else
        /bin/mount −n −o remount,ro /
        if [ $? = 0 ]
        then
                if [ −f /forcefsck ]
                then
echo "/forcefsck exists, forcing file system check"
                        force="−f"
                else
                        force=""
                fi

                echo "Checking file systems..."
                /sbin/fsck $force −a −A −C −T −V

                if [ $? −gt 1 ]
                then
                        $FAILURE
echo
                        echo −n "fsck failed. Please repair your file "
                        echo "systems manually by running /sbin/fsck"
                        echo "without the −a option"
                        echo
                        echo −n "Please note that the root file system is "
                        echo "currently mounted in read−only mode."
                        echo
                        echo −n "I will start sulogin now. When you  "
                        echo "logout I will reboot your system."
                        echo
$NORMAL
```

```
                /sbin/sulogin
                /sbin/reboot -f
else
print_status success
fi

    else
        echo -n "Cannot check root file system because it "
        echo "could not be mounted in read-only mode."
    fi
fi

# End /etc/init.d/checkfs
```

# Creating the halt script

Create a new file `/etc/init.d/halt` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/halt

/sbin/halt –d –f –i –p

# End /etc/init.d/halt
```

# Creating the loadkeys script

You only need to create this script if you don't have a default 101 keys US keyboard layout. Create a new file `/etc/init.d/loadkeys` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/loadkeys

source /etc/init.d/functions

echo –n "Loading keymap..."
/usr/bin/loadkeys /usr/share/keymaps/<arch>/<layout>/<keymap> >/dev/null
evaluate_retval

# End /etc/init.d/loadkeys
```

Replace <arch>, <layout> and <keymap> with the proper directories and filenames to match your system and language.

---

# Creating the mountfs script

Create a new file `/etc/init.d/mountfs` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/mountfs

source /etc/init.d/functions

echo −n "Remounting root file system in read−write mode..."
/bin/mount −n −o remount,rw /
evaluate_retval

echo > /etc/mtab
/bin/mount −f −o remount,rw /

/bin/rm −f /fastboot /forcefsck

echo −n "Mounting other file systems..."
/bin/mount −a
evaluate_retval

# End /etc/init.d/mountfs
```

# Creating the reboot script

Create a new file `/etc/init.d/reboot` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/reboot

echo "System reboot in progress..."

/sbin/reboot –d –f –i

# End /etc/init.d/reboot
```

# Creating the sendsignals script

Create a new file `/etc/init.d/sendsignals` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/sendsignals

. /etc/init.d/functions

echo −n "Sending all processes the TERM signal..."
/sbin/killall5 −15
evaluate_retval

echo −n "Sending all processes the KILL signal..."
/sbin/killall5 −9
evaluate_retval

# End /etc/init.d/sendsignals
```

# Creating the setclock script

Create a new file `/etc/init.d/setclock` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/setclock

evaluate_retval()
{
        if [ $? = 0 ]
        then echo ""
                else
        echo "FAILED"
        fi
}

echo −n "Setting clock..."
/sbin/hwclock
evaluate_retval

# End /etc/init.d/setclock
```

# Creating the sysklogd script

Create a new file `/etc/init.d/sysklogd` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/sysklogd

source /etc/init.d/functions

case "$1" in
start)
echo −n "Starting system log daemon..."
loadproc /usr/sbin/syslogd −m 0

echo −n "Starting kernel log daemon..."
loadproc /usr/sbin/klogd
;;

stop)
echo −n "Stopping kernel log daemon..."
killproc klogd

echo −n "Stopping system log daemon..."
killproc syslogd
;;

reload)
echo −n "Reloading system log daemon configuration file..."
reloadproc syslogd −1
;;

restart)
$0 stop
sleep 1
$0 start
;;

status)
statusproc /usr/sbin/syslogd
statusproc /usr/sbin/klogd
;;

*)
echo "Usage: $0 {start|stop|reload|restart|status}"
exit 1
;;
```

```
esac

# End /etc/init.d/sysklogd
```

---

# Creating the umountfs script

Create a new file `/etc/init.d/umountfs` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/umountfs

source /etc/init.d/functions

echo −n "Deactivating swap..."
/sbin/swapoff −a
evaluate_retval

echo −n "Unmounting file systems..."
/bin/umount −a −r
evaluate_retval

# End /etc/init.d/umountfs
```

# Setting up symlinks and permissions

Give these files the proper permissions and create the necessary symlinks by running the following commands:

```
root:~#   cd /etc/init.d
root:init.d#   chmod 754 rc rcS functions checkfs halt
loadkeys mountfs
root:init.d#   chmod 754 reboot sendsignals setclock sysklogd
umountfs
root:init.d#   cd ../rc0.d
root:rc0.d#   ln -s ../init.d/sysklogd K90sysklogd
root:rc0.d#   ln -s ../init.d/sendsignals S80sendsignals
root:rc0.d#   ln -s ../init.d/umountfs S90umountfs
root:rc0.d#   ln -s ../init.d/halt S99halt
root:rc0.d#   cd ../rc6.d
root:rc6.d#   ln -s ../init.d/sysklogd K90sysklogd
root:rc6.d#   ln -s ../init.d/sendsignals S80sendsignals
root:rc6.d#   ln -s ../init.d/umountfs S90umountfs
root:rc6.d#   ln -s ../init.d/reboot S99reboot
root:rc6.d#   cd ../rcS.d
root:rcS.d#   ln -s ../init.d/setclock S01setclock
root:rcS.d#   ln -s ../init.d/checkfs S05checkfs
root:rcS.d#   ln -s ../init.d/mountfs S10mountfs
root:rcS.d#   ln -s ../init.d/loadkeys S20loadkeys
root:rcS.d#   cd ../rc1.d
root:rc1.d#   ln -s ../init.d/sysklogd K90sysklogd
root:rc1.d#   cd ../rc2.d
root:rc2.d#   ln -s ../init.d/sysklogd S03sysklogd
root:rc2.d#    cd ../rc3.d
root:rc3.d#    ln -s ../init.d/sysklogd S03sysklogd
root:rc3.d#    cd ../rc4.d
root:rc4.d#    ln -s ../init.d/sysklogd S03sysklogd
root:rc4.d#    cd ../rc5.d
root:rc5.d#    ln -s ../init.d/sysklogd S03sysklogd
```

# Creating the /etc/fstab file

In order for certain programs to be able to determine where certain partitions are supposed to be mounted by default, the /etc/fstab file is used. Create a new file `/etc/fstab` containing the following:

```
# Begin /etc/fstab

/dev/<LFS−partition designation> / ext2 defaults 1 1
/dev/<swap−partition designation> none swap sw 0 0
proc /proc proc defaults 0 0

# End /etc/fstab
```

Replace <LFS−partition designation> and <swap−partition designation> with the appropriate devices (/dev/hda5 and /dev/hda6 in my case).

---

# Chapter 13. Setting up basic networking

# Introduction

This chapter will setup basic networking. Although you might not be connected to a network, Linux software uses network functions anyway. We'll be installing at least the local loopback device and a network card as well if applicable. Also the proper bootscripts will be created so that networking will be enabled during boot time.

---

# Installing network software

## Installing Netkit–base

Install Netkit–base by running the following commands:

```
root:netkit-base-0.16#    ./configure --prefix=/usr
root:netkit-base-0.16#    make -e
root:netkit-base-0.16#    make install
root:netkit-base-0.16#    cd etc.sample
root:netkit-base-0.16/etc.sample#    cp services protocols /etc
```

---

## Installing Net–tools

Edit the `Makefile` file and edit the CFLAGS variable if you want to add compiler optimzations.

Install Net–tools by running the following commands:

```
root:net-tools-1.57#    make
root:net-tools-1.57#    make install
```

You might have noticed that we don't use the compiler optimizations for this package. The reason is that overriding the CFLAGS variable causes compilation problems. You would have to edit the Makefile file and add the proper values to the CFLAGS variable and then compile the package. If you want to do that it's up to you. I don't think it's worth the trouble though. The programs in this package aren't that big that optimization would have any noticable effect on the performance.

---

# Creating network boot scripts

## Creating the /etc/init.d/localnet bootscript

Create a new file `/etc/init.d/localnet` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/localnet

source /etc/init.d/functions
source /etc/sysconfig/network

case "$1" in
        start)
                echo –n "Bringing up the loopback interface..."
                /sbin/ifconfig lo 127.0.0.1
                evaluate_retval

                echo –n "Setting up hostname..."
                /bin/hostname $HOSTNAME
                evaluate_retval
                ;;

        stop)
                echo –n "Bringing down the loopback interface..."
                /sbin/ifconfig lo down
                evaluate_retval
                ;;

        *)
                echo "Usage: $0: {start|stop}"
                exit 1
                ;;
esac

# End /etc/init.d/localnet
```

---

## Setting up permissions and symlink

Set the proper file permissions and create the necessary symlink by running the following commands:

```
root:~#    cd /etc/init.d
root:init.d#    chmod 754 /etc/init.d/localnet
root:init.d#    cd ../rcS.d
root:rcS.d#    ln -s ../init.d/localnet S03localnet
```

---

## Creating the /etc/sysconfig/network file

Create a new file `/etc/sysconfig/network` and put the hostname in it by running:

```
root:~#   echo "HOSTNAME=lfs" > /etc/sysconfig/network
```

Replace "lfs" by the name you wish to call your computer. Please not that you should not enter the FQDN (Fully Qualified Domain Name) here. That information will be put in the `/etc/hosts` file later.

---

## Creating the /etc/hosts file

If you want to configure a network card, you have to decide on the IP−address, FQDN and possible aliases for use in the /etc/hosts file. An example is:

```
<my−IP> myhost.mydomain.org aliases
```

Make sure the IP−address is in the private network IP−address range. Valid ranges are:

```
Class Networks
A    10.0.0.0
B    172.16.0.0 through 172.31.0.0
C    192.168.0.0 through 192.168.255.0
```

A valid IP address could be 192.168.1.1. A valid FQDN for this IP could be www.linuxfromscratch.org

If you're not going to use a network card, you still need to come up with a FQDN. This is necessary for programs like Sendmail to operate correctly (in fact; Sendmail won't run when it can't determine the FQDN).

If you don't configure a network card, create a new file `/etc/hosts` containing:

```
# Begin /etc/hosts (no network card version)

127.0.0.1 www.mydomain.com <value of HOSTNAME> localhost

# End /etc/hosts (no network card version)
```

If you do configure a network card, create a new file `/etc/hosts` containing:

```
# Begin /etc/hosts (network card version)

127.0.0.1 localhost.localdomain localhost
192.168.1.1 www.mydomain.org <value of HOSTNAME>

# End /etc/hosts (network card version)
```

Of course, change the 192.168.1.1 and www.mydomain.org to your own liking (or requirements if you are assigned an IP−address by a network/system administrator and you plan on connecting this machine to that network).

---

## Creating the /etc/init.d/ethnet script

This section only applies if you are going to configure a network card. If you're not, skip this section.

Create a new file `/etc/init.d/ethnet` containing the following:

```
#!/bin/sh
# Begin /etc/init.d/ethnet

source /etc/init.d/functions
source /etc/sysconfig/network

case "$1" in
        start)
                echo −n "Bringing up the eth0 interface..."
                /sbin/ifconfig eth0 $IPADDR broadcast $BROADCAST netmask $NETMASK
                evaluate_retval
                ;;

        stop)
```

```
            echo –n "Bringing down the eth0 interface..."
            /sbin/ifconfig eth0 down
            evaluate_retval
            ;;

        *)
            echo "Usage: $0 {start|stop}"
            exit 1
            ;;
esac

# End /etc/init.d/ethnet
```

---

## Editing the /etc/sysconfig/network file

Edit the `/etc/sysconfig/network` file and add the following lines to it. Don't remove the HOSTNAME= line.

```
IPADDR=192.168.1.1
NETMASK=255.255.255.0
BROADCAST=192.168.1.255
```

Chagne the IPADDR, NETMASK and BROADCAST values to match your network setup.

---

## Setting up permissions and symlink

Set the proper file permissions and create the necessary symlink by running the following commands:

```
root:~#    cd /etc/init.d
root:init.d#    chmod 754 /etc/init.d/ethnet
root:init.d#   cd ../rc1.d
root:rc1.d#   ln –s ../init.d/ethnet K90ethnet
root:rc1.d#   cd ../rc2.d
root:rc2.d#   ln –s ../init.d/ethnet K90ethnet
root:rc2.d#    cd ../rc3.d
root:rc3.d#    ln –s ../init.d/ethnet S10ethnet
root:rc3.d#    cd ../rc4.d
root:rc4.d#    ln –s ../init.d/ethnet S10ethnet
root:rc4.d#    cd ../rc5.d
```

```
root:rc5.d#    ln -s ../init.d/ethnet S10ethnet
```

# Chapter 14. Making the LFS system bootable

# Introduction

This chapter will make LFS bootable. This chapter deals with building a new kernel for our new LFS system and moving the kernel to the MacOS side so we can boot the LFS system.

# Installing a kernel

A kernel is the heart of a Linux system. We could use the kernel image from our normal system, but we might as well compile a new kernel from the most recent kernel sources available.

Building the kernel involves a few steps: configuring it and compiling it. There are a few ways to configure the kernel. If you don't like the way this book does it, read the `README` file and find out what your other options are. Run the following commands to build the kernel:

If you need to apply the Kernel USB patch, do that by running the following commands:

```
root:~#   cd /usr/src/linux
root:linux#   patch -p1 -i ../usb-2.3.50-1-for-2.2.14.diff.gz
```

The build the actual kernel, run the following commands:

```
root:linux#   make mrproper
root:linux#   make pmac_config
root:linux#   make menuconfig
root:linux#   make dep
root:linux#   make vmlinux
root:linux#   cp System.map /boot
root:linux#   cp vmlinux /boot/lfskernel
```

---

# Updating BootX

Now we have to get /boot/lfskernel to the Mac OS side so we can boot our LFS system. There are a few ways to copy the /boot/lfskernel file to the Linux kernel folder on the Mac OS side.

The easiest way is be to mount a Mac HFS partition under Linux and copy the kernel to that partition in the right folder. The Linux kernel currently does not support the HFS+ partition, do do not attempt to mount a Mac HFS+ (also known as HFS Extended) partition under Linux.

Copy the kernel to your Mac HFS partition by running the following commands:

```
root:~#   mkdir /mnt/exchange
root:~#   mount -t hfs /dev/sda1 /mnt/exchange
root:~#   cp /boot/lfskernel /mnt/exchange
root:~#   umount /dev/sda1
```

Of course, replace /dev/sda1 by your Mac partition's designation.

If you can't mount the Mac partition for some reason (for example because it's a HFS+ partition) you'll have to email the kernel to yourself. Use a shell on your normal Linux's system (not the the chroot'ed environment) to obtain the kernel image. Compress it with gzip and attach it to an email. Boot into your MacOS and download the email. You can use the MacGzip application to ungzip the kernel image and move it to the "Linux Kernels" folder under "System Folder". If you don't have MacGzip installed, you can download it from http://macinsearch.com/infomac/cmp/mac−gzip−111.html

Of course, if the kernel is small enough to fit on a floppy disk, and your Mac has a floppy drive, you can transfer it that way. Of if you have a ZIP drive at your disposal, you can transfer it on that medium.

---

# Testing the system

Now that all software has been installed, bootscripts have been written and the local network is setup, it's time for you to reboot your computer and test these new scripts to verify that they actually work. You first want to execute them manually from the /etc/init.d directory so you can fix the most obvious problems (typos, wrong paths and such). When those scripts seem to work just fine manually they should also work during a system start or shutdown. There's only one way to test that. Shutdown your system with shutdown –r now and reboot into LFS. After the reboot you will have a normal login prompt like you have on your normal Linux system (unless you use XDM or some sort of other Display Manger (like KDM – KDE's version of XDM).

# IV. Part IV – Appendixes

***Table of Contents***

*A. Package descriptions*
*B. Resources*

# Appendix A. Package descriptions

# Introduction

This appendix describes the following aspect of each and every package that is installed in this book:

- What every package contains
- What every program from a package does

The packages are listed in the same order as they are installed in chapter 5 (Intel system) or chapter 11 (PPC systems).

Most information about these packages (especially the descriptions of it) come from the man pages from those packages. I'm not going to print the entire man page, just the core elements to make you understand what a program does. If you want to know full details on a program, I suggest you start by reading the complete man page in addition to this appendix.

You will also find that certain packages are documented more in depth than others. The reason is that I just happen to know more about certain packages than I know about others. If you have anything to add on the following descriptions, please don't hesitate to email me. This list is going to contain an in depth description of every package installed, but I can't do this on my own. I have had help from various people but more help is needed.

Please note that currently only what a package does is described and not why you need to install it. That will be added later.

---

# Glibc

## Contents

The Glibc package contains the GNU C Library.

## Description

The C Library is a collection of commonly used functions in programs. This way a programmer doens't need to create his own functions for every single task. The most common things like writing a string to your screen are already present and at the disposal of the programmer.

The C library (actually almost every library) come in two flavours: dynamic ones and static ones. In short when a program uses a static C library, the code from the C library will be copied into the executable file. When a program uses a dynamic library, that executable will not contain the code from the C library, but instead a routine that loads the functions from the library at the time the program is run. This means a significant decrease in the file size of a program. If you don't understand this concept, you better read the documentation that comes with the C Library as it is too complicated to explain here in one or two lines.

# Linux kernel

## Contents

The Linux kernel package contains the Linux kernel.

## Description

The Linux kernel is at the core of every Linux system. It's what makes Linux tick. When you turn on your computer and boot a Linux system, the very first piece of Linux software that gets loaded is the kernel. The kernel initializes the system's hardware components such as serial ports, parallel ports, sound cards, network cards, IDE controllers, SCSI controllers and a lot more. In a nutshell the kernel makes the hardware available so that the software can run.

# Ed

## Contents

The Ed package contains the ed program.

## Description

Ed is a line−oriented text editor.  It is used to create, display, modify and otherwise manipulate text files.

# Patch

## Contents

The Patch package contains the patch program.

## Description

The patch program modifies a file according to a patch file. A patch file usually is a list created by the diff program that contains instructions on how an original file needs to be modified. Patch is used a lot for source code patches since it saves time and space. Imagine you have a package that is 1MB in size. The next version of that package only has changes in two files of the first version. You can ship an entirely new package of 1MB or provide a patch file of 1KB which will update the first version to make it identical to the second version. So if you have downloaded the first version already, a patch file can save you a second large download.

# GCC

## Contents

The GCC package contains compilers, preprocessors and the GNU C++ Library.

---

## Description

### Compiler

A compiler translates source code in text format to a format that a computer understands. After a source code file is compiled into an object file, a linker will create an executable file from one or more of these compiler generated object files.

---

### Pre−processor

A pre−processor pre−processes a source file, such as including the contents of header files into the source file. You generally don't do this yourself to save yourself a lot of time. You just insert a line like #include <filename>. The pre−processor file insert the contents of that file into the source file. That's one of the things a pre−processor does.

---

### C++ Library

The C++ library is used by C++ programs. The C++ library contains functions that are frequently used in C++ programs. This way the programmer doens't have to write certain functions (such as writing a string of text to the screen) from scratch every time he creates a program.

---

# Bison

## Contents

The Bison package contains the bison program.

## Description

Bison is a parser generator, a replacement for YACC. YACC stands for Yet Another Compiler Compiler. What is Bison then? It is a program that generates a program that analyses the structure of a textfile. Instead of writing the actual program you specify how things should be connected and with those rules a program is constructed that analyses the textfile.

There are alot of examples where structure is needed and one of them is the calculator.

Given the string :

```
1 + 2 * 3
```

You can easily come to the result 7. Why ? Because of the structure. You know how to interpretet the string. The computer doesn't know that and Bison is a tool to help it understand by presenting the string in the following way to the compiler:

```
  +
 / \
1   *
   / \
  2   3
```

You start at the bottom of a tree and you come across the numbers 2 and 3 which are joined by the multiplication symbol, so the computers multiplies 2 and 3. The result of that multiplication is remembered and the next thing that the computer sees is the result of 2*3 and the number 1 which are joined by the add symbol. Adding 1 to the previous result makes 7. In calculating the most complex calculations can be broken down in this tree format and the computer just starts at the bottom and works it's way up to the top and comes with the correct answer. Of course, Bison isn't only used for calculators alone.

# Mawk

## Contents

The Mawk package contains the mawk program.

---

## Description

### gawk

Mawk is an interpreter for the AWK Programming Language. The AWK language is useful for manipulation of data files, text retrieval and processing, and for prototyping and experimenting with algorithms.

---

# Findutils

## Contents

The Findutils package contains the find, locate, updatedb and xargs programs.

## Description

### Find

The find program searches for files in a directory hierarchy which match a certain criteria. If no criteria is given, it lists all files in the current directory and it's subdirectories.

### Locate

Locate scans a database which contain all files and directories on a filesystem. This program lists the files and directories in this database matching a certain criteria. If you're looking for a file this program will scan the database and tell you exactly where the files you requested are located. This only makes sense if your locate database is fairly up−to−date else it will provide you with out−of−date information.

### Updatedb

The updatedb program updates the locate database. It scans the entire file system (including other file system that are currently mounted unless you specify it not to) and puts every directory and file it finds into the database that's used by the locate program which retrieves this information. It's a good practice to update this database once a day so that you are ensured of a database that is up−to−date.

### Xargs

The xargs command applies a command to a list of files. If you need to perform the same command on multiple files, you can create a file that contains all these files (one per line) and use xargs to perform that command on the list.

# Ncurses

## Contents

The Ncurses package contains the ncurses, panel, menu and form libraries. It also contains the tic, infocmp, clear, tput, toe and tset programs.

---

## Description

### The libraries

The libraries that make up the Ncurses library are used to display text (often in a fancy way) on your screen. An example where ncurses is used is in the kernel's "make menuconfig" process. The libraries contain routines to create panels, menu's, form and general text display routines.

---

### Tic

Tic is the terminfo entry−description compiler. The program translates a terminfo file from source format into the binary format for use with the ncurses library routines. Terminfo files contain information about the capabilities of your terminal.

---

### Infocmp

The infocmp program can be used to compare a binary terminfo entry with other terminfo entries, rewrite a terminfo description to take advantage of the use= terminfo field, or print out a terminfo description from the binary file (term) in a variety of formats (the opposite of what tic does).

---

### clear

The clear program clears your screen if this is possible. It looks in the environment for the terminal type and then in the terminfo database to figure out how to clear the screen.

---

### tput

The tput program uses the terminfo database to make the values of terminal−dependent capabilities and information available to the shell, to initialize or reset the terminal, or return the long name of the requested terminal type.

---

## toe

The toe program lists all available terminal types by primary name with descriptions.

---

## tset

The Tset program initializes terminals so they can be used, but it's not widely used anymore. It's provided for 4.4BSD compatibility.

---

# Less

## Contents

The Less package contains the less program

## Description

The less program is a file pager (or text viewer). It displays the contents of a file with the ability to scroll. Less is an improvement on the common pager called "more". Less has the ability to scroll backwards through files as well and it doesn't need to read the entire file when it starts, which makes it faster when you are reading large files.

# Groff

## Contents

The Groff packages contains the addftinfo, afmtodit, eqn, grodvi, groff, grog, grohtml, grolj4, grops, grotty, hpftodit, indxbib, lkbib, lookbib, neqn, nroff, pfbtops, pic, psbb, refer, soelim, tbl, tfmtodit and troff programs.

---

## Description

### addftinfo

addftinfo reads a troff font file and adds some additional font−metric information that is used by the groff system.

---

### afmtodit

afmtodit creates a font file for use with groff and grops.

---

### eqn

eqn compiles descriptions of equations embedded within troff input files into commands that are understood by troff.

---

### grodvi

grodvi is a driver for groff that produces TeX dvi format.

---

### groff

groff is a front−end to the groff document formatting system. Normally it runs the troff program and a postprocessor appropriate for the selected device.

---

### grog

grog reads files and guesses which of the groff options −e, −man, −me, −mm, −ms, −p, −s, and −t are required for printing files, and prints the groff command including those options on the standard output.

---

## grohtml

grohtml translates the output of GNU troff to html

---

## grolj4

grolj4 is a driver for groff that produces output in PCL5 format suitable for an HP Laserjet 4 printer.

---

## grops

grops translates the output of GNU troff to PostScript.

---

## grotty

grotty translates the output of GNU troff into a form suitable for typewriter−like devices.

---

## hpftodit

hpftodit creates a font file for use with groff −Tlj4 from an HP tagged font metric file.

---

## indxbib

indxbib makes an inverted index for the bibliographic databases a specified file for use with refer, lookbib, and lkbib.

---

## lkbib

lkbib searches bibliographic databases for references that contain specified keys and prints any references found on the standard output.

---

## lookbib

lookbib prints a prompt on the standard error (unless the standard input is not a terminal), reads from the standard input a line containing a set of keywords, searches the bibliographic databases in a specified file for references containing those keywords, prints any references found on the standard output, and repeats this process until the end of input.

---

## neqn

It is currently not known what neqn is and what it does.

## nroff

The nroff script emulates the nroff command using groff.

## pfbtops

pfbtops translates a PostScript font in .pfb format to ASCII.

## pic

pic compiles descriptions of pictures embedded within troff or TeX input files into commands that are understood by TeX or troff.

## psbb

psbb reads a file which should be a PostScript document conforming to the Document Structuring conventions and looks for a %%BoundingBox comment.

## refer

refer copies the contents of a file to the standard output, except that lines between .[ and .] are interpreted as citations, and lines between .R1 and .R2 are interpreted as commands about how citations are to be processed.

## soelim

soelim reads files and replaces lines of the form *.so file* by the contents of *file*.

## tbl

tbl compiles descriptions of tables embedded within troff input files into commands that are understood by troff.

## tfmtodit

tfmtodit creates a font file for use with **`groff -Tdvi`**

## troff

troff is highly compatible with Unix troff. Usually it should be invoked using the groff command, which will also run preprocessors and postprocessors in the appropriate order and with the appropriate options.

# Man

## Contents

The Man package contains the man, apropos whatis and makewhatis programs.

---

## Description

### man

man formats and displays the on−line manual pages.

---

### apropos

apropos searches a set of database files containing short descriptions of system commands for keywords and displays the result on the standard output.

---

### whatis

whatis searches a set of database files containing short descriptions of system commands for keywords and displays the result on the standard output. Only complete word matches are displayed.

---

### makewhatis

makewhatis reads all the manual pages contained in given sections of manpath or the preformatted pages contained in the given sections of catpath. For each page, it writes a line in the whatis database; each line consists of the name of the page and a short description, separated by a dash. The description is extracted using the content of the NAME section of the manual page.

---

# Perl

## Contents

The Perl package contains Perl – Practical Extraction and Report Language

## Description

Perl combines the features and capabilities of C, awk, sed and sh into one powerful programming language.

# M4

## Contents

The M4 package contains the M4 processor

## Description

M4 is a macro processor. It copies input to output expanding macros as it goes. Macros are either builtin or user−defined and can take any number of arguments. Besides just doing macro expansion m4 has builtin functions for including named files, running UNIX commands, doing integer arithmetic, manipulating text in various ways, recursion, etc. M4 can be used either as a front−end to a compiler or as a macro processor in its own right.

# Texinfo

## Contents

The Texinfo package contains the info, install−info, makeinfo, texi2dvi and texindex programs

---

## Description

### info

The info program reads Info documents, usually contained in your /usr/doc/info directory. Info documents are like man(ual) pages, but they tend to be more in depth than just explaining the options to a program.

---

### install−info

The install−info program updates the info entries. When you run the info program a list with available topics (ie: available info documents) will be presented. The install−info program is used to maintain this list of available topics. If you decice to remove info files manually, you need to delete the topic in the index file as well. This program is used for that. It also works the other way around when you add info documents.

---

### makeinfo

The makeinfo program translates Texinfo source documents into various formats. Available formats are: info files, plain text and HTML.

---

### texi2dvi

The texi2dvi program prints Texinfo documents

---

### texindex

The texindex program is used to sort Texinfo index files.

---

# Autoconf

## Contents

The Autoconf package contains the autoconf, autoheader, autoreconf, autoscan, autoupdate and ifnames programs

---

## Description

### autoconf

Autoconf is a tool for producing shell scripts that automatically configure software source code packages to adapt to many kinds of UNIX−like systems. The configuration scripts produced by Autoconf are independent of Autoconf when they are run, so their users do not need to have Autoconf.

---

### autoheader

The autoheader program can create a template file of C #define statements for configure to use

---

### autoreconf

If you have a lot of Autoconf−generated configure scripts, the autoreconf program can save you some work. It runs autoconf (and autoheader, where appropriate) repeatedly to remake the Autoconf configure scripts and configuration header templates in the directory tree rooted at the current directory.

---

### autoscan

The autoscan program can help you create a configure.in file for a software package. autoscan examines source files in the directory tree rooted at a directory given as a command line argument, or the current directory if none is given. It searches the source files for common portability problems and creates a file configure.scan which is a preliminary configure.in for that package.

---

### autoupdate

The autoupdate program updates a configure.in file that calls Autoconf macros by their old names to use the current macro names.

---

### ifnames

ifnames can help when writing a configure.in for a software package. It prints the identifiers that the

package already uses in C preprocessor conditionals. If a package has already been set up to have some portability, this program can help you figure out what its configure needs to check for. It may help fill in some gaps in a configure.in generated by autoscan.

---

# Automake

## Contents

The Automake package contains the aclocal and automake programs

---

## Description

### aclocal

Automake includes a number of Autoconf macros which can be used in your package; some of them are actually required by Automake in certain situations. These macros must be defined in your aclocal.m4; otherwise they will not be seen by autoconf.

The aclocal program will automatically generate aclocal.m4 files based on the contents of configure.in. This provides a convenient way to get Automake−provided macros, without having to search around. Also, the aclocal mechanism is extensible for use by other packages.

---

### automake

To create all the Makefile.in's for a package, run the automake program in the top level directory, with no arguments. automake will automatically find each appropriate Makefile.am (by scanning configure.in) and generate the corresponding Makefile.in.

---

# Bash

## Contents

The Bash package contains the bash program

## Description

Bash is the Bourne−Again SHell, which is a widely used command interpreter on Unix systems. Bash is a program that reads from standard input, the keyboard. You type something and the program will evaluate what you have typed and do something with it, like running a program.

# Flex

## Contents

The Flex package contains the flex program

## Description

Flex is a tool for generating programs which regognize patterns in text. Pattern recognition is very useful in many applications. You set up rules what to look for and flex will make a program that looks for those patterns. The reason people use flex is that it is much easier to set up rules for what to look for than to write the actual program that finds the text.

# Binutils

## Description

The Binutils package contains the ld, as, ar, nm, objcopy, objdump, ranlib, size, strings, strip, c++filt, addr2line and nlmconv programs

---

## Description

### ld

ld combines a number of object and archive files, relocates their data and ties up symbol references. Often the last step in building a new compiled program to run is a call to ld.

---

### as

as is primarily intended to assemble the output of the GNU C compiler gcc for use by the linker ld.

---

### ar

The ar program creates, modifies, and extracts from archives. An archive is a single file holding a collection of other files in a structure that makes it possible to retrieve the original individual files (called members of the archive).

---

### nm

nm lists the symbols from object files.

---

### objcopy

objcopy utility copies the contents of an object file to another. objcopy uses the GNU BFD Library to read and write the object files. It can write the destination object file in a format different from that of the source object file.

---

### objdump

objdump displays information about one or more object files. The options control what particular information to display. This information is mostly useful to programmers who are working on the compilation tools, as opposed to programmers who just want their program to compile and work.

---

## ranlib

ranlib generates an index to the contents of an archive, and stores it in the archive. The index lists each symbol defined by a member of an archive that is a relocatable object file.

---

## size

size lists the section sizes −−and the total size−− for each of the object files objfile in its argument list. By default, one line of output is generated for each object file or each module in an archive.

---

## strings

For each file given, strings prints the printable character sequences that are at least 4 characters long (or the number specified with an option to the program) and are followed by an unprintable character. By default, it only prints the strings from the initialized and loaded sections of object files; for other types of files, it prints the strings from the whole file.

strings is mainly useful for determining the contents of non−text files.

---

## strip

strip discards all or specific symbols from object files. The list of object files may include archives. At least one object file must be given. strip modifies the files named in its argument, rather than writing modified copies under different names.

---

## c++filt

The C++ language provides function overloading, which means that you can write many functions with the same name (providing each takes parameters of different types). All C++ function names are encoded into a low−level assembly label (this process is known as mangling). The c++filt program does the inverse mapping: it decodes (demangles) low−level names into user−level names so that the linker can keep these overloaded functions from clashing.

---

## addr2line

addr2line translates program addresses into file names and line numbers. Given an address and an executable, it uses the debugging information in the executable to figure out which file name and line number are associated with a given address.

---

## nlmconv

nlmconv converts relocatable object files into the NetWare Loadable Module files, optionally reading header files for NLM header information.

# Bzip2

## Contents

The Bzip2 packages contains the bzip2, bunzip2, bzcat and bzip2recover programs.

---

## Description

### Bzip2

bzip2 compresses files using the Burrows−Wheeler block sorting text compression algorithm, and Huffman coding. Compression is generally considerably better than that achieved by more conventional LZ77/LZ78−based compressors, and approaches the performance of the PPM family of statistical compressors.

---

### Bunzip2

Bunzip2 decompresses files that are compressed with bzip2.

---

### bzcat

bzcat (or bzip2 −dc) decompresses all specified files to the standard output.

---

### bzip2recover

bzip2recover recovers data from damaged bzip2 files.

---

# Diffutils

## Contents

The Diffutils packagec contains the cmp, diff, diff3 and sdiff programs.

---

## Description

### cmp and diff

cmp and diff both compare two files and report their differences. Both programs have extra options which compare files in different situations.

---

### diff3

The difference between diff and diff3 is that diff comprares 2 files, diff3 compares 3 files.

---

### sdiff

sdiff merges two two files and interactively outputs the results.

---

# E2fsprogs

## Contents

The e2fsprogs package contains the chattr, lsattr, uuidgen, badblocks, debugfs, dumpe2fs, e2fsck, e2label, fsck, fsck.ext2, mke2fs, mkfs.ext2, mklost+found and tune2fs programs.

---

## Description

### chattr

chattr changes the file attributes on a Linux second extended file system.

---

### lsattr

lsattr lists the file attributes on a second extended file system.

---

### uuidgen

The uuidgen program creates a new universally unique identifier (UUID) using the libuuid library. The new UUID can reasonably be considered unique among all UUIDs created on the local system, and among UUIDs created on other systems in the past and in the future.

---

### badblocks

badblocks is used to search for bad blocks on a device (usually a disk partition).

---

### debugfs

The debugfs program is a file system debugger. It can be used to examine and change the state of an ext2 file system.

---

### dumpe2fs

dumpe2fs prints the super block and blocks group information for the filesystem present on a specified device.

---

## e2fsck and fsck.ext2

e2fsck is used to check a Linux second extended file system. fsck.ext2 does the same as e2fsck.

---

## e2label

e2label will display or change the filesystem label on the ext2 filesystem located on the specified device.

---

## fsck

fsck is used to check and optionally repair a Linux file system.

---

## mke2fs and mkfs.ext2

mke2fs is used to create a Linux second extended file system on a device (usually a disk partition). mkfs.ext2 does the same as mke2fs.

---

## mklost+found

mklost+found is used to create a lost+found directory in the current working directory on a Linux second extended file system. mklost+found pre−allocates disk blocks to the directory to make it usable by e2fsck.

---

## tune2fs

tune2fs adjusts tunable filesystem parameters on a Linux second extended filesystem.

---

# File

## Contents

The File package contains the file program.

---

## Description

File tests each specified file in an attempt to classify it. There are three sets of tests, performed in this order: filesystem tests, magic number tests, and language tests. The first test that succeeds causes the file type to be printed.

---

# Fileutils

## Contents

The Fileutils package contains the chgrp, chmod, chown, cp, dd, df, dir, dircolors, du, install, ln, ls, mkdir, mkfifo, mknod, mv, rm, rmdir, sync, touch and vdir programs.

---

## Description

### chgrp

chgrp changes the group ownership of each given file to the named group, which can be either a group name or a numeric group ID.

---

### chmod

chmod changes the permissions of each given file according to mode, which can be either a symbolic representation of changes to make, or an octal number representing the bit pattern for the new permissions.

---

### chown

chown changes the user and/or group ownership of each given file.

---

### cp

cp copies files from one place to another.

---

### dd

dd copies a file (from the standard input to the standard output, by default) with a user−selectable blocksize, while optionally performing conversions on it.

---

### df

df displays the amount of disk space available on the filesystem containing each file name argument. If no file name is given, the space available on all currently mounted filesystems is shown.

---

## ls, dir and vdir

dir and vdir are versions of ls with different default output formats. These programs list each given file or directory name. Directory contents are sorted alphabetically. For ls, files are by default listed in columns, sorted vertically, if the standard output is a terminal; otherwise they are listed one per line. For dir, files are by default listed in columns, sorted vertically. For vdir, files are by default listed in long format.

---

## dircolors

dircolors outputs commands to set the LS_COLOR environment variable. The LS_COLOR variable is use to change the default color scheme used by ls and related utilities.

---

## du

du displays the amount of disk space used by each argument and for each subdirectory of directory arguments.

---

## install

install copies files and sets their permission modes and, if possible, their owner and group.

---

## ln

ln makes hard or soft (symbolic) links between files.

---

## mkdir

mkdir creates directories with a given name.

---

## mkfifo

mkfifo creates a FIFO with each given name.

---

## mknod

mknod creates a FIFO, character special file, or block special file with the given file name.

---

## mv

mv moves files from one directory to another or renames files, depending on the arguments given to mv.

---

## rm

rm removes files or directories.

---

## rmdir

rmdir removes directories, if they are empty.

---

## sync

sync forces changed blocks to disk and updates the super block.

---

## touch

touch changes the access and modification times of each given file to the current time. Files that do not exist are created empty.

---

# Gettext

## Contents

The gettext package contains the gettext, gettextize, msgcmp, msgcomm, msgfmt, msgmerge, msgunfmt and xgettext programs.

---

## Description

### gettext

The gettext package is used for internationalization (also known as i18n) and for localization (also known as l10n). Programs can be compiled with Native Language Support (NLS) which enable them to output messages in your native language rather than in the default English languge.

---

# Grep

## Contents

The grep package contains the egrep, fgrep and grep programs.

---

## Description

### egrep

egrep prints lines from files matching an extended regular expression pattern.

---

### fgrep

fgrep prints lines from files matching a list of fixed strings, separated by newlines, any of which is to be matched.

---

### grep

grep prints lines from files matching a basic regular expression pattern.

---

# Gzip

## Contents

The Gzip package contains the gunzip, gzexe, gzip, zcat, zcmp, zdiff, zforece, zgrep, zmore and znew programs.

---

## Description

### gunzip

gunzip decompresses files that are compressed with gzip.

---

### gzexe

gzexe allows you to compress executables in place and have them automatically uncompress and execute when you run them (at a penalty in performance).

---

### gzip

gzip reduces the size of the named files using Lempel−Ziv coding (LZ77).

---

### zcat

zcat uncompresses either a list of files on the command line or its standard input and writes the uncompressed data on standard output

---

### zcmp

zcmp invokes the cmp program on compressed files.

---

### zdiff

zdiff invokes the diff program on compressed files.

---

### zforce

zforce forces a .gz extension on all gzip files so that gzip will not compress them twice. This can be useful for files with names truncated after a file transfer.

## zgrep

zgrep invokes the grep program on compressed files.

## zmore

Zmore is a filter which allows examination of compressed or plain text files one screenful at a time on a soft−copy terminal (similar to the more program).

## znew

Znew recompresses files from .Z (compress) format to .gz (gzip) format.

# Ld.so

## Contents

From the Ld.so package we're using the ldconfig and ldd programs.

## Description

### ldconfig

ldconfig creates the necessary links and cache (for use by the run−time linker, ld.so) to the most recent shared libraries found in the directories specified on the command line, in the file /etc/ld.so.conf, and in the trusted directories (/usr/lib and /lib). ldconfig checks the header and file names of the libraries it encounters when determining which versions should have their links updated.

### ldd

ldd prints the shared libraries required by each program or shared library specified on the command line.

# Libtool

## Contents

The Libtool package contains the libtool and libtoolize programs. It also contains the ltdl library.

## Description

### libtool

Libtool provides generalized library−building support services.

### libtoolize

libtoolize provides a standard way to add libtool support to your package.

### ltdl library

Libtool provides a small library, called `libltdl', that aims at hiding the various difficulties of dlopening libraries from programmers.

# Bin86

## Contents

The Bin86 contains the as86, as86_encap, ld86, objdump86, nm86 and size86 programs.

## Description

### as86

as86 is an assembler for the 8086...80386 processors.

### as86_encap

as86_encap is a shell script to call as86 and convert the created binary into a C file prog.v to be included in or linked with programs like boot block installers.

### ld86

ld86 understands only the object files produced by the as86 assembler, it can link them into either an impure or a separate I&D executable.

### objdump86

No description available.

### nm86

No description available.

### size86

No description available.

# Lilo

## Contents

The Lilo package contains the lilo program.

## Description

lilo installs the Linux boot loader which is used to start a Linux system.

# Make

## Contents

The Make package contains the make program.

---

## Description

make determine automatically which pieces of a large program need to be recompiled, and issue the commands to recompile them.

---

# Shellutils

## Contents

The Shellutils package contains the basename, chroot, date, dirname, echo, env, expr, factor, false, groups, hostid, hostname, id, logname, nice, nohup, pathchk, pinky, printenv, printf, pwd, seq, sleep, stty, su, tee, test, true, tty, uname, uptime, users, who, whoami and yes programs.

---

## Description

### basename

basename strips directory and suffixes from filenames.

---

### chroot

chroot runs a command or interactive shell with special root directory.

---

### date

date displays the current time in a specified format, or sets the system date.

---

### dirname

dirname strips non−directory suffixes from file name.

---

### echo

echo displays a line of text.

---

### env

env runs a program in a modified environment.

---

### expr

expr evaluates expressions.

---

## factor

factor prints the prime factors of all specified integer numbers.

## false

false always exits with a status code indicating failure.

## groups

groups prints the groups a user is in.

## hostid

hostid prints the numeric identifier (in hexadecimal) for the current host.

## hostname

hostname sets or prints the name of the current host system

## id

id prints the real and effective UIDs and GIDs of a user or the current user.

## logname

logname prints the current user's login name.

## nice

nice runs a program with modified scheduling priority.

## nohup

nohup runs a command immune to hangups, with output to a non−tty

## pathchk

pathchk checks whether file names are valid or portable.

## pinky

pinky is a lightweight finger utility which retrieves information about a certain user

## printenv

printenv prints all or part of the environment.

## printf

printf formats and print data (the same as the printf C function).

## pwd

pwd prints the name of the current/working directory

## seq

seq prints numbers in a certain range with a certain increment.

## sleep

sleep delays for a specified amount of time.

## stty

stty changes and prints terminal line settings.

## su

su runs a shell with substitute user and group IDs

## tee

tee reads from standard input and write to standard output and files.

## test

test checks file types and compares values.

## true

True always exitx with a status code indicating success.

## tty

tty prints the file name of the terminal connected to standard input.

## uname

uname prints system information.

## uptime

uptime tells how long the system has been running.

## users

users prints the user names of users currently logged in to the  current host.

## who

who shows who is logged on.

## whoami

whoami prints your effective userid.

## yes

yes outputs a string repeatedly until killed.

# Shadow Password Suite

## Contents

The Shadow Password Suite contains the chage, chfn, chsh, expiry, faillog, gpasswd, lastlog, login, newgrp, passwd, sg, su, chpasswd, dpasswd, groupadd, groupdel, groupmod, grpck, grpconv, grpunconv, logoutd, mkpasswd, newusers, pwck, pwconv, pwunconv, useradd, userdel, usermod and vipw programs.

---

## Description

### chage

chage changes the number of days between password changes and the date of the last password change.

---

### chfn

chfn changes user fullname, office number, office extension, and home phone number information for a user's account.

---

### chsh

chsh changes the user login shell.

---

### expiry

It's currently unknown what this program is for.

---

### faillog

faillog formats the contents of the failure log,/var/log/faillog, and maintains failure counts and limits.

---

### gpasswd

gpasswd is used to administer the /etc/group file

---

### lastlog

lastlog formats and prints the contents of the last login log, /var/log/lastlog. The login−name, port, and last login time will be printed.

## login

login is used to establish a new session with the system.

## newgrp

newgrp is used to change the current group ID during a login session.

## passwd

passwd changes passwords for user and group accounts.

## sg

sg executes command as a different group ID.

## su

Change the effective user id and group id to that of a user. This replaces the su programs that's installed from the Shellutils package.

## chpasswd

chpasswd reads a file of user name and password pairs from standard input and uses this information to update a group of existing users.

## dpasswd

dpasswd adds, deletes, and updates dialup passwords for user login shells.

## groupadd

The groupadd command creates a new group account using the values specified on the command line and the default values from the system.

## groupdel

The groupdel command modifies the system account files, deleting all entries that refer to group.

## groupmod

The groupmod command modifies the system account files to reflect the changes that are specified on the command line.

## grpck

grpck verifies the integrity of the system authentication information.

## grpconv

grpunconv converts to shadow group files from normal group files.

## grpunconv

grpunconv converts from shadow group files to normal group files.

## logoutd

logoutd enforces the login time and port restrictions specified in /etc/porttime.

## mkpasswd

mkpasswd reads a file in the format given by the flags and converts it to the corresponding database file format.

## newusers

newusers reads a file of user name and cleartext password pairs and uses this information to update a group of existing users or to create new users.

## pwck

pwck verifies the integrity of the system authentication information.

## pwconv

pwconv converts to shadow passwd files from normal passwd files.

---

## pwunconv

pwunconv converts from shadow passwd files to normal files.

---

## useradd

useradd creates a new user or update default new user information.

---

## userdel

userdel modifies the system account files, deleting all entries that refer to a specified login name.

---

## usermod

usermod modifies the system account files to reflect the changes that are specified on the command line.

---

## vipw and vigr

vipw and vigr will edit the files /etc/passwd and /etc/group, respectively. With the –s flag, they will edit the shadow versions of those files, /etc/shadow and /etc/gshadow, respectively.

---

# Modutils

## Contents

The Modutils package contains the depmod, genksyms, insmod, insmod_ksymoops_clean, kerneld, kernelversion, ksyms, lsmod, modinfo, modprobe and rmmod programs.

---

## Description

### depmod

depmod handles dependency descriptions for loadable kernel modules.

---

### genksyms

genksyms reads (on standard input) the output from gcc −E source.c and generates a file containing version information.

---

### insmod

insmod installs a loadable module in the running kernel.

---

### insmod_ksymoops_clean

insmod_ksymoops_clean deletes saved ksyms and modules not accessed in 2 days.

---

### kerneld

kerneld performs kernel action in user space (such as on−demand loading of modules)

---

### kernelversion

kernelversion reports the major version of the running kernel.

---

### ksyms

ksyms displays exported kernel symbols.

---

## lsmod

lsmod shows information about all loaded modules.

---

## modinfo

modinfo examines an object file associated with a kernel module and displays any information that it can glean.

---

## modprobe

Modprobe uses a Makefile−like dependency file, created by depmod, to automatically load the relevant module(s) from the set of modules available in predefined directory trees.

---

## rmmod

rmmod unloads loadable modules from the running kernel.

---

# Procinfo

## Contents

The Procinfo package contains the procinfo program.

---

## Description

procinfo gathers some system data from the /proc directory and prints it nicely formatted on the standard output device.

---

# Procps

## Contents

The Procps package contains the free, kill, oldps, ps, skill, snice, sysctl, tload, top, uptime, vmstat, w and watch programs.

---

## Description

### free

free displays the total amount of free and used physical and swap memory in the system, as well as the shared memory and buffers used by the kernel.

---

### kill

kills sends signals to processes.

---

### oldps and ps

ps gives a snapshot of the current processes.

---

### skill

skill sends signals to process matching a criteria.

---

### snice

snice changes the scheduling priority for process matching a criteria.

---

### sysctl

sysctl modifies kernel parameters at runtime.

---

### tload

tload prints a graph of the current system load average to the specified tty (or the tty of the tload process if none is specified).

---

## top

top provides an ongoing look at processor activity in real time.

---

## uptime

uptime gives a one line display of the following information: the current time, how long the system has been running, how many users are currently logged on, and the system load averages for the past 1, 5, and 15 minutes.

---

## vmstat

vmstat reports information about processes, memory, paging, block IO, traps, and cpu activity.

---

## w

w displays information about the users currently on the machine, and their processes.

---

## watch

watch runs command repeatedly, displaying its output (the first screenfull).

---

# Vim

## Contents

The Vim package contains the ctags, etags, ex, gview, gvim, rgview, rgvim, rview, rvim, view, vim, vimtutor and xxd programs.

---

## Description

### ctags

ctags generate tag files for source code.

---

### etags

etags does the same as ctags but it can generate cross reference files which list information about the various source objects found in a set of lanugage files.

---

### ex

ex starts vim in Ex mode.

---

### gview

gview is the GUI version of view.

---

### gvim

gvim is the GUI version of vim.

---

### rgview

rgview is teh GUI version of rview.

---

### rgvim

rgvim is the GUI version of rvim.

---

## rview

rview is a restricted version of view. No shell commands can be started and Vim can't be suspended.

## rvim

rvim is the restricted version of vim. No shell commands can be started and Vim can't be suspended.

## view

view starts vim in read−only mode.

## vim

vim starts vim in the normal, default way.

## vimtutor

vimtutor starts the Vim tutor.

## xxd

xxd makes a hexdump or does the reverse.

# Psmisc

## Contents

The Psmisc package contains the fuser, killall and pstree programs.

## Description

### fuser

fuser displays the PIDs of processes using the specified files or file systems.

### killall

killall sends a signal to all processes running any of the specified commands.

### pstree

pstree shows running processes as a tree.

# Sed

## Contents

The Sed package contains the sed program.

## Description

sed is a stream editor. A stream editor is used to perform basic text transformations on an input stream (a file or input from a pipeline).

# Sysklogd

## Contents

The Sysklogd package contains the klogd and syslogd programs.

---

## Description

### klogd

klogd is a system daemon which intercepts and logs Linux kernel messages.

---

### syslogd

Syslogd provides a kind of logging that many modern programs use.Every logged message contains at least a time and a hostname field, normally a program name field, too, but that depends on how trusty the logging program is.

---

# Sysvinit

## Contents

The Sysvinit package contains the pidof, last, lastb, mesg, utmpdump, wall, halt, init, killall5, poweroff, reboot, runlevel, shutdown, sulogin and telinit programs.

---

## Description

### pidof

Pidof finds the process id's (pids) of the named programs and prints those id's on standard output.

---

### last

last searches back through the file /var/log/wtmp (or the file designated by the −f flag) and displays a list of all users logged in (and out) since that file was created.

---

### lastb

lastb is the same as last, except that by default it shows a log of the file /var/log/btmp, which contains all the bad login attempts.

---

### mesg

Mesg controls the access to your terminal by others. It's typically used to allow or disallow other users to write to your terminal.

---

### utmpdump

utmpdumps prints the content of a file (usually /var/run/utmp) on standard output in a user friendly format.

---

### wall

Wall sends a message to everybody logged in with their mesg permission set to yes.

---

## halt

Halt notes that the system is being brought down in the file /var/log/wtmp, and then either tells the kernel to halt, reboot or poweroff the system. If halt or reboot is called when the system is not in runlevel 0 or 6, shutdown will be invoked instead (with the flag −h or −r).

---

## init

Init is the parent of all processes. Its primary role is to create processes from a script stored in the file /etc/inittab. This file usually has entries which cause init to spawn gettys on each line that users can log in. It also controls autonomous processes required by any particular system.

---

## killall5

killall5 is the SystemV killall command. It sends a signal to all processes except the processes in its own session, so it won't kill the shell that is running the script it was called from.

---

## poweroff

poweroff is equivalent to shutdown −h −p now. It halts the computer and switches off the computer (when using an APM compliant BIOS and APM is enabled in the kernel).

---

## reboot

reboot is equivalent to shutdown −r now. It reboots the computer.

---

## runlevel

Runlevel reads the system utmp file (typically /var/run/utmp) to locate the runlevel record, and then prints the previous and current system runlevel on its standard output, separated by a single space.

---

## shutdown

shutdown brings the system down in a secure way. All logged−in users are notified that the system is going down, and login is blocked.

---

## sulogin

sulogin is invoked by init when the system goes into single user mode (this is done through an entry in /etc/inittab). Init also tries to execute sulogin when it is passed the −b flag from the bootmonitor (eg, LILO).

## telinit

telinit sends appropriate signals to init, telling it which runlevel to change to.

# Tar

## Contents

The tar package contains the tar and rmt programs.

---

## Description

### tar

tar is an archiving program designed to store and extract files from an archive file known as a tarfile.

---

### rmt

rmt is a program used by the remote dump and restore programs in manipulating a magnetic tape drive through an interprocess communication connection.

---

# Textutils

## Contents

The Textutils package contains the cat, cksum, comm, split, cut, expand, fmt, fold, head, join, md5sum, nl, od, paste, pr, ptx, sort, split, sum, tac, tail, tr, tsort, unexpand, uniq and wc programs.

---

## Description

### cat

cat concatenates file(s) or standard input to standard output.

---

### cksum

cksum prints CRC checksum and byte counts of each specified file.

---

### comm

comm compares two sorted files line by line.

---

### csplit

cplit outputs pieces of a file separated by (a) pattern(s) to files xx01, xx02, ..., and outputs byte counts of each piece to standard output.

---

### cut

cut prints selected parts of lines from specified files to standard output.

---

### expand

expand converts tabs in files to spaces, writing to standard output.

---

### fmt

fmt reformats each paragraph in the specified file(s), writing to standard output.

---

## fold

fold wraps input lines in each specified file (standard input by default), writing to standard output.

## head

Print first xx (10 by default) lines of each specified file to standard output.

## join

join joins lines of two files on a common field.

## md5sum

md5sum prints or checks MD5 checksums.

## nl

nl writes each specified file to standard output, with line numbers added.

## od

od writes an unambiguous representation, octal bytes by default, of a specified file to standard output.

## paste

paste writes lines consisting of the sequentially corresponding lines from each specified file, separated by TABs, to standard output.

## pr

pr paginates or columnates files for printing.

## ptx

ptx produces a permuted index of file contents.

## sort

sort writes sorted concatenation of files to standard output.

## split

split outputs fixed−size pieces of an input file to PREFIXaa, PREFIXab, ...

## sum

sum prints checksum and block counts for each specified file.

## tac

tac writes each specified file to standard output, last line first.

## tail

tail print the last xx (10 by default) lines of each specified file to standard output.

## tr

tr translates, squeezes, and/or deletes characters from standard input, writing to standard output.

## tsort

tsort writes totally ordered lists consistent with the partial ordering in specified files.

## unexpand

unexpand converts spaces in each file to tabs, writing to standard output.

## uniq

uniq discards all but one of successive identical lines from files or standard input and writes to files or standard output.

## wc

wc prints line, word, and byte counts for each specified file, and a total line if more than one file is specified.

---

# Util Linux

## Contents

The Util−linux package contains the arch, dmesg, kill, more, mount, umount, agetty, blockdev, cfdisk, ctrlaltdel, elvtune, fdisk, fsck.minix, hwclock, kbdrate, losetup, mkfs, mkfs.bfs, mkfs.minix, mkswap, sfdisk, swapoff, swapon, cal, chkdupexe, col, colcrt, colrm, column, cytune, ddate, fdformat, getopt, hexdump, ipcrm, ipcs, logger, look, mcookie, namei, rename, renice, rev, script, setfdprm, setsid, setterm, ul, whereis, write, ramsize, rdev, readprofile, rootflags, swapdev, tunelp and vidmode programs.

## Description

### arch

arch prints the machine architecture.

### dmesg

dmesg is used to examine or control the kernel ring buffer (boot messages from the kernel).

### kill

kill sends a specified signal to the specified process.

### more

more is a filter for paging through text one screenful at a time.

### mount

mount mounts a filesystem from a device to a directory (mount point).

### umount

umount unmounts a mounted filesystem.

## agetty

agetty opens a tty port, prompts for a login name and invokes the /bin/login command.

## blockdev

No description available.

## cfdisk

cfdisk is an libncurses based disk partition table manipulator.

## ctrlaltdel

ctrlaltdel sets the function of the CTRL+ALT+DEL key combination (hard or soft reset).

## elvtune

elvtune allows to tune the I/O elevator per blockdevice queue basis.

## fdisk

fdisk is a disk partition table manipulator.

## fsck.minix

fsck.minix performs a consistency check for the Linux MINIX filesystem.

## hwclock

hwclock queries and sets the hardware clock (Also called the RTC or BIOS clock).

## kbdrate

kbdrate resets the keyboard repeat rate and delay time.

## losetup

losetup sets up and controls loop devices.

## mkfs

mkfs builds a Linux filesystem on a device, usually a harddisk partition.

## mkfs.bfs

mkfs.bfs creates a SCO bfs file system on a device, usually a harddisk partition.

## mkfs.minix

mkfs.minix creates a Linux MINIX filesystem on a device, usually a harddisk partition.

## mkswap

mkswap sets up a Linux swap area on a device or in a file.

## sfdisk

sfdisk is a disk partition table manipulator.

## swapoff

swapoff disables devices and files for paging an swapping.

## swapon

swapon enables devices and files for paging and swapping.

## cal

cal displays a simple calender.

## chkdupexe

chkdupexe finds duplicate executables.

## col

col filters reverse line feeds from input.

## colcrt

colcrt filters nroff output for CRT previewing.

## colrm

colrm removes columns from a file.

## column

column columnates lists.

## cytune

cytune queries and modifies the interruption threshold for the Cyclades driver.

## ddate

ddate converts Gregorian dates to Discordian dates.

## fdformat

fdformat low−level formats a floppy disk.

## getopt

getops parses command options the same way as the getopt C command.

## hexdump

hexdump displays specified files, or standard input, in a user specified format (ascii, decimal, hexadecimal, octal).

---

## ipcrm

ipcrm removes a specified resource.

---

## ipcs

ipcs provides information on ipc facilities.

---

## logger

logger makes entries in the system log.

---

## look

look displays lines beginning with a given string.

---

## mcookie

mcookie generates magic cookies for xauth.

---

## namei

namei follows a pathname until a terminal point is found.

---

## rename

rename renames files.

---

## renice

renice alters priority of running processes.

---

## rev

rev reverses lines of a file.

## script

script makes typescript of terminal session.

## setfdprm

setfdprm sets user−provides floppy disk parameters.

## setsid

setsid runs programs in a new session.

## setterm

setterm sets terminal attributes.

## ul

ul reads a file and translates occurences of underscores to the sequence which indicates underlining for the terminal in use.

## whereis

whereis locates a binary, source and manual page for a command.

## write

write sends a message to another user.

## ramsize

ramsize queries and sets RAM disk size.

## rdev

rdev queries and sets image root device, swap device, RAM disk size, or video mode.

## readprofile

readprofile reads kernel profiling information.

## rootflags

rootflags queries and sets extra information used when mounting root.

## swapdev

swapdev queries and sets swap device.

## tunelp

tunelp sets various paramters for the lp device.

## vidmode

vidmode queries and sets the video mode.

# Console−tools

## Contents

The Console−tools package contains the charset, chvt, consolechars, deallocvt, dumpkeys, fgconsole, fix_bs_and_del, font2psf, getkeycodes, kbd_mode, loadkeys, loadunimap, mapscrn, mk_modmap, openvt, psfaddtable, psfgettable, psfstriptable, resizecons, saveunimap, screendump, setfont, setkeycodes, setleds, setmetamode, setvesablank, showcfont, showkey, splitfont, unicode_start, unicode_stop, vcstime, vt−is−URF8, writevt

## Description

### charset

charset sets an ACM for use in one of the G0/G1 charsets slots.

### chvt

chvt changes foreground virtual terminal.

### codepage

No description available.

### consolechars

consolechars loads EGA/VGA console screen fonts, screen font maps and/or application−charset maps.

### deallocvt

deallocvt deallocates unused virtual terminals.

### dumpkeys

dumpkeys dumps keyboard translation tables.

## fgconsole

fgconsole prints the number of the active virtual terminal.

## fix_bs_and_del

No description available.

## font2psf

No description available.

## getkeycodes

getkeycodes prints the kernel scancode−to−keycode mapping table.

## kbd_mode

kbd_mode reports or sets the keyboard mode.

## loadkeys

loadkeys loads keyboard translation tables.

## loadunimap

No description available.

## mapscrn

No description available.

## mk_modmap

No description available.

## openvt

openvt starts a program on a new virtual terminal.

## psfaddtable

psfaddtable adds a Unicode character table to a console font.

## psfgettable

psfgettable extracts the embedded Unicode character table from a console font.

## psfstriptable

psfstriptable removes the embedded Unicode character table from a console font.

## resizecons

resizecons changes the kernel idea of the console size.

## saveunimap

No description available.

## screendump

No description available.

## setfont

No description available.

## setkeycodes

setkeycodes loads kernel scancode−to−keycode mapping table entries.

## setleds

setleds sets the keyboard leds.

## setmetamode

setmetamode defines the keyboard meta key handling.

## setvesablank

No description available.

## showcfont

showcfont displays all character in the current screenfont.

## showkey

showkey examines the scancodes and keycodes sent by the keyboard.

## splitfont

No description available.

## unicode_start

unicode_start puts the console in Unicode mode.

## unicode_end

No description available.

## vcstime

No description available.

## vt−is−UTF8

vt−is−UTF8 checks whether the current virtual terminal is in UTF8− or byte−mode.

## writevt

No description available.

# Console−data

## Contents

The console−data package contains the data files that are used and needed by the console−tools package.

# Man−pages

## Contents

The Man−pages package contains various manual pages that don't come with the packages.

## Description

Examples of provided manual pages are the manual pages describing all the C and C++ functions, few important /dev/ files and more.

# Appendix B. Resources

# Introduction

A list of books, HOWTOs and other documents you might find useful to download or buy follows. This list is just a small list to start with. We hope to be able to expand this list in time as we come across more useful documents or books.

# Books

- Linux Network Administrator's Guide published by O'Reilly. ISBN:  1−56502−087−2
- Running Linux published by O'Reilly. ISBN: 1−56592−151−8

# HOWTOs and Guides

All of the following HOWTOs can be downloaded from the Linux Documentation Project site at http://www.linuxdoc.org

- Linux Network Administrator's Guide
- Powerup2Bash−HOWTO

# Other

- The various man and info pages that come with the packages